# **DRAFT Pond Siting Report**

# Widening Western Beltway (SR 429) Project

# **Development and Environment (PD&E) Study**

From Interstate 4 to Seidel Road (MP 0.5 to MP 11.5)

Osceola and Orange Counties, Florida

Financial Project ID (FPID) No. 446164-1 ETDM No.: 14446



Prepared By: RS&H, Inc. 1715 N. Westshore Blvd., Suite 600 Tampa, FL 33607

November 2022

#### POND SITING REPORT PD&E Study Widening Western Beltway from Interstate 4 to Seidel Road Florida's Turnpike Enterprise Financial Project ID 446164-1 November 2022

This DRAFT Pond Siting Report is based solely upon the information made available to or gathered by RS&H. RS&H does not assume responsibility for conditions, which did not come to knowledge, or conditions not recognized as unacceptable at the time this report was prepared. RS&H has performed these drainage calculations and recommendations in a manner consistent with sound practices and that level of care and skill normally exercised by members of the profession operating under similar circumstances.


This document and the information contained within have been prepared solely for the use of Florida's Turnpike Enterprise.

This report consists of the following parts:

Sections 1 through 11 Appendices A through F

I, Erik N. Scott, hereby certify that this report, as listed above, is true and correct, represents the described work and is in accordance with the requirements of this project.

This item has been digitally signed and sealed by



on the date adjacent to the seal.

Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

RS&H, Inc. 1715 N. Westshore Blvd., Suite 600 Tampa, Florida 33607 Erik N. Scott, P.E. No. 72944

### **EXECUTIVE SUMMARY**

The Florida Turnpike Enterprise (FTE), part of the Florida Department of Transportation (FDOT), is evaluating the widening of Florida's Turnpike (State Road (SR) 429) from Interstate 4 to Seidel Road, a distance of approximately 10 miles. The project is located in Osceola and Orange Counties, Florida. The vertical datum used for this project is the North American Vertical Datum of 1988 (NAVD-88). The datum shift from NGVD-29 is (-)0.87-ft, with NAVD-88 being the lower elevation of the two.

NAVD-88 = NGVD-29 + datum shift

Florida's Turnpike currently has a 4-lane typical section within the study limit. This PD&E study evaluates the widening of the mainline from 4-lanes to 8-lanes. The roadway is functionally classified as an Urban Principal Arterial – Freeway and Expressway and has a posted speed limit of 70 miles per hour (mph). The purpose of the project is to improve mobility on Florida's Turnpike mainline to accommodate current and future traffic volumes, as well as improve safety along SR 429.

The analysis presented in this report identifies the stormwater management needs for each of the 20 basins defined within the study area. For basins which required new stormwater management facilities, three potential stormwater management alternatives within the basin were identified. The preferred alternative for each basin and anticipated right-of-way needs associated with the preferred alternatives are outlined in **Table 1**. The evaluation matrix which contains the details of the analysis has been provided in **Appendix E**. It should be noted that the information contained herein is preliminary and will need to be refined once this project enters the design phase. As outlined in the report which follows, there is excess treatment and attenuation provided within the currently permitted stormwater management systems that should be accounted for when developing the stormwater management design during the design phase.

Basin	Preferred Alternative	Anticipated Right of Way Requirements (acres)	Total Cost
2A-2	1	12.42 <sup>1,2</sup>	\$6,426,744
FGB (Basin B)	3	4.80 <sup>1</sup>	\$1,048,101

 Table 1: Preferred Pond Alternatives and Anticipated Right-of-Way
 Image: Comparison of Compariso

1. Pond to be placed within remnant parcel of land being purchased for proposed roadway alignment.

2. A portion of proposed Pond 2A-2 will be located within the existing right-of-way.

# TABLE OF CONTENTS

Executive	Summary	i
Section 1	.0 – Introduction	1
Section 2	.0 – Project Description	1
Section 3	.0 – Data Collection	5
Section 4	.0 – Design Criteria	5
4.1	Rules & Regulations / Regulatory Agency Coordination	5
4.1.1	Water Quality Criteria	6
4.1.2	Water Quantity Criteria	6
4.2	Project-Specific Criteria	6
4.2.1	TMDL Requirements	7
4.2.2	Basin Management Action Plans (BMAPs)	7
Section 5	.0 – Environmental Look Around	7
Section 6	.0 – Existing & Proposed Conditions	8
6.1	Existing Drainage Conditions	8
6.1.1	Basin F-4	
6.1.2	Basin B-2	
6.1.3	Basin B-3	
6.1.4	Basin B-4	13
6.1.5	Basin B-5	13
6.1.6	Basin B-6	13
6.1.7	Basin 2A-2	13
6.1.8	Basin 2A-3	13
6.1.9	Basin 2B-1	14
6.1.1	0 Basin 2B-2	14
6.1.1	1 Basin 10	14
6.1.1	2 Basin 11	14
6.1.1	3 Basin 12	14
6.1.1	4 Basin 13	

6.1.15	Basin 14	. 15
6.1.16	Basin 15	. 15
6.1.17	Basin 1	. 15
6.1.18	Basin 2	. 15
6.1.19	Basin B (FGB)	. 15
6.1.20	Basin FL 530	. 16
6.2 Pro	posed Drainage Conditions	. 16
6.2.1	Basin F-4	. 17
6.2.2	Basin B-2	. 17
6.2.3	Basin B-3	. 18
6.2.4	Basin B-4	. 19
6.2.5	Basin B-5	. 19
6.2.6	Basin B-6	. 19
6.2.7	Basin 2A-2	. 20
6.2.8	Basin 2A-3	. 21
6.2.9	Basin 2B-1	. 21
6.2.10	Basin 2B-2	. 22
6.2.11	Basin 10	. 22
6.2.12	Basin 11	. 23
6.2.13	Basin 12	. 23
6.2.14	Basin 13	. 24
6.2.15	Basin 14	. 24
6.2.16	Basin 15	. 25
6.2.17	Basin 1	. 25
6.2.18	Basin 2	. 26
6.2.19	Basin B (FGB)	. 26
6.2.20	Basin FL 530	. 26
Section 7.0 –	Floodplain & Environment Information	. 27
Section 8.0 –	Stormwater Ponds	. 27
8.1.1 Basin	2A-2	. 28

8.1.2 Basin FGB	
Section 9.0 – Results	29
Section 10.0 – Conclusions	29
Section 11.0 – References	

#### LIST OF TABLES

Table 1: Preferred Pond Alternatives and Anticipated Right-of-Way	i
Table 2: Statewide Water Quality Assessments	7
Table 3: Basin Management Action Plans	7
Table 4: Drainage Connection Permits	9
Table 5: Project Basin Summary	9
Table 6: Existing Pond Summary	. 10
Table 7: Existing Treatment Summary	. 11
Table 8: Preferred Pond Alternatives and Anticipated Right of Way	. 29

#### LIST OF FIGURES

Figure 1: Project Location Map	2
Figure 2: Existing Typical Section	3
Figure 3: Proposed Typical Section	3
Figure 4: USGS Quad Map	4

#### APPENDICES

Appendix A – Drainage Maps
Appendix B – Pre-Development Calculations
Appendix C – Post-Development Calculations
Appendix D – Floodplain Encroachment Calculations
Appendix E – Pond Site Evaluation Matrix
Appendix F – Correspondence, Meeting Minutes, and Excerpts from Previous Permits and Studies

# SECTION 1.0 – INTRODUCTION

The Florida Turnpike Enterprise (FTE) is evaluating alternatives to widen Florida's Turnpike (State Road (SR) 429) from Interstate 4 to Seidel Road, a distance of approximately 11 miles. As part of the study, all existing interchanges within the project limits and the need for a new interchange will be evaluated. The purpose of the project is to improve mobility on Florida's Turnpike mainline to accommodate current and future traffic volumes and improve safety along SR 429.

### SECTION 2.0 – PROJECT DESCRIPTION

The project is located in Osceola and Orange Counties, Florida. See **Figure 1** for a Project Location Map. The vertical datum used for this project is the North American Vertical Datum of 1988 (NAVD-88). The datum shift from NGVD-29 is (-)0.87-ft, with NAVD-88 being the lower elevation of the two.

NAVD-88 = NGVD-29 + datum shift

Florida's Turnpike currently has 4-lane typical section within the study limits. See **Figure 2** for the existing typical section. The roadway is functionally classified as an Urban Principal Arterial – Freeway and Expressway and has a posted speed limit of 70 miles per hour (mph).

This PD&E Study will evaluate the widening of the Florida's Turnpike from 4-lanes to 8-lanes, along with interchange improvements. See **Figure 3** for the proposed typical section. The total project length is approximately 11.0-miles. The study includes five existing interchanges and one new interchange.

Existing interchanges are as follows:


- Interstate 4 (MP 0)
- Sinclair Road (MP 1)
- US 192 (MP 6)
- Western Way (MP 8)
- Seidel Road (MP 11)

Proposed interchange:

• Livingston Road (MP 4)


See Figure 4 for United States Geological Survey (USGS) Quadrangle Map.

#### Figure 1: Project Location Map




Pond Siting Report Widening Western Beltway PD&E Study from Interstate 4 to Seidel Road Florida's Turnpike Enterprise Financial Project ID 446164-1


#### Figure 2: Existing Typical Section



#### Figure 3: Proposed Typical Section



Page | 3



Pond Siting Report Widening Western Beltway PD&E Study from Interstate 4 to Seidel Road Florida's Turnpike Enterprise Financial Project ID 446164-1

# SECTION 3.0 – DATA COLLECTION

Pre-application meetings were held with the Florida Department of Environmental Protection (FDEP), South Florida Water Management District (SFWMD), and Reedy Creek Improvement District (RCID) to discuss permitting requirements for the project. Meeting minutes from these pre-applications meeting have been provided in **Appendix F**. In order to locate and size the stormwater management facilities the following sources were utilized:

- USDA NRCS Web Soil Survey (2022)
- SFWMD ePermitting Web App
- FDEP NEXUS Permit Search Information Portal
- FDEP GIS Viewer (WBIDs, Impaired Waterbodies, etc.)
- FEMA Flood Insurance Rate Maps (12097C0040G, 12097C0030G, 12095C0580F, 12095C0390F, 12095C0375F)
- Conservation Easements and Wetlands- SFWMD 2016 (Updated 2020)
- LIDAR Data http://digir.fiu.edu/

# SECTION 4.0 – DESIGN CRITERIA

### 4.1 Rules & Regulations / Regulatory Agency Coordination

Project improvements will be designed to meet the regulatory requirements of the applicable water management districts, the requirements outlined in the FDOT Drainage Manual, and the requirements of Florida's Turnpike Enterprise (FTE). The project is located within the SFWMD jurisdiction, however FDEP reviewed and issued the original Environmental Resource Permit (ERP) in 2001. In addition, the Reedy Creek Improvement District entered into a drainage agreement with FTE for discharges outside the right of way.

FDEP will be the permitting lead for the ERP based on Ch. 338.250, FS "The Central Florida Beltway Mitigation Bill", while utilizing the applicable local water management district criteria. In addition, the project is within the Reedy Creek Watershed, therefore approval / drainage agreement from RCID will be required as well. The FDEP ERP application should be submitted to RCID for review prior to submitting to FDEP for concurrence. FDEP will be responsible for Section 404 reviews and permitting. A National Pollutant Discharge Elimination System (NPDES) permit will also be required from FDEP.

#### 4.1.1 Water Quality Criteria

#### SFWMD, FDEP, and RCID

- *Wet detention*: Detention volume shall be provided for the first inch of total runoff from the developed project, or 2.5 inches of the runoff from impervious area, whichever is greater.
- **Dry Retention**: retention volume shall be provided equal to 50 percent of the above amounts computed for wet detention. Retention volume included in flood protection calculations requires a guarantee of long-term operation and maintenance of system bleed-down ability.
- **Dry Detention**: volume shall be provided equal to 75 percent of the above amounts computed for wet detention.

#### 4.1.2 Water Quantity Criteria

#### SFWMD

For open basins, the post-development peak discharge rate must not exceed the predevelopment peak discharge rate during the 25-year, 72-hour storm. For closed basins, the post-development peak discharge volume must not exceed the pre-development peak discharge rate and volume during the 100-year, 72-hour storm.

#### RCID

Reedy Creek Improvement District will impose a drainage fee for any discharge from the proposed project which exceeds 13 csm (cfs per square mile) for the 50-year, 72-hour (12.91 inches of rainfall) event using the SFWMD distribution. See **Appendix F** for documentation.

#### FDOT

Per FDOT requirements, the above noted SFWMD requirements are to be followed in open basins. FDOT does, however, require that the constraints found in Chapter 14-86 of the Florida Administrative Code be utilized for design purposes in basins that are closed and where there are flooding concerns. For the purposes of this report, the volumetric difference associated with the 100-year, 10-day storm has been utilized for pond sizing in closed basins and basins with a history of flooding concerns.

### 4.2 Project-Specific Criteria

This project does not discharge to Outstanding Florida Waters. The project does, however, traverse basins where a basin management action plan has been established. A summary of these special requirements is noted in the sections that follow.

#### 4.2.1 TMDL Requirements

FDEP maintains the Statewide Comprehensive List of Impaired Waters, which contains waterbody-parameter combinations that have been verified as impaired based on criteria and assessment methodologies. Waterbody Identification (WBID) 3170K and 3170F4 have been identified for impairments. **Table 2** outlines the impairments associated with these WBID's. It should be noted that there are nutrient removal requirements associated with the basin management action plans for WBID's which may not be listed as impaired for nutrients in the Statewide Verified List.

Waterbody Name	WBID	Class	Impairment	
Davenport Creek	3170K	3F	Bacteria (Fecal)	
Davenport Creek Headwaters	3170F5	3F	None	
Whittenhorse Creek	3170F4	3F	Dissolved Oxygen	
Lake Hickorynut Drain	3170IA	3F	None	

#### Table 2: Statewide Water Quality Assessments

Existing stormwater management facilities are based on the water management districts presumptive treatment volumes. No additional treatment volume beyond the presumptive treatment volume will be provided for the impaired basins.

#### 4.2.2 Basin Management Action Plans (BMAPs)

This project is within the Lake Okeechobee BMAP. Phosphorus is the nutrient of concern for this BMAP. A summary of the BMAP has been provided in **Table 3**. No additional treatment considerations were given for total phosphorus removal. Though the project is located within the basin of the BMAP, stormwater runoff from the corridor will not direct discharge into Reedy Creek, which ultimately discharges into Lake Okeechobee

 Table 3: Basin Management Action Plans

Basin Management Action Plan	Date	Parameters
Lake Okeechobee	January 2020	Total Phosphorus (TP)

## SECTION 5.0 - ENVIRONMENTAL LOOK AROUND

Individual technical meetings were held with RCID, FDEP, SFWMD, Osceola County, and Orange County as part of the coordination efforts of this project. During these meetings the potential opportunities for implementing a joint use or regional stormwater facility were discussed. FDEP and SFWMD stated they were open to the use of regional ponds, but no specific opportunities were identified during or after these meetings for any of the agencies and municipalities. The meeting minutes for each of these meetings have been included in **Appendix F**.

# SECTION 6.0 – EXISTING & PROPOSED CONDITIONS

### 6.1 Existing Drainage Conditions

The existing Western Beltway (SR 429) corridor was constructed in phases in the early 2000's. The PD&E study area falls within "Part C" of the system. Part C was further subdivided into sections; the sections of interest are Section 1, Section 2A, Section 2B, and Section 3. 20 basins have been identified within the limits of the study area. These basins consist of open and closed basins. Basins have been defined to corelate with currently permitted conditions within the project limits. Basin divides have been developed from existing permit information which has been supplemented with LIDAR data. Basin divides have been detailed on the existing basin maps included in **Appendix A**.

The original Western Beltway (SR 429) corridor was designed and permitted for a 6-lane configuration, with 4-lanes constructed and 2 "future lanes" to be added within the median. This analysis takes the existing 6-lane permitted condition and analysis the treatment and attenuation requirements for an 8-lane corridor with a new interchange at Livingston Road. Existing treatment calculations depicting the required and provided treatment volumes can be found in **Appendix B**.

FDOT District 5 has two ongoing projects within the I-4 / SR 429 interchange. These projects are part of the overall Beyond the Ultimate (BTU) I-4 improvements. The first project, which is currently in construction, is the Interstate 4/SR 429 Auxiliary Lanes (FPID 444329-1-52-01). Improvements include an auxiliary lane along Interstate 4 connecting to the outside of the existing northbound lanes of SR 429. Permitting documentation for this project can be found in ERP No. 0187636-005-EI issued August 19, 2019. The second project is the widening of Interstate 4 to 10-lanes and improvements to the Interstate 4/SR 429 interchange (FPID 431456-1-52-01). Permitting documentation for this project can be found in ERP No. 0187636-003-EI issued August 19, 2019. In addition, Florida's Turnpike Enterprise is conducting a PD&E study for the extension of Poinciana Parkway from CR 532 to Sinclair Road.

For the purposes of this study only the auxiliary lane project will be considered as an existing condition. The reason for this is twofold, the BTU Interstate 4/SR 429 improvements are still in design and the Poinciana Parkway Extension evaluation will evaluate the 8-lane configuration with the BTU Interstate 4/SR 429 improvements incorporated. Based on the permit data for the auxiliary lane project found in ERP No. 0187636-005-EI, the existing stormwater management system associated with the original construction of the corridor has enough water quality and quantity volume to capture, treat, and attenuate the runoff for the auxiliary lane improvements. These improvements only fall within Basin F-4 of the PD&E study area.

As noted in **Section 4.1.2**, RCID implements a fee for water quantity for any discharge over 13 csm. The Turnpike entered into an agreement with RCID for the construction of SR 429 in 2001. This agreement states the following, "Florida's Turnpike Enterprise may discharge, and RCID, agrees to receive, surface water from the Western Beltway and the Interchange into RCID Facility at a rate of no greater than 297.64 cubic feet per second (cfs) for the 50-year/3-day storm event...". A table is cited within the contract agreement which supposably breaks down the discharge per outfall, however this table is missing. FDOT District 5 has also entered into an agreement with RCID for excess discharges from the I-4/SR 429 interchange. Upon review of BTU permit documentation, the original contract agreement adopted between FDOT and RCID could not be located. Therefore, the two agencies are currently negotiating a new agreement. It should be noted that RCID has additional fees for permit reviews and for impacts within their watershed. See **Appendix F** for additional information.

There are four drainage connection permits within the project corridor. These connection permits have been listed in **Table 4** below with the corresponding milepost for reference. Additionally, the receiving waterbody, whether the basin is open or closed, and any special basin criteria is outlined in **Table 5**. FDEP has defined four WBID's that encompass the study area. **Table 2** also outlines which impairment relates to each WBID. Specific characteristics related to each basin are outlined in the following sections.

**Table 6** below provides a summary of the stormwater management facilities in each basin, along with the type of facility and the permit number for each. **Table 7** provides the required treatment and provided treatment within each of the each of the existing stormwater management facilities.

Name	Permit Number	Mile Post
Sinclair Road Apartments	TP-92-DC-180-18	1.5
Flamingo Crossings PD	TP-75-DC-130-18	7.5
Flamingo Crossings Ph I	TP-75-DC-010-08	7
Horizon High School	TP-75-DC-181-20	11

#### Table 4: Drainage Connection Permits

#### Table 5: Project Basin Summary

Name	Туре	<b>Receiving Waterbody</b>
BASIN F-4	Open	Davenport Trib
BASIN B-2	Open	Davenport Trib
BASIN B-3	Open	Davenport Creek
BASIN B-4	Open	Davenport Creek
BASIN B-5	Open	Davenport Creek

Pond Siting Report Widening Western Beltway PD&E Study from Interstate 4 to Seidel Road Florida's Turnpike Enterprise Financial Project ID 446164-1 Page | 9

Name	Туре	Receiving Waterbody
BASIN B-6	Open	Davenport Creek
BASIN 2A-2	Open	Davenport Creek
BASIN 2A-3	Open	Boggy Creek
BASIN 2B-1	Open	Boggy Creek
BASIN 2B-2	Open	Boggy Creek
BASIN 10	Closed	-
BASIN 11	Open	RCID Perimeter Canal
BASIN 12	Open	Whittenhorse Creek
BASIN 13	Open	Whittenhorse Creek
BASIN 14	Open	Bear Bay / Whittenhorse Creek
BASIN 15	Closed	-
BASIN 1	Open	Panther Lake
BASIN 2	Open	Wetland
BASIN B (FGB)	Open	Davenport Creek
BASIN FL 530	Open	Boggy Creek

#### Table 6: Existing Pond Summary

Name	Basin	<b>Treatment Method</b>	Permit
EXIST. POND F4-A	F4	Wet Detention	49-187636001
EXIST. POND F4-B	F4	Wet Detention	49-187636001
EXIST. POND B-2	B2	Wet Detention	49-187636001
EXIST. POND B-3A	В3	Wet Detention	49-187636001
EXIST. POND B-3B	B3	Wet Detention	49-187636001
EXIST. POND B-3C	B3	Dry Detention	49-187636001
EXIST. POND B-3D	B3	Dry Detention	49-187636001
EXIST. POND B-4	B4	Wet Detention	49-187636001
EXIST. POND B-5	B5	Wet Detention	49-187636001
EXIST. POND B-6A	B6	Wet Detention	49-187636001
EXIST. POND B-6B	B6	Dry Detention	49-187636001
EXIST. POND B-6C	B6	Dry Detention	49-187636001
EXIST. POND 2A-2	2A-2	Wet Detention	49-187636001
EXIST. POND 2A-3	2A-3	Wet Detention	49-187636001
EXIST. POND 2B-1	2B-1	Wet Detention	49-187636001
EXIST. POND 2B-2	2B-2	Wet Detention	49-187636001
EXIST. POND 10	10	Dry Retention	49-187636001
EXIST. SWALE 11A	11	Dry Retention	49-187636001
EXIST. SWALE 11B	11	Dry Retention	49-187636001
EXIST. SWALE 11C	11	Dry Retention	49-187636001
EXIST. POND 11D	11	Dry Retention	49-187636001
EXIST. POND 12	12	Wet Detention	49-187636001
EXIST. POND 13	13	Wet Detention	49-187636001
EXIST. POND 14A	14	Dry Retention	49-187636001
EXIST. POND 14B	14	Dry Retention	49-187636001
EXIST. POND 14C	14	Dry Retention	49-187636001

Pond Siting Report Widening Western Beltway PD&E Study from Interstate 4 to Seidel Road Florida's Turnpike Enterprise Financial Project ID 446164-1 Page | 10

Name	Basin	<b>Treatment Method</b>	Permit
EXIST. POND 15A	15	Dry Retention	49-187636001
EXIST. POND 15B	15	Dry Retention	49-187636001
EXIST. POND 15C	15	Dry Retention	49-187636001
EXIST. POND 15D	15	Dry Retention	49-187636001
EXIST. POND 15E	15	Dry Retention	49-187636001
EXIST. POND 1	1	Dry Retention	48-166214001*
EXIST. POND 2	2	Wet Detention	48-166214001*
EXIST. POND B (FGB)	B (FGB)	Wet Detention	49-00507-S
EXIST. POND A (FL 530)	A (FL 530)	Wet Detention	49-00956-P
EXIST. SWALE B (FL 530)	B (FL 530)	Dry Detention	49-00956-P
EXIST. POND C (FL 530)	C (FL 530)	Wet Detention	49-00956-P

\* - Permit information could not be found through FDEP NEXUS Portal. As-built plans and drainage documentation obtained through CFX records request.

Name	Basin	Required Treatment Volume (ac-ft)	Permitted Treatment Volume (ac-ft)
EXIST. POND F4-A / F4-B	F4	3.03	3.36
EXIST. POND B-2	B2	1.58	1.78
EXIST. POND B-3A / B-3B / B-3C / B-3D / B-5	В3	2.18	2.64
EXIST. POND B-4	B4	2.26	2.47
EXIST. POND B-6A / B-6B / B-6C	B6	0.64	1.68
EXIST. POND 2A-2	2A-2	11.21	11.62
EXIST. POND 2A-3	2A-3	5.19	5.43
EXIST. POND 2B-1	2B-1	4.65	4.81
EXIST. POND 2B-2	2B-2	4.12	4.25
EXIST. POND 10	10	1.50	1.60
EXIST. SWALE 11A	11	0.72	12.54
EXIST. SWALE 11B	11	0.79	0.69
EXIST. SWALE 11C	11	0.56	0.54
EXIST. POND 11D	11	0.68	0.81
EXIST. POND 12	12	1.68	1.80
EXIST. POND 13	13	5.98	6.10
EXIST. POND 14A	14	0.88	1.03
EXIST. POND 14B	14	0.33	0.44
EXIST. POND 14C	14	0.80	0.80
EXIST. POND 15A	15	1.56	1.57
EXIST. POND 15B	15	1.28	1.68
EXIST. POND 15C	15	0.15	0.32
EXIST. POND 15D	15	0.43	0.18
EXIST. POND 15E	15	0.74	0.80
EXIST. POND 1	1	0.88	1.06
EXIST. POND 2	2	2.50	2.50

#### Table 7: Existing Treatment Summary

Pond Siting Report Widening Western Beltway PD&E Study from Interstate 4 to Seidel Road Florida's Turnpike Enterprise Financial Project ID 446164-1 Page | 11

Name	Basin	Required Treatment Volume (ac-ft)	Permitted Treatment Volume (ac-ft)
EXIST. POND B (FGB)	B (FGB)	N/A	N/A
EXIST. POND A (FL 530)	A (FL 530)	1.85*	2.16
EXIST. SWALE B (FL 530)	B (FL 530)	0.48	0.54
EXIST. POND C (FL 530)	C (FL 530)	4.18	4.18

\* - Required treatment calculations show 1.85 ac-ft or 2.04 ac-ft, the greater of the two. However, the permit shows 1.85 ac-ft as the required volume when it should have been 2.04 ac-ft.

#### 6.1.1 Basin F-4

Basin F-4 is located within the Interstate 4 interchange, just north of Interstate 4 (Sta. 54+00 to 80+40). Basin F-4 is an open basin which ultimately discharges to a tributary of Davenport Creek. There are two wet detention ponds located within Basin F-4, Pond F-4-A and Pond F-4-B. These ponds receive runoff from SR 429, Interstate 4 westbound lanes, and portions of Ramps A, B, C, and D within the interchange. See **Appendix B** for existing treatment calculations.

This basin falls within the project limits of the auxiliary lane project, however as noted in the permit documentation for the auxiliary lanes project, no improvements will be made to Pond F-4 because there is sufficient treatment within the existing pond for the proposed improvements. See **Appendix B** for existing treatment calculations.

#### 6.1.2 Basin B-2

Basin B-2 is located just north of the Interstate 4 interchange and just south of Sinclair Road (Sta. 80+40 to Sta. 101+00). Basin B-2 is an open drainage basin which ultimately discharges into a tributary of Davenport Creek. This basin contains one wet detention pond which discharges to a spreader swale located along the toe of Pond B-2 that overflows into an adjacent wetland. See **Appendix B** for existing treatment calculations.

#### 6.1.3 Basin B-3

This basin is a compilation of the sub-basins located just south of Sinclair Road and just north of Sinclair Road, on the east side of the corridor (Sta. 101+00 to Sta. 141+00). This basin also includes portions of Sinclair Road from the high point of the bridge over SR 429 to the east to Ramp F and Ramp G. There are four ponds in total with corresponding sub-basins: Pond B-3-A, Pond B-3-B, Pond B-3-C, and Pond B-3-D. The control structure for Basin B-3 discharges from Pond B-3-A to a wetland associated with Davenport Creek. Pond B-3-C and Pond B-3-D are dry detention facilities that do not provide treatment. Pond B-3-A and Pond B-3-B are wet detention facilities. Additionally, Pond B-5 is interconnected with Pond B-3-A to provide additional attenuation. See **Appendix B** for existing treatment calculations.

#### 6.1.4 Basin B-4

Basin B-4 is located from Sand Hill Road and to the north (Sta. 141+50 and Sta. 167+00). This basin has one wet detention pond. Pond B-4 discharges under the adjacent access road to the west and into a wetland associated with Davenport Creek. See **Appendix B** for existing treatment calculations.

#### 6.1.5 Basin B-5

Basin B-5 is located south of Sand Hill Road on the east side of SR 429. Basin B-5 includes Sand Hill Road from Sta. 803+00 to 814+00 and portions of the Connector Road. This basin has one wet detention pond. Pond B-5 is interconnected with Pond B-3-A in order to better utilize the large volume in Pond B-5 to help reduce flows out of Basin B-3. Pond B-5 discharges through a control structure in Pond B-3-A into a wetland associated with Davenport Creek. See **Appendix B** for existing treatment calculations. Please note treatment calculations are coupled with Basin B-3.

#### 6.1.6 Basin B-6

This basin is a compilation of the sub-basins located just south of Sinclair Road to north of Sinclair Road (Sta. 101+00 to Sta. 125+00) on the west side of SR 429. Basin B-6 consists of three ponds: Pond B-6-A, Pond B-6-B, and Pond B-6-C. Pond B-6-B and Pond B-6C are dry detention ponds with no treatment volume associated with them. These two ponds discharge into Pond B-6-A, which is a wet detention facility. Pond B-6-A discharges into a wetland associated with Davenport Creek. See **Appendix B** for existing treatment calculations.

#### 6.1.7 Basin 2A-2

Basin 2A-2 is located north of Sand Hill Road to Funie Steed Road (Sta. 180+00 to Sta. 268+00). This basin has one wet detention pond. Pond 2A-2 discharges under SR 429 and into Davenport Creek. This basin accepts flow from a number of offsite ponds from adjacent residential communities, as noted in the FDEP ERP documentation (49-187636001). As shown in the treatment calculations in **Appendix B**, portions of Sand Hill Road, Funie Steed Road, and Oak Island Cove are conveyed into Pond 2A-2 for treatment. The stormwater management facilities for adjacent communities Wyndham Palms and Indian Creek discharge into FTE right-of-way. It should be noted the Indian Creek/Fantasy Heights subdivision located on the east side of the SR 429 corridor discharges to a privately owned stormwater management facility on the west side of the SR 429 via a 42-inch storm sewer pipe.

#### 6.1.8 Basin 2A-3

Basin 2A-3 is located between Funie Steed Road and SR 530 (Sta. 268+00 to Sta. 320+50). This basin has one wet detention pond. Pond 2A-3 discharges into Boggy Creek. Offsite areas east

of SR 429 is collected within roadside ditches and taken into Pond 2A-3. It is stated within the permit documentation that is possible for a portion of Basin 2A-3 to be sent to Basin 2B-1 for treatment. Though the treatment calculations seem to reflect this, the basin boundaries shown within the as-built drawings do not reflect this. See **Appendix B** for existing treatment calculations.

#### 6.1.9 Basin 2B-1

Basin 2B-1 is located between SR 530 and just south the toll plaza (Sta. 320+50 and Sta. 1359+00). This basin has one wet detention pond. Pond 2A-3 discharges to Boggy Creek. As noted in the treatment calculations a portion of SR 530 and possibly a portion of Basin 2A-3 is conveyed to Pond 2B-1. See **Appendix B** for existing treatment calculations.

#### 6.1.10 Basin 2B-2

Basin 2B-2 begins just south of the toll plaza located north of SR 530 and continues north to the bridge over W Orange Lake Boulevard (Sta. 1359+00 to Sta. 414+00). This basin has one wet detention pond. Pond 2B-2 discharges to Boggy Creek. See **Appendix B** for existing treatment calculations.

#### 6.1.11 Basin 10

Basin 10 is located from the high point of the bridge over W Orange Lake Boulevard to just south of Western Way (Sta. 414+00 to Sta. 438+43). Basin 10 is a closed basin with one dry retention pond. Pond 10 was designed to retain the 100-year,10-day storm event. Approximately 14.80-acres of offsite area discharged into this pond from the west. See **Appendix B** for existing treatment calculations.

#### 6.1.12 Basin 11

This basin is a compilation of the sub-basins located within the SR 429 at Western Way interchange (Sta. 435+00 to Sta. 474+00). Basin 11 is comprised of four dry retention ponds within the interchange. Three of the four ponds are interconnected: Pond 11B, Pond 11C and Pond 11D. The basin has a by-pass system used to convey runoff from offsite drainage areas through the project corridor without co-mingling. The ponds discharge through Pond 11C control structure to the by-pass system which outfalls into the RCID perimeter canal via a closed storm sewer system located adjacent the eastbound lanes of Western Way. See **Appendix B** for existing treatment calculations. Pond 11A was oversized to provide additional attenuation.

#### 6.1.13 Basin 12

Basin 12 is located just north of the Western Way interchange (Sta. 474+00 to Sta. 490+00). This basin has one wet detention pond. Pond 12 discharges into an outfall ditch which conveys discharge to Whittenhorse Creek. See **Appendix B** for existing treatment calculations.

#### 6.1.14 Basin 13

Basin 13 is located between Western Way and Seidel Road (Sta. 490+00 to Sta. 574+00). This basin has one wet detention pond. Pond 13 discharges into a by-pass system that runs south along the east right-of-way line to Whittenhorse Creek. See **Appendix B** for existing treatment calculations.

#### 6.1.15 Basin 14

This basin is a compilation of the sub-basins located just south of the SR 429 at Seidel Road interchange (Sta. 530+00 to Sta. 585+00). Basin 14 provides treatment for SR 429 and the improvements to Hartzog Road. Pond 14A is dry retention pond that provide treatment and attenuation for Hartzog Road. Pond 14A discharges into a wetland, Bear Bay, which is associated with Whittenhorse Creek. Pond 14B is a dry retention pond that provides treatment and attenuation for Hartzog Road. Pond 14B discharges to a wetland associated with Reedy Lake. Pond 14C is a dry retention pond that provides treatment for SR 429. This pond discharges to a wetland associated with Reedy Lake. See **Appendix B** for existing treatment calculations.

#### 6.1.16 Basin 15

This basin is a compilation of the sub-basins located within the SR 429 at Seidel Road interchange (Sta. 585+00 to Sta. 618+00). Basin 15 is a closed basin which consists of five ponds: Pond 15A, Pond 15B, Pond 15C, Pond 15D, and Pond 15E. Pond 15B, Pond 15C, and Pond 15D are interconnected with equalizer pipes to maximize treatment. Pond 15E discharges into Pond 15A, which is designed to retain the 100-year, 10-day storm event. Pond 15A does have an emergency overflow weir that discharges into Pond 15B. See **Appendix B** for existing treatment calculations.

#### 6.1.17 Basin 1

This basin is located from Seidel Road to just north of Seidel Road (Sta. 1622+18.86 to Sta. 602+00). This basin has one dry retention pond. Pond 1 discharges into Panther Lake. See **Appendix B** for existing treatment calculations.

#### 6.1.18 Basin 2

This basin is located from north of Seidel Road to CR 545 (Sta. 602+00 to Sta. 641+83.82). This basin has one wet detention pond. Pond 2 discharges into a wetland located on the east side of SR 429. See **Appendix B** for existing treatment calculations.

#### 6.1.19 Basin B (FGB)

Basin OS-1 and Basin B are associated with the Formosa Gardens subdivision located east of SR 429 between Livingston Road and Funie Steed Road. Basin OS-1 is located on the west side of

Formosa Gardens Boulevard (FGB) and discharges under the roadway into Basin B. Basin B is located on the east side of FGB and is comprised of single-family homes. Pond B provides treatment and attenuation for these basins. Permit information for Formosa Gardens can be found in ERP No. 49-00507-S.

Pond B provides treatment and attenuation for the 2-lane portion of Formosa Gardens Blvd located between Livingston Road and Formosa Blvd.

#### 6.1.20 Basin FL 530

Widening of FL 530 (SR 530 or US192) in the vicinity of SR 429 received a permit March 11, 1999 (ERP No. 49-00956-P). The improvements included stormwater management facilities along the corridor. Basin A, Basin B, and Basin C of these improvements are located within the vicinity of SR 429. Pond A is a wet detention pond that discharges to Boggy Creek. Basin B discharges into a dry swale with swale blocks and a raised inlet that discharges to Boggy Creek. Pond C is a wet detention pond that discharges to an adjacent channel.

### 6.2 Proposed Drainage Conditions

20 basins have been identified within the limits of the study area, which have been outlined on the proposed drainage maps included in **Appendix A**. It is anticipated that only minor changes to the basin divides will occur in the proposed condition, with the vast majority of the changes controlled by the layout of the conveyance system which will occur during the design phase. When this project was originally constructed the surrounding area was primarily rural with wetlands, wooded areas, and pastures. Over the years residential and commercial development has occurred adjacent to the corridor. This development has changed some of the offsite areas that previously discharged in the Turnpike's right-of-way. These changes are reflected in the offsite basins shown within the proposed drainage maps and within each of the basin descriptions that follow.

The original Western Beltway (SR 429) corridor was designed and permitted for a 6-lane configuration, with 4-lanes constructed and 2 "future lanes" to be added within the median. This analysis takes the existing 6-lane permitted condition and analyzes the treatment and attenuation requirements for an 8-lane corridor with a new interchange at Livingston Road. Existing treatment calculations depicting the required and provided treatment volumes can be found in **Appendix B**. Proposed treatment and attenuation calculations can be found in **Appendix C**. For the purposes of this document, the term new impervious area will only refer to the amount of impervious area that is beyond the permitted value for "future pavement". Additional analysis will be required during the design phase once the design of the conveyance system has been incorporated into the project.

As noted in **Section 6.1** the Turnpike entered into an agreement with RCID for the construction of the Western Beltway in 2001. As such, RCID will accept 297.64 cfs of discharge from the corridor. For the purposes of this design analysis, attenuation volumes will be based on the FDOT design storm of 50-year, 3-day (11.40-inches) for existing facilities. The rationale being the fee will be less than the cost of new right-of-way and construction of new stormwater management facilities. Please note this fee does not eliminate the pre vs post development water quantity requirement. No discharge over the pre-condition rate will be accepted. This is the reason for using the 50-year, 3-day instead of the 25-year, 3-day. In areas where new stormwater management facilities are required, the RCID design storm of 50-year, 3-day (12.91inches) will be utilized. The intent is to provide attenuation within Turnpike right-of-way as to not discharge more runoff into RCID than necessary for new facilities.

In addition to the discharge fee posed by RCID, they also have a \$750 administration fee for permit review and an impact fee of \$200 per acre. An impact fee was paid by the Turnpike for the original Western Beltway improvements. This should be interpreted as the area within the existing right-of-way. Any new right-of-way will be subject to a fee at the rate previously described.

#### 6.2.1 Basin F-4

Basin F-4 is located within the Interstate 4 interchange, just north of Interstate 4 (Sta. 54+00 to 80+40). Basin F-4 is an open basin which ultimately discharges to a tributary of Davenport Creek. There are two existing wet detention ponds located within Basin F-4: Pond F-4-A and Pond F-4-B. These ponds receive runoff from SR 429, Interstate 4, Ramp A, Ramp B, Ramp C, and Ramp D within the interchange.

The proposed improvements will not impact the existing stormwater management facilities Pond F-4-A and Pond F-4-B. The proposed improvements will result in approximately 1.50acreas of impervious area requiring treatment. Based on the treatment volume provided, the surplus treatment within these interconnected ponds should be sufficient to meet permit requirements without modification or the need to purchase additional right-of-way. Approximately 0.86 ac.-ft. of attenuation is anticipated to meet the RCID requirements. The outfall structure will need to be adjusted to accommodate the attenuation requirements. Proposed treatment and attenuation calculations can be found in **Appendix C**.

#### 6.2.2 Basin B-2

Basin B-2 is located just north of the Interstate 4 interchange and just south of Sinclair Road (Sta. 80+40 to Sta. 101+00). Basin B-2 is an open drainage basin which ultimately discharges into a tributary of Davenport Creek. This basin contains one wet detention pond, which

discharges to a spreader swale located along the toe of Pond B-2 that overflows into an adjacent wetland.

The proposed improvements will bring the total impervious area within Basin B-2 to approximately 7.85-acres. According to the existing permit, Pond B-2 was designed to treat 8.08-acres of impervious, therefore no changes to Pond B-2 are anticipated. Proposed treatment and attenuation calculations can be found in **Appendix C**.

It should be noted that improvements associated with the I-4 Beyond the Ultimate will impact Pond B-2, reducing the treatment volume by approximately 0.10 ac-ft. This will effectively bring the provided treatment volume down to 1.68 ac-ft, which would match the required volume of 1.68 ac-ft. Should additional treatment and attenuation be required due to changes associated with the I-4 Beyond the Ultimate improvements currently in design, the closed storm sewer system which collects the inside lanes can be configured to discharge into Pond B-3-D and/or Pond B-6-C. With the proposed removal of impervious area associated of the existing toll gantries and surplus treatment associated with these basins, sufficient treatment and attenuation should be available.

#### 6.2.3 Basin B-3

This basin is a compilation of the sub-basins located just south of Sinclair Road and just north of Sinclair Road, on the east side of the corridor (Sta. 101+00 to Sta. 141+00). This basin also includes portions of Sinclair Road from the high point of the bridge over SR 429 to the east to Ramp F and Ramp G. There are four ponds in total with corresponding sub-basins: Pond B-3-A, Pond B-3-B, Pond B-3-C, and Pond B-3-D. The control structure for Basin B-3 discharges from Pond B-3-A to a wetland associated with Davenport Creek. Pond B-3-C and Pond B-3-D are dry detention facilities that do not provide treatment. Pond B-3-A and Pond B-3-B are wet detention facilities. Additionally, Pond B-5 is interconnected with Pond B-3-A to provide additional attenuation.

Approximately 2.35-acres of impervious area will require treatment within Basin B-3 and Basin B-5. The proposed improvements are not anticipated to impact the existing footprint of the existing ponds. In contrast, with the re-alignment of SR 429 and the northbound off ramp onto Sinclair Road, it will be feasible to expand the existing ponds to provide additional attenuation.

The proposed improvements will utilize surplus treatment within the existing ponds to offset the new impervious area. Approximately 2.84 ac-ft of volume is anticipated for attenuation. This volume will be offset with the expansion of Pond B-3-D. Proposed treatment and attenuation calculations can be found in **Appendix C**.

#### 6.2.4 Basin B-4

Basin B-4 is located from Sand Hill Road and to the north (Sta. 141+50 and Sta. 167+00). This basin has one wet detention pond. Pond B-4 discharges under the adjacent access road to the west and into a wetland associated with Davenport Creek.

Proposed improvements include the re-alignment of SR 429 in the vicinity of Pond B-4. This will necessitate the need for a MSE wall adjacent to Pond B-4 to ensure the proposed roadway side slope does not encroach into the existing pond. With the use of a wall, it will be possible to expand the existing pond to allow for additional attenuation and to reduce stages. Per existing design documentation, the design high water (25-yr event) exceeds the pond berm but is lower than the adjacent side road edge of shoulder.

The proposed improvements will require approximately 0.75-acres of impervious area to be treated. This results in a required treatment volume of 2.41 ac-ft. Per the permit documentation 2.47 ac-ft of treatment volume has been provided within Pond B-4. Additionally, approximately 0.04 ac-ft of volume is required for attenuation purposes. As previously noted, the pond can be expanded to provide the additional volume without additional right-of-way. Proposed treatment and attenuation calculations can be found in **Appendix C**.

#### 6.2.5 Basin B-5

Basin B-5 is located south of Sand Hill Road on the east side of SR 429. Basin B-5 includes Sand Hill Road from Sta. 803+00 to 814+00 and portions of the Connector Road. This basin has one wet detention pond. Pond B-5 is interconnected with Pond B-3-A to better utilize the large volume in Pond B-5 and reduce flows out of Basin B-3. Pond B-5 discharges through a control structure in Pond B-3-A into a wetland associated with Davenport Creek. See **Appendix C** for proposed treatment calculations. Please note treatment calculations are coupled with Basin B-3. See Basin B-3 for additional information regarding the treatment and attenuation volumes.

#### 6.2.6 Basin B-6

This basin is a compilation of the sub-basins located just south of Sinclair Road to north of Sinclair Road (Sta. 101+00 to Sta. 125+00) on the west side of SR 429. Basin B-6 consists of three ponds: Pond B-6-A, Pond B-6-B, and Pond B-6-C. Pond B-6-B and Pond B-6C are dry detention ponds with no treatment volume associated with them. These two ponds discharge into Pond B-6-A, which is a wet detention facility. Pond B-6-A discharges into a wetland associated with Davenport Creek.

Approximately 0.28-acres of impervious area will require treatment. Surplus treatment provided within this basin exceeds the required treatment volume associated with the new impervious area. Approximately 0.73 ac-ft of attenuation will be required. This represents approximately

1.5-inches within the existing Basin B-6 ponds. With the proposed removal of the existing toll gantry Pond B-6-C can be expanded to provide the attenuation volume necessary to accommodate the additional pavement. Proposed treatment and attenuation calculations can be found in **Appendix C**.

#### 6.2.7 Basin 2A-2

Basin 2A-2 is located north of Sand Hill Road to Funie Steed Road (Sta. 180+00 to Sta. 268+00). This basin has one existing wet detention pond. This pond will be modified or relocated to accommodate the new Livingston Road interchange, see Section 8.0 for pond alternatives. This basin accepts flow from a number of offsite ponds from adjacent residential communities, as noted in the FDEP ERP No. 49-187636001. As shown in the existing treatment calculations in **Appendix B**, portions of Sand Hill Road, Funie Steed Road, and permitted Oak Island Cove, Oak Island Harbor subdivision, are conveyed into Pond 2A-2 for treatment. The new Pond 2A-2 has been sized to accommodate these offsite flows. The stormwater management facilities for adjacent communities Wyndham Palms and Indian Creek discharge into FTE right-of-way. The permitted Wyndham Palms, Windsor Palms Subdivision, stormwater management facility (Pond P-2), located in the southwest quadrant of the Canary Island Drive and SR 429 overpass, discharges into the FTE closed storm sewer system at structure W-6. See the Western Beltway Part C – Section 2A as-builts for detailed information. The Indian Creek stormwater management facility, SMA-3, discharges into FTE right-of-way approximately 400-ft north of the Indian Creek Road bridge over SR 429. The existing FTE ditch which accepts SMA-3 discharge will be impacted as part of the proposed improvements. It will be necessary to convey the discharge from SMA-3 to the outfall via a closed storm sewer pipe.

The Indian Creek/Fantasy Heights subdivision located on the east side of the SR 429 corridor discharges to a privately owned stormwater management facility, SMA-2, located on the west side of the SR 429 via a 42-inch storm sewer pipe. As part of the PD&E analysis a technical memorandum was developed analyzing design alternatives for the Canary Island Road overpass bridge. As part of this memorandum various drainage design alternatives were identified to work around or relocate the existing 42-inch storm sewer pipe that traverses SR 429. One of the alternatives outlined in the memo was to redirect flow from the Indian Creek subdivision into Pond 2A-2 for treatment; this would eliminate the need for the 42-inch pipe under SR 429, thus removing the conflict. Because this was only one of a handful of solutions, the treatment calculations provided in **Appendix C** do not account for this possibility. If during design that alternative is selected, Pond 2A-2 would need to be adjusted accordingly to ensure sufficient treatment is provided.

The proposed Livingston Road interchange will require treatment of approximately 14.09-acres of new impervious area and an attenuation volume of approximately 6.60 ac-ft to accommodate the new roadway.

#### 6.2.8 Basin 2A-3

Basin 2A-3 is located between Funie Steed Road and SR 530 (Sta. 268+00 to Sta. 320+50). This basin has one wet detention pond. Pond 2A-3 discharges into Boggy Creek. Offsite areas east of SR 429 is collected within roadside ditches and taken into Pond 2A-3. It is stated within the permit documentation that is possible for a portion of Basin 2A-3 to be sent to Basin 2B-1 for treatment. Though the treatment calculations seem to reflect this, the basin boundaries shown within the as-built drawings do not reflect this.

Despite the possible irregularity previously noted between Basin 2A-3 and Basin 2B-1, Pond 2A-3 will be able to provide treatment and attenuation for the proposed improvements without modification. This is primarily in part due to the change in basin size and a surplus amount of treatment previously provided. When the Western Beltway was constructed approximately 12.32-acres of offsite open grass area was conveyed into Pond 2A-3 for treatment. Over the years the surrounding areas has been developed and the offsite area which once entered Pond 2A-3 for treatment has been converted into residential and commercial properties. These new facilities, Rolling Oaks Mass Grading and Rolling Oaks Commons (ERP No. 49-01801-P), no longer discharge into FTE right-of-way and discharge into stormwater management facilities located within the private development. Because the existing Pond 2A-3 was sized to treat one inch over the basin area, the required treatment volume has decreased. Treatment calculations provided in **Appendix C** depict the proposed treatment requirements based on the new basin size and new impervious area associated with the roadway widening. No additional right-of-way is anticipated for this basin.

### 6.2.9 Basin 2B-1

Basin 2B-1 is located between SR 530 and just south the toll plaza (Sta. 320+50 and Sta. 1359+00). This basin has one wet detention pond. Pond 2A-3 discharges to Boggy Creek. As noted in the treatment calculations a portion of SR 530 and possibly a portion of Basin 2A-3 is conveyed to Pond 2B-1.

The proposed improvements will result in a net zero gain for impervious area. There is an existing toll gantry located within Basin 2B-2 that will be removed as part of the 8-lane configuration. Though the gantry itself is located within the adjacent basin, the extra lanes associated with the gantry extends into this basin. With the new impervious associated with the widening and the removal of pavement associated with the toll gantry the amount of new impervious area requiring treatment is negligible. Pond 2B-1 currently has a surplus treatment

volume of 0.24 ac-ft. No additional right-of-way is anticipated for this basin. See **Appendix C** for proposed treatment calculations.

#### 6.2.10 Basin 2B-2

Basin 2B-2 begins just south of the toll plaza located north of SR 530 and continues north to the bridge over W Orange Lake Boulevard (Sta. 1359+00 to Sta. 414+00). This basin has one wet detention pond. Pond 2B-2 discharges to Boggy Creek.

The proposed improvements will result in a net loss of impervious pavement within this basin. The proposed 8-lane configuration would remove the existing toll gantry, eliminating approximately 6.50-acres of impervious area. No additional right-of-way is anticipated for this basin. See **Appendix C** for proposed treatment calculations.

#### 6.2.11 Basin 10

Basin 10 is located from the high point of the bridge over W Orange Lake Boulevard to just south of Western Way (Sta. 414+00 to Sta. 438+43). Basin 10 is a closed basin with one dry retention pond. Pond 10 was designed to retain the 100-year, 10-day storm event. In the existing condition approximately 14.80-acres of offsite area discharged into this pond from the west. However, in 2021 an apartment complex was being constructed to the west of the Western Beltway. The Flamingo Crossing East development can be found in ERP No. 48-00714-P. Permit documentation the proposed development will utilize an exfiltration system to provide treatment and attenuation prior to entering FTE right-of-way. The design drawings and corresponding drainage calculations show an area within the developed area discharging to Pond 10 which is greater in the post condition than the pre-condition. See Drainage Maps in **Appendix A**. The developer noted that the post development flow entering Pond 10 was equal to or less than the pre-condition. Per the documentation, additional flow would enter the soil via the filtration system and therefore a greater basin area could discharge into Pond 10 while not surpassing the pre-condition discharge rate. A connection permit was issued by FTE. See **Table 5** for details.

Because 14.80-acres of offsite area entered the pond in the existing condition, treatment was provided for this area. With the development of this area, treatment of this area is no longer required. This will offset the 0.15-acres of impervious area requiring treatment and leave Pond 10 with a surplus treatment volume of 0.71 ac-ft. The new impervious area will require approximately 0.10 ac-ft of attenuation for the 100-yr, 10-day storm event. This volume is anticipated to increase the stage within the pond for the 100-yr, 10-day event by 0.02-ft. Treatment and attenuation calculations have been provided on separated for this particular basin. The treatment calculations have removed the 14.80-acres of offsite not requiring treatment. The attenuation spreadsheet has left the 14.80-acres of offsite area to account for

the Flamingo Crossing development discharge into Pond 10. No additional right-of-way is anticipated for this basin. The pond was designed based on Chapter 14-86 critical duration approach. During design the same approach will be required. See **Appendix C** for proposed treatment calculations.

#### 6.2.12 Basin 11

This basin is a compilation of the sub-basins located within the SR 429 at Western Way interchange (Sta. 435+00 to Sta. 474+00). Basin 11 is comprised of four dry retention ponds within the interchange. Three of the four ponds are interconnected: Pond 11B, Pond 11C and Pond 11D. The basin has a by-pass system used to convey runoff from offsite drainage areas through the project corridor without co-mingling. Ponds 11B-11D discharge through Pond 11C control structure to the by-pass system which outfalls into the RCID perimeter canal via a closed storm sewer system located adjacent the eastbound lanes of Western Way. Pond 11A was oversized to provide additional attenuation. Pond 11A discharges into Pond 11B via a control structure.

In order to provide sufficient attenuation during the original design Pond 11A was oversized. As noted in the permit documentation 14.58 ac-ft of treatment volume was provided, when 2.75 ac-ft was required. Therefore, the surplus treatment can be utilized towards the approximate 2.35-acres of new impervious area. With regards to attenuation, approximately 0.85 ac-ft of volume will be required. This can be accomplished by adjusting the existing control structures by 2-inches. No additional right-of-way is anticipated for this basin. See **Appendix C** for proposed treatment calculations.

#### 6.2.13 Basin 12

Basin 12 is located just north of the Western Way interchange (Sta. 435+00 to Sta. 490+00). This basin has one wet detention pond. Pond 12 discharges into an outfall ditch which conveys discharge to Whittenhorse Creek.

Per permit documentation for the original design approximately 6.05-acres of offsite area was treated in Pond 12. With the construction of Walt Disney World Master Plan Development (ERP No. 48-00718-P) adjacent to Pond 12, this offsite area no longer requires treatment and attenuation. Therefore, the approximately 0.34-acres of new impervious area requiring treatment can be offset utilizing the surplus treatment and attenuation from the removal of this area discharging to the pond.

#### 6.2.14 Basin 13

Basin 13 is located between Western Way and Seidel Road (Sta. 490+00 to Sta. 574+00). This basin has one wet detention pond. Pond 13 discharges into a by-pass system that runs south along the east right-of-way line to Whittenhorse Creek.

Pond 13 was sized to provide treatment for one inch over the basin area. With the proposed improvements adding an additional 2.63-acres of impervious pavement, the treatment calculations were re-evaluated to ensure the 2.5-inches over the impervious area was not the controlling criteria. As shown in the treatment calculation provided in **Appendix C**, the one inch over the basin still controls, therefore no additional treatment needs to be provided.

The new impervious area will result in approximately 1.71 ac-ft of volume needed for attenuation. This results in a 3.30-inch increase in depth within the pond to accommodate attenuation. The design peak stage for the 25-year, 72-hr event is 105.87-ft. The inside berm elevation is 105.50-ft with a outside berm elevation of 107.00-ft. The ability to expand the pond or provide a secondary site for attenuation is limited in this basin due to Whittenhorse Creek being located immediately south of Pond 13 and the surrounding area is owned by RCID for the purposes of their rapid infiltration basins. Basin 12 is anticipated to have a reduction in outflow due to the change in basin size. The attenuation previously provided in Basin 12 (approximately 1.83 ac-ft) could be used to offset the attenuation needs for Basin 13 (approximately 1.71 ac-ft). Both basins discharge into Whittenhorse Creek.

#### 6.2.15 Basin 14

This basin is a compilation of the sub-basins located just south of the SR 429 at Seidel Road interchange (Sta. 530+00 to Sta. 585+00). Basin 14 provides treatment for SR 429 and the improvements to Hartzog Road. Pond 14A is dry retention pond that provide treatment and attenuation for Hartzog Road. Pond 14A discharges into a wetland, Bear Bay, which is associated with Whittenhorse Creek. Pond 14B is a dry retention pond that provides treatment and attenuation for Hartzog Road. Pond 14B discharges to a wetland associated with Reedy Lake. Pond 14C is a dry retention pond that provides treatment for SR 429. This pond discharges to a wetland associated with Reedy Lake.

Only Basin 14C will change as a result of the proposed improvements. Approximately 0.24-acres of impervious will require additional treatment, requiring approximately 0.03 ac-ft of volume. However, there is a surplus amount of treatment within the basin of 0.27 ac-ft. See **Appendix C** for proposed treatment calculations.

Attenuation required for the proposed improvements is approximately 0.14 ac-ft. This is approximately 2-inches of depth within Pond 14C alone or <sup>3</sup>/<sub>4</sub>-inches among all three ponds.

Much like Basin 13, the RCID rapid infiltration basins surround this basin. With the reduction of area discharging to Pond 15A and Pond 15B, it may be possible to route a portion of Basin 14 to these ponds for attenuation.

#### 6.2.16 Basin 15

This basin is a compilation of the sub-basins located within the SR 429 at Seidel Road interchange (Sta. 585+00 to Sta. 618+00). Basin 15 is a closed basin which consists of five ponds: Pond 15A, Pond 15B, Pond 15C, Pond 15D, and Pond 15E. Pond 15B, Pond 15C, and Pond 15D are interconnected with equalizer pipes to maximize treatment. Pond 15E discharges into Pond 15A, which is designed to retain the 100-year, 10-day storm event. Pond 15A does have an emergency overflow weir that discharges into Pond 15B.

With the construction recent construction of the Horizon High School (ERP No. 48-101923-P) approximately 18.89-acres will be removed from Pond 15A and 6.73-acres from Pond 15B. Additional improvements include the Waterleigh development (ERP No. 48-02575-P), located on the west side of Western Beltway adjacent to Basin 15E. This development redirected approximately 2.00-acres of offsite area which previously discharged into FTE right-of-way.

The proposed improvement will add an additional 0.42-acres of impervious area. With the surplus volume provided in the existing condition and the removal of offsite area, Basin 15 will have a surplus treatment volume of approximately 1.63 ac-ft after accounting for the proposed improvements. See **Appendix C** for proposed treatment calculations.

With the removal offsite areas discharging to FTE right-of-way there is a surplus of attenuation within Basin 15 ponds. This surplus exceeds the amount needed to offset the new impervious area.

### 6.2.17 Basin 1

This basin is located from Seidel Road to just north of Seidel Road (Sta. 1622+18.86 to Sta. 602+00). This basin has one dry retention pond. Pond 1 discharges into Panther Lake.

In the existing condition approximately 2.00-acres of offsite area was treated in Pond 1. With the construction of the Seidel East (ERP No. 48-02363-P) located on the east side of the Western Beltway, the offsite 2.00-acres no longer enters FTE right-of-way.

The anticipated impervious area associated with the proposed improvements do not exceed the 8.44-acres permitted. Therefore, no additional treatment or attenuation is anticipated for this basin. See **Appendix C** for proposed treatment calculations.

#### 6.2.18 Basin 2

This basin is located from north of Seidel Road to CR 545 (Sta. 602+00 to Sta. 641+83.82). This basin has one wet detention pond. Pond 2 discharges into a wetland located on the east side of SR 429.

The anticipated impervious area associated with the proposed improvements do not exceed the 12.01-acres permitted. Therefore, no additional treatment or attenuation is anticipated for this basin. See **Appendix C** for proposed treatment calculations.

#### 6.2.19 Basin B (FGB)

Basin OS-1 and Basin B are associated with the Formosa Gardens subdivision located east of SR 429 between Livingston Road and Funie Steed Road. Basin OS-1 is located on the west side of Formosa Gardens Boulevard (FGB) and discharges under the roadway into Basin B. Basin B is located on the east side of FGB and is comprised of single-family homes. Pond B provides treatment and attenuation for these basins. Permit information for Formosa Gardens can be found in ERP No. 49-00507-S.

In the existing condition Pond B located within the residential community provides treatment and attenuation for the 2-lane crowned roadway of Formosa Gardens Boulevard between Livingston Road and Formosa Boulevard. With the addition of 2-lanes, it should be possible to regrade the existing 2-lanes (future northbound lanes) to discharge to the east into existing Pond B. The future two southbound lanes and a portion of the Livingston Road interchange will require treatment and attenuation. This will be provided in a new stormwater management facility, see **Section 8.0** for stormwater management facility alternatives.

#### 6.2.20 Basin FL 530

Widening of FL 530 (SR 530 or US192) in the vicinity of SR 429 received a permit March 11, 1999 (ERP No. 49-00956-P). The improvements included stormwater management facilities along the corridor. Basin A, Basin B, and Basin C of these improvements are located within the vicinity of SR 429. Pond A is a wet detention pond that discharge to Boggy Creek. Basin B discharges into a dry swale with swale blocks and a raised inlet that discharges to Boggy Creek. Pond C is a wet detention pond that discharges to an adjacent channel.

A portion of FL 530 is treated within FTE stormwater management facilities. With the proposed improvements the new impervious will require treatment and attenuation. Pond A will require approximately 0.20 ac-ft of treatment and 0.37 ac-ft of attenuation. Pond C will require approximately 0.22 ac-ft of treatment and 0.61 ac-ft of attenuation. Some of this can be compensated within FTE Pond 2A-3 and 2B-1, however modifications to FL 530 Pond A and Pond C will be required.

Orange County and RCID have expressed interest in widening FL 530 in the near future given the amount of recent development in the area. Therefore, it is possible these improvements will be done prior to the widening of Western Beltway. Coordination with these entities is recommended during the design phase.

## SECTION 7.0 – FLOODPLAIN & ENVIRONMENT INFORMATION

Project Improvements will have a minimal impact on adjacent floodplains. A detailed analysis of the impacts resulting from roadway improvements and compensation for these impacts has been included in the *Location Hydraulic Report,* included under separate cover with this submittal. The limits of the floodplain have been outlined on the drainage maps included in **Appendix A**.

### SECTION 8.0 – STORMWATER PONDS

As previously noted in **Section 6.0**, the corridor was originally designed to accommodate a 6lane configuration. Additionally, the majority of the existing ponds were sized to treat one inch over the basin, not the impervious area only. This has allowed new impervious area beyond the existing 6-lanes to be accounted for since treatment is based on the greater of the two scenarios; one inch over the basin or 2.5-inches over the impervious area. Three pond alternatives have only been provided for Basin 2A-2 and Basin FGB due to the impacts to the existing Pond 2A-2 and the new Livingston Road interchange. Seasonal high-water elevations were determined from the best available information which was typically either as-built information or permit documentation. Where feasible existing FDOT parcels were considered for pond alternatives. The location of the FDOT owned parcels haven been called out on the proposed drainage maps provided in **Appendix A**. The required treatment and attenuation volumes are included on the pond sizing calculation sheets provided in **Appendix C**. The preferred alternative interchange alignment was utilized for determining storage requirements. Impacts to existing ponds was also factored into the analysis. The impacted volumes were combined with the required treatment and attenuation volumes as noted on the calculations provided in Appendix B. As noted in Section 5.0 of this report, no joint use or regional opportunities were identified as part of the environmental look around process. A brief synopsis of the concerns and outstanding features related to each pond alternative is also provided in the paragraphs that follow and the evaluation matrix has been included in **Appendix E**. The location of all pond alternatives has been shown on the proposed drainage maps included in **Appendix A**.

### 8.1.1 Basin 2A-2

With the proposed Livingston Road interchange impacting the existing Pond 2A-2, three pond alternatives have been provided. Pond alternative 1 utilizes the infield area and large parcel of land immediately south of the proposed interchange on the east side of the Western Beltway. The pond will be located within the same parcel of land being acquired for the new interchange. Therefore, it is anticipated that the pond will be placed within a remnant piece of the parcel. This alternative is similar to the existing pond, therefore the seasonal high water table elevation of 101.50-ft and other design data from the original pond design was utilized. Alternative 1 will impact an existing electric corridor, which will require to be relocated. Pond alternative 2 and 3 utilize a FDOT remnant parcel located on the west side of Western Beltway.

Pond Alternative 2 would require an additional parcel from the Indian Creek Homeowners Association. Additionally, alternative 2 would require compensation for wetland impacts and additional floodplain storage for lost storage space in existing Pond 2A-2. During the geotechnical site evaluation, the area was inundated with water. Pond 2A-2 is located upstream with a seasonal high water elevation of 101.50-ft, therefore that value was used for the analysis.

Pond alternative 3 would require an additional parcel from the Tohopekaliga Water Authority. Additionally, alternative 3 would require compensation for wetland impacts and additional floodplain storage for lost storage space in existing Pond 2A-2. Pond 2A-2 is located upstream with a seasonal high water elevation of 101.50-ft, therefore that value was used for the analysis.

### 8.1.2 Basin FGB

The improvements to Formosa Gardens Boulevard will require treatment and attenuation. As previously mentioned, the existing 2-lanes are currently treated within a wet detention pond located within the residential community immediately east of the roadway. One possible alternative (Alternative 1) is to provide treatment and attenuation for the proposed 2-lane expansion within this existing pond. The peak stage within the pond for the 100-yr, 72-hr event is 105.60-ft (NGVD-29) with a finish floor elevation of 107.00-ft (NGVD-29). Proposed attenuation for this storm event is anticipated to require 4.60 ac-ft of volume. This would potentially increase the stage within the pond to 106.20-ft (NGVD-29) for the 100-yr event.

Alternative 2 is to provide treatment and attenuation for Formosa Gardens Boulevard within proposed Pond 2A-2 located within the Livingston Road interchange. This pond alternative is only viable if the preferred alternative for Pond 2A-2 is selected, and it is not necessary to reroute the Indian Creek subdivision in FTE right-of-way for treatment and attenuation.

Pond alternative 3 is to provide a pond located in the northwest quadrant of the intersection of Livingston Road and Formosa Gardens Boulevard. This location will utilize an anticipated

remnant parcel required for the Livingston Road interchange. An outfall pipe will need to be constructed within the border width of the proposed interchange to the current outfall of Pond 2A-2. Based on a preliminary geotechnical evaluation the seasonal high water table is approximately 4-ft below the surface, at approximately elevation 108.00-ft.

### SECTION 9.0 – RESULTS

The analysis presented in this report identified potential pond sites based on recent aerials and other preliminary data. Once the potential pond sites were narrowed down to three alternatives, a more detailed analysis was conducted utilizing the following parameters: right of way requirements, easement requirements, atypical construction costs for a given pond site, hazardous materials, threatened endangered & significant species, maintenance, cultural resources, wetland impacts, floodplain impacts and impacts to other relevant features as noted in the pond stie evaluation matrix provided in **Appendix E**. In conjunction with this analysis, a *Contamination Screening Evaluation Report, Natural Resource Evaluation*, and a *Cultural Resource Assessment Survey* were prepared and are provided under separate cover with this submittal. The preferred alternative for each basin and anticipated right of way needs associated with the preferred alternatives are outlined in **Table 9**. The evaluation matrix which contains the details of the analysis has been provided in **Appendix E**.

Basin	Preferred Alternative	Anticipated Right of Way Requirements (acres)	Total Cost
2A-2	1	12.42 <sup>1,2</sup>	\$6,426,744
FGB (Basin B)	3	4.80 <sup>1</sup>	\$1,048,101

#### Table 8: Preferred Pond Alternatives and Anticipated Right of Way

1. Pond to be placed within remnant parcel of land being purchased for proposed roadway alignment.

2. A portion of proposed Pond 2A-2 will be located within the existing right-of-way.

### SECTION 10.0 – CONCLUSIONS


As part of this analysis, pond site alternatives were analyzed for two basins. The previous sections of this report and the evaluation matrix included in **Appendix E** summarize the results of the analysis. A preferred alternative was selected based off of this analysis with the selection and estimated right of way needs summarized in **Table 8** provided in the previous section. It should be noted that the information contained herein is preliminary and will need to be refined once this project enters the design phase.


### SECTION 11.0 – REFERENCES

FDOT Drainage Design Guide, 2022 FDOT Drainage Manual, 2022 ERP Applicant's Handbook Volume I, 2018 SFWMD ERP Applicant's Handbook Volume II, 2016 FDOT Project Development and Environment Manual, 2020

## APPENDIX A – DRAINAGE MAPS


Pond Siting Report Widening Western Beltway PD&E Study from Interstate 4 to Seidel Road Florida's Turnpike Enterprise Financial Project ID 446164-1-22-01






5:10:48 PM SC

BASIN B-4	
HILL ROAD OND B-4	
50 m m	
DSA GARDENS BLVD	
AVD.	
BASIN B-4	
Allanna 1	
a section of the sect	
· · · · · ·	
1	
N/ N/ WETLANDS	
100 YEAR FLOODPLAIN	
500 YEAR FLOODPLAIN	
AF XX 100 YEAR FLOOD ZONE/ELEVA	TION
EXISTING	SHEET NO.
DRAINAGE MAP	2




(1/9/2022 5:10:55 PM ScottE

EAND DR	400
	****************
WETLANDS FLOW ARROW 100 YEAR FLOODPLAIN 500 YEAR FLOODPLAIN	
AF XX 100 YEAR FLOOD ZONE/ELEVA	TION
EXISTING DRAINAGE MAP	SHEET NO. 3



5:11:04 PM


ING OAK GRADIN E AE JON 2A-3	The second se	= 400
	WETLANDS FLOW ARROW	
	100 YEAR FLOODPLAIN	
	500 YEAR FLOODPLAIN	
AF XX	100 YEAR FLOOD ZONE/ELEVAT	TION
	EXISTING AINAGE MAP	SHEET NO. 4




1/9/2022 5:11:11

ũ i

ΡM




Mo 5:11:19




1/9/2022 5:11:27 PM ScottE

ND-11B POND-11D	= 400
M       WETLANDS         Image: WETLANDS       FLOW ARROW         Image: WETLANDS       100 YEAR FLOODPLAIN         Image: Soon YEAR FLOODPLAIN       500 YEAR FLOODPLAIN	
AF XX 100 YEAR FLOOD ZONE/ELEVA	TION
EXISTING DRAINAGE MAP	SHEET NO. 7




Sc PM 5:11:35

	_
** ** ** **	
510	
REEDY CREEK RAPID INFLITRATION BASINS	
and a second	
W WETLANDS FLOW ARROW	
FLOW ARROW 100 YEAR FLOODPLAIN	




5:11:45 PM Scott w\scotte\d034678


The second	
the mark more of	
5	
570	
1, 5, 1, 1, 1	
NK NK WETLANDS	
> FLOW ARROW	
100 YEAR FLOODPLAIN	
500 YEAR FLOODPLAIN	
AF XX 100 YEAR FLOOD ZONE/ELEVA	TION
EXISTING	SHEET NO.
DRAINAGE MAP	9




9/2022 5:11:53 PM ScottE w work\rsh pw\scotte\d0346785\DRMPRD




9/2022 5:12:02 PM ScottE w work/reb ow/scotte2d03467855DBMDB1




222 5:12:56 PM ScottE work\rsh\_pw\scotte\d0346785\DRMPR







1/2022 5:13:09 PM Scot




	Turne Steen B	JAD C
		20.00
		278+(
	ROLLING OAKS MASS GRADING	11 LINE 278+00.00
	ZONE AE (EL. 104.3) BASIN 2A-3	
		1
ماه ماه		
	FLOW ARROW	
	100 YEAR FLOODPLAIN	
	500 YEAR FLOODPLAIN	
AF XX	100 YEAR FLOOD ZONE/ELEVAT	<b>FION</b>
	PROPOSED	SHEET NO.
D	RAINAGE MAP	15




Mo 5:13:21



2022 5:13:28 PM ScottE / work\rsh pw\scotte\d0346785\DRMPR





9/2022 5:13:35 PM ScottE num worthreb num scotterAd02467855 DBM




5:13:

REEDY CREEK RAPID INFILT RATION BASINS	, " <u>400</u>
5,10 ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	MATCH LINE 518+32.80
VETLANDS	
100 YEAR FLOODPLAIN	
500 YEAR FLOODPLAIN	
AF XX 100 YEAR FLOOD ZONE/ELEVA	TION
PROPOSED	SHEET NO.
DRAINAGE MAP	19





/9/2022 5 \pw\_work\rsh\_pw



/2022 5:14:00 PM ScottE

	* 400
ZONE AE (EL. 103.2) END STUDY AREA	
ZONE AE EL. 103.2)	
WETLANDS       VWETLANDS       VWETLANDS       FLOW ARROW       100 YEAR FLOODPLAIN	
500 YEAR FLOODPLAIN AF XX 100 YEAR FLOOD ZONE/ELEVA	TION
PROPOSED DRAINAGE MAP	SHEET NO. 22

# APPENDIX B – PRE-DEVELOPMENT CALCULATIONS

Pond Siting Report Widening Western Beltway PD&E Study from Interstate 4 to Seidel Road Florida's Turnpike Enterprise Financial Project ID 446164-1-22-01 Existing Development: Basin F-4 Stations 54+00 to 80+40

<u>*Project:*</u> Widen Western Beltway PD&E <u>*Project* No</u>.: 446164-1-22-01 Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Basin F–4</u>				
Impervious Area	A	14.13	98	1384.74
Pervious	A	17.62	48	845.76
Pervious	D	0.00	80	0.00
Water		4.57	100	457.00
		36.32		2687.50
		CN=		74.0
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention				
1" Over Total Project Area		1	36.32	3.03
2.5" Over Project Impervious Areas (Exclude Po	onds)	2.5	14.13	2.94
	Treatment Vo	lume Required	(ac.ft.) =	3.03
	Treatment Vo	lume Provided	(ac.ft.) =	3.36

#### Existing Development: Basin B-2

Stations 80+40 to 101+00

<u>*Project:*</u> Widen Western Beltway PD&E <u>*Project No.*</u>: 446164–1–22–01 Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>		2.54	10	160.40
Open Space-Good Condition	A	3.51	48	168.48
	D	0.00	80	0.00
Pavement	A	8.08	98	791.84
	D	0.00	98	0.00
Pond	A	3.45	100	345.00
	D	0.00	100	0.00
		15.04	-	1305.32
		CN=		86.8
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention				
1" Over Total Project Area		1	15.04	1.25
2.5" Over Project Impervious Areas (Excl	ude Ponds)	2.5	8.08	1.68
	Treatment V	olume Required/	(ac.ft.) =	1.68
	Treatment \	/olume Provided	(ac.ft.) =	1.78

#### <u>NOTES:</u>

1. Based on Interstate 4/SR 429 Aux Lane proposed condition

Existing Development: Basin B-3-A, B-3-B, B-3-C, B-3-D, B-5

Stations 101+00 to 141+50

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

	LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
Impervious Area Pervious Pervious Water	<u>Basin B-3-A</u>	A A D	5.70 2.03 0.00 1.28 9.01	98 48 80 100	558.60 97.44 0.00 128.00 784.04
Impervious Area Pervious Pervious Water	<u>Basin B-3-B</u>	A A D	1.73 2.71 0.00 0.29 4.73	98 48 80 100	169.54 130.08 0.00 29.00 328.62
Impervious Area Pervious Pervious Water	<u>Basin B-3-C</u>	A A D	2.41 5.46 0.00 0.00 7.87	98 48 80 100	236.18 262.08 0.00 0.00 498.26
Impervious Area Pervious Pervious Water	<u>Basin B-3-D</u>	A A D	2.73 3.21 0.00 0.00 5.94	98 48 80 100	267.54 154.08 0.00 0.00 421.62
Impervious Area Pervious Pervious Water	<u>Basin B-5</u>	A A D	2.10 6.71 0.00 <u>3.60</u> 12.41	98 48 80 100	205.80 322.08 0.00 360.00 887.88
	ATER QUALITY		CN= CRITERIA (IN)	AREA (AC)	73.1 TREATMENT (AC.FT.)
Wet Detention 1" Over Total Pro 2.5" Over Project	ject Area Impervious Areas (Exclude Pon	ds)	1 2.5	39.96 14.67	3.33 3.06
			olume Required Dlume Provided		

#### Existing Development: Basin B-4

Stations 141+50 to 167+00 (180+00)

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Basin B-4</u> Impervious Area Pervious Pervious Water	A A D	10.85 7.79 1.66 2.60 22.90	98 48 80 100	1063.30 373.92 132.80 260.00 1830.02
WATER QUALITY		CRITERIA (IN)	AREA (AC)	79.9 TREATMENT (AC.FT.)
Wet Detention 1" Over Total Project Area 2.5" Over Project Impervious Areas (Exclude P	onds)	1 2.5	22.90 10.85	1.91 2.26
	Treatment Voi Treatment Vo	lume Required lume Provided		

Existing Development: Basin B-6-A, B-6-B, B-6-C

Stations 101+00 to 125+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

	LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
Impervious Area Pervious Pervious Water	Basin B-6-A	A A D	0.74 3.23 0.41 3.33	98 48 80 100	72.52 155.04 32.80 333.00
Impervious Area Pervious Pervious Water	<u>Basin B-6-B</u>	A A D	7.71 3.42 4.49 0.00 0.00 7.91	98 48 80 100	593.36 335.16 215.52 0.00 0.00 550.68
Impervious Area Pervious Pervious Water	<u>Basin B-6-C</u>	A A D	2.16 3.59 0.00 0.00 5.75 <b>CN=</b>	98 48 80 100	211.68 172.32 0.00 0.00 384.00 71.5
	VATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention 1" Over Total Pro 2.5" Over Project	ject Area Impervious Areas (Exclude P	onds)	1 2.5	21.37 6.32	1.78 1.32
			lume Required lume Provided		

<u>Existing</u>	Development:	Basin W	lyndham	Palms	Basin 1

Stations 198+00 - 213+00

Date: 10/7/2021

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 104-0125-000

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	A	14.55	39	567.45
Pavement	А	14.20	98	1391.60
Pond	A	0.85	98	83.30
		29.60		2042.35
		CN=		69.0
		CRITERIA	AREA	TREATMENT
WATER QUALITY		(IN)	(AC)	(AC.FT.)
1" Over Total Project Area		1	29.60	2.47
2.5" Over Project Impervious Areas (Exc	lude Ponds)	2.5	14.20	2.96
Treatment Volume=Greater of Two Value	es (ac.ft.)	Treatment	Volume=	2.96
TIME OF CONCENTRATION	LENGTH (FT)	VELOCITY (FT/S)		TC (MIN)
Sheet Flow	Assume 1	5 minutes		15.0
Ditch Flow	N/A	N/A		
Pipe Flow	N/A	N/A		
		Time of (	Conc.=	15.0

#### Existing Development: Wyndham Palms Basin B-2

Stations 198+00 - 213+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 104–0125–000

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	A	3.09	39	120.51
Dreamer's Drive	A	1.10	98	107.80
Wyndham Pavement	A	1.20	98	117.60
Pond	A	0.71	98	69.58
		6.10		415.49
		CN=		68.1
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
1" Over Total Project Area		1	6.10	0.51
2.5" Over Project Impervious Areas (Ex	clude Ponds)	2.5	2.30	0.48
Treatment Volume=Greater of Two Value	es (ac.ft.)	Treatment	Volume=	0.51
TIME OF CONCENTRATION	LENGTH (FT)	VELOCITY (FT/S)		TC (MIN)
Sheet Flow	Assume 1	5 minutes		15.0
Ditch Flow	N/A	N/A		
Pipe Flow	N/A	N/A		
		Time of	_	15.0

#### Date: 10/7/2021

<u>Existing</u>	Development:	W	yndham	Palms	Basin	B-3

Stations 198+00 - 213+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 104-0125-000

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	A	3.09	39	120.51
		3.09		120.51
		CN=		39.0
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
1" Over Total Project Area		1	3.09	0.26
2.5" Over Project Impervious Areas (Excl	lude Ponds)	2.5	0.00	0.00
Treatment Volume=Greater of Two Value.	s (ac.ft.)	Treatment	/olume=	0.26
TIME OF CONCENTRATION	LENGTH (FT)	VELOCITY (FT/S)		TC (MIN)
Sheet Flow	Assume 1	5 minutes		15.0
Ditch Flow	N/A	N/A		
Pipe Flow	N/A	N/A		

Time of Conc.= 15.0

Date: 10/7/2021

Existing Development: Basin 2A-2 Stations 180+00 - 268+00

Project: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

*Date:* 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	А	11.61	39	452.79
	D	14.03	80	1122.40
Pavement	А	12.59	98	1233.82
	D	6.70	98	656.60
Future Pavement	A	6.93	98	679.14
	D	3.82	98	374.36
Pond	A	4.97	98	487.06
	D	6.97	98	683.06
Wyndham Palms (Triangle Offsite)				
Woods – Grass Combination Fair	А	4.67	43	200.81
Dreamer's Drive	А	0.62	98	60.76
Sandhill	А	1.10	98	107.80
Treatment Plant (Offsite)				
Woods – Grass Combination Fair	A	29.07	43	1250.01
Offeite				
<u>Offsite</u>	Δ	10.04	26	202.04
Woods Fair	A	10.94	36	393.84
Sand Hill Road Pavement	Δ	0.98	98	96.04
Funie Steed Road	A	0.96	90	90.04
	Δ	0.46	00	15.00
Pavement	A	0.46	98	45.08
Oak Island Cove	٨	1005	77	1205 15
Res. 1/8 acre or less (65% Imp)	A	16.95	77 92	1305.15
	D	2.14	92	196.88
		134.55		9345.60
		CN=		69.5
		CRITERIA	AREA	TREATMENT
WATER QUALITY		(IN)	(AC)	(AC.FT.)
Wet Detention				
1" Over Total Project Area 2.5" Over Project Impervious Areas (Excl	ude Ponds)	1 2.5	134.55 45.61	11.21 9.50
	Treatment Vo	lume Required	(ac.ft.) =	11.21
	<b>_</b> ,		, <u>,</u> , ,	
	Treatment Vo	olume Provided	(ac.tt.) =	11.62

Existing Development: Basin 2A-3 Stations 268+00 - 320+50

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

*Date:* 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	A	22.21	39	866.19
Pavement	A	12.91	98	1265.18
	D	1.40	98	137.20
Future Pavement	A	5.91	98	579.18
	D	0.73	98	71.54
Pond	A	4.71	98	461.58
<u>Offsite</u>				
Woods	A	12.32	36	443.52
SR 530/US 192				
Pavement	A	1.20	98	117.60
Open Space-Good Condition	A	0.91	39	35.49
		62.30	=	3977.48
		CN=		63.8
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention				
1" Over Total Project Area		1	62.30	5.19
2.5" Over Project Impervious Areas (Exc	lude Ponds)	2.5	22.15	4.61
	Treatment Vo	olume Required	(ac.ft.) =	5.19
	Treatment Vo	olume Provided	(ac.ft.) =	5.43

Existing Development: Basin 2B-1

Stations 320+50 - 1359+00

<u>*Project*</u>: Widen Western Beltway PD&E <u>*Project No.*</u>: 446164–1–22–01 Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	A	4.04	39	157.56
	С	5.87	74	434.38
	D	3.38	80	270.40
Pavement	A	2.94	98	288.12
	С	7.36	98	721.28
	D	3.79	98	371.42
Future Pavement	A	2.73	98	267.54
	С	1.47	98	144.06
	D	2.28	98	223.44
Pond	А	3.50	98	343.00
	С	5.07	98	496.86
	D	2.92	98	286.16
SR 530/US 192				
Pavement	А	1.74	98	170.52
Open Space-Good Condition	A	1.75	39	68.25
		48.84	-	4242.99
		CN=		86.9

WATER QUALITY	CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention			
1" Over Total Project Area	1	48.84	4.07
2.5" Over Project Impervious Areas (Exclude Ponds)	2.5	22.31	4.65
		_	
Treatment Vo	lume Required	(ac.ft.) =	4.65

Treatment Volume Provided (ac.ft.) = 4.81

Existing Development: Basin 2B-2 Stations 1359+00 - 414+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	С	2.91	74	215.34
	D	1.31	80	104.80
Toll Facility	D	0.86	98	84.28
Pavement	С	5.83	98	571.34
	D	4.40	98	431.20
Future Pavement	С	2.28	98	223.44
	D	1.09	98	106.82
Pond	С	1.78	98	174.44
	D	0.79	98	77.42
Section 3 (Sta. 400+00 - 414+00)				
Pavement	С	1.28	98	125.44
	D	2.24	98	219.52
Future Pavement	C	0.65	98	63.70
	D	1.15	98	112.70
	_	26.57	:	2510.44
		CN=		94.5
		CRITERIA	AREA	TREATMENT
WATER QUALITY		(IN)	(AC)	(AC.FT.)
Wet Detention 1" Over Total Project Area		1	26.57	2.21
2.5" Over Project Impervious Areas (Exclu	ıde Ponds)	2.5	20.37 19.78	4.12
	4.12			

Treatment Volume Provided (ac.ft.) = 4.25

Existing Development: Basin 10 Stations 414+00 - 445+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	А	8.20	49	401.80
Pavement	A	8.40	98	823.20
Pond	A	4.50	100	450.00
FUTU	A	4.50	100	430.00
<u>Offsite</u>				
Woods (grove)–Poor	A	14.80	57	843.60
	<i>,</i> ,	35.90	-	2518.60
		55.90		2510.00
		CN=		70.2
		CRITERIA	AREA	TREATMENT
WATER QUALITY		(IN)	(AC)	(AC.FT.)
Dry Retention		· · ·	· · ·	
50% of 1" Over Total Project Area		1	35.90	1.50
50% of 2.5" Over Project Impervious Areas (Ex	clude Ponds)	2.5	8.40	0.88
50% of 2.5 over thojett impervious Areus (Ex		2.5	0.40	0.00
	Treatment Vol	ume Required	(ac.ft.) =	1.50
	<u> </u>		<i>( c</i> , )	
	Treatment Vol	ume Provided	(ac.ft.) =	1.60

## Existing Development: Basin 11A Stations 435+00 - 455+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	6.00	49	294.00
	С	0.20	79	15.80
Pavement	А	6.20	98	607.60
Pond	А	4.90	100	490.00
		17.30		1407.40
		CN=		81.4
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention				
50% of 1" Over Total Project Area		1	17.30	0.72
	xclude Ponds)	1 2.5	17.30 6.20	0.72 0.65
50% of 1" Over Total Project Area	xclude Ponds) <b>Treatment Vol</b>		6.20	0.65
50% of 1" Over Total Project Area		ume Required	6.20 (ac.ft.) =	0.65 <b>0.72</b>

## Existing Development: Basin 11B Stations 455+00 - 490+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

## Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	5.90	49	289.10
	С	0.70	79	55.30
	D	0.40	84	33.60
Pavement	A	7.60	98	744.80
Pond	A	2.20	100	220.00
		16.80		1342.80
		CN=		79.9
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention				
50% of 1" Over Total Project Area		1	16.80	0.70
50% of 2.5" Over Project Impervious Areas (Exc	lude Ponds)	2.5	7.60	0.79
	Treatment Vol	ume Required	(ac.ft.) =	0.79
	Treatment Vol	ume Provided	(ac.ft.) =	0.69

## Existing Development: Basin 11C Stations 438+00 - 457+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

SCS CLASS	AREA (AC)	CN	PRODUCT
A	5.00	49	245.00
С	2.90	79	229.10
A	3.90	98	382.20
A	1.60	100	160.00
	13.40		1016.30
	CN=		75.8
	CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
	1	13.40	0.56
clude Ponds)	2.5	3.90	0.41
Treatment Vol	ume Required	(ac.ft.) =	0.56
Treatment Vol	ume Provided	(ac.ft.) =	0.54
	CLASS A C A A A C Treatment Vol	CLASS         (AC)           A         5.00           C         2.90           A         3.90           A         1.60           13.40         Image: CRITERIA (IN)           Clude Ponds)         1           1         2.5           Treatment Volume Required	CLASS         (AC)         CN           A         5.00         49           C         2.90         79           A         3.90         98           A         1.60         100           13.40         Image: CRITERIA AREA (IN)         AREA (AC)           1         13.40         13.40

## Existing Development: Basin 11D Stations 457+00 - 474+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	7.30	49	357.70
	С	0.20	79	15.80
Pavement	A	6.20	98	607.60
Pond	A	2.50	100	250.00
		16.20		1231.10
		CN=		76.0
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention				
50% of 1" Over Total Project Area		1	16.20	0.68
50% of 2.5" Over Project Impervious Areas (Ex	clude Ponds)	2.5	6.20	0.65
	Treatment Vol	ume Required	(ac.ft.) =	0.68
	Treatment Vol	ume Provided	(ac.ft.) =	0.81

Existing Development: Basin 12 Stations 474+00 - 490+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

*Date:* 7/12/2022

Basin Info:

LAND USE	SCS CLASS		AREA (AC)	CN	PRODUCT
<u>Onsite</u>					
Open Space-Fair Condition	A		5.70	49	279.30
	С		1.20	79	94.80
Woods (grove)-Fair	A		4.70	43	202.10
Pavement	A		6.70	98	656.60
Pond	A		1.80	100	180.00
		=	20.10	=	1412.80
		C	CN=		70.3
WATER QUALITY			CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention					
1" Over Total Project Area			1	20.10	1.68
2.5" Over Project Impervious Areas (Exclu	ıde Ponds)		2.5	6.70	1.40
	Treatment	Volu	me Requirea	(ac.ft.) =	1.68
	Treatment	Volu	ıme Providea	(ac.ft.) =	1.80

Existing Development: Basin 13 & 13A Stations 490+00 - 574+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
Basin 13A				
<u>Onsite</u>				
Open Space-Fair Condition	A	26.70	49	1308.30
	В	0.50	69	34.50
	С	0.30	79	23.70
Pavement	A	25.80	98	2528.40
Offsite				
Tree Farm-Poor Condition	A	9.50	57	541.50
	, ,	62.80	57	4436.40
		02.00		4490.40
		CN=		70.6
Basin 13				
<u>Onsite</u>				
Open Space-Fair Condition	A	1.50	49	73.50
	С	1.30	79	102.70
Pond	A	6.20	100	620.00
		9.00		796.20
		CN=		88.5
WATER QUALITY		CRITERIA	AREA	TREATMENT
		(IN)	(AC)	(AC.FT.)
Wet Detention				
1" Over Total Project Area		1	71.80	5.98
2.5" Over Project Impervious Areas (Exclude Po	onas)	2.5	25.80	5.38
	Treatment V	olume Required	(ac.ft.) =	5.98
		•		
	Treatment V	'olume Provided	(ac.ft.) =	6.10

Existing Development: Basin 14A Stations 530+00 - 585+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u> Open Space-Fair Condition Pavement Pond	A A A	15.00 4.10 <u>1.90</u> 21.00	49 98 100	735.00 401.80 190.00 1326.80
		CN=		63.2
<u>Compensatory Treatment</u> (Hartzog Road) Pavement	A	0.80	98	78.40
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention 50% of 1" Over Total Project Area 50% of 2.5" Over Project Impervious Areas (E>	(clude Ponds)	1 2.5	21.00 4.90	0.88 0.51
	Treatment Vol	ume Required	(ac.ft.) =	0.88
	Treatment Vol	ume Provided	(ac.ft.) =	1.03

Existing Development: Basin 14B Stations 587+00 - 590+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u> Woods (Poor) Pavement Pond	A A A	5.90 1.10 1.00 8.00	45 98 100	265.50 107.80 100.00 473.30
		CN=		59.2
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention 50% of 1" Over Total Project Area 50% of 2.5" Over Project Impervious Area	as (Exclude Ponds)	1 2.5	8.00 1.10	0.33 0.11
	Treatment Vol	ume Required	(ac.ft.) =	0.33
	Treatment Vol	ume Provided	(ac.ft.) =	0.44

Existing Development: Basin 14C Stations 574+00 - 595+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

## Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	7.70	49	377.30
Pavement	A	7.70	98	754.60
Pond	A	1.40	100	140.00
		16.80		1271.90
		CN=		75.7
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention				
50% of 1" Over Total Project Area		1	16.80	0.70
50% of 2.5" Over Project Impervious Areas (Ex	clude Ponds)	2.5	7.70	0.80
	Treatment Vol	ume Required	(ac.ft.) =	0.80
	Treatment Vol	ume Provided	(ac.ft.) =	0.80

Existing Development: Basin 15A Stations 595+00 - 618+00

<u>Project</u>: Widen Western Beltway PD&E Project No.: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Closed Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
Basin 15A <u>Onsite</u>				
Open Space-Fair Condition Pavement Pond	A A A	7.40 5.20 5.10	49 98 100	362.60 509.60 510.00
<u>Offsite</u> Grove-Good Condition Meadow	A A	5.80 4.40 27.90	32 30	185.60 132.00 1699.80
		CN=		60.9
Basin 15F <u>Onsite</u>				
Meadow Pavement	A A	9.00 0.50 9.50	30 98	270.00 49.00 319.00
		CN=		33.6

WATER QUALITY	CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention			
50% of 1" Over Total Project Area	1	37.40	1.56
50% of 2.5" Over Project Impervious Areas (Exclude Ponds)	2.5	5.70	0.59
Treatment Volu	ume Required	(ac.ft.) =	1.56

Treatment Volume Provided (ac.ft.) = 1.57 Existing Development: Basin 15B Stations 595+00 - 618+00

<u>Project</u>: Widen Western Beltway PD&E Project No.: 446164-1-22-01

Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	5.70	49	279.30
Open Space-Fair Condition	С	1.30	79	102.70
Open Space-Fair Condition	D	0.40	84	33.60
Pavement	A	8.00	98	784.00
Pond	A	3.00	100	300.00
<u>Offsite</u>				
Grove-Good Condition	А	1.60	43	68.80
Meadow	А	9.10	30	273.00
Grove-Good Condition	С	0.60	72	43.20
Grove-Good Condition	D	1.00	79	79.00
		30.70		1963.60
		CN=		64.0
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention 50% of 1" Over Total Project Area 50% of 2.5" Over Project Impervious Areas (E)	xclude Ponds)	1 2.5	30.70 8.00	1.28 0.83
	Treatment Vol	ume Required	(ac.ft.) =	1.28
	Treatment Vol	lume Provided	(ac.ft.) =	1.68

Existing Development: Basin 15C Stations 595+00 - 618+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

SCS CLASS	AREA (AC)	CN	PRODUCT
A	1.50	49	73.50
С	0.70	79	55.30
D	0.40	84	33.60
A	0.40	98	39.20
А	0.50	100	50.00
	3.50		251.60
	CN=		71.9
	CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
	1	3.50	0.15
clude Ponds)	2.5	0.40	0.04
Treatment Vol	ume Required	(ac.ft.) =	0.15
Treatment Vol	ume Provided	(ac.ft.) =	0.32
	CLASS A C D A A A Treatment Vol	CLASS         (AC)           A         1.50           C         0.70           D         0.40           A         0.50           3.50         3.50           CN=         CRITERIA (IN)           cclude Ponds)         2.5           Treatment Volume Required	CLASS         (AC)         CN           A $1.50$ $49$ C $0.70$ $79$ D $0.40$ $84$ A $0.40$ $98$ A $0.50$ $100$ $3.50$ CN=         CRITERIA         AREA           (IN) $(AC)$ $1$ $3.50$

## Existing Development: Basin 15D Stations 595+00 - 618+00

<u>Project</u>: Widen Western Beltway PD&E Project No.: 446164-1-22-01

Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	А	3.40	49	166.60
Open Space-Fair Condition	С	1.10	79	86.90
Open Space-Fair Condition	D	0.20	84	16.80
Pavement	А	1.70	98	166.60
Pond	А	0.20	100	20.00
Offsite				
Meadow	A	3.70	30	111.00
		10.30		567.90
		CN=		55.1
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention				
50% of 1" Over Total Project Area		1	10.30	0.43
50% of 2.5" Over Project Impervious Areas (E)	(clude Ponds)	2.5	1.70	0.18
	Treatment Vo	lume Required	(ac.ft.) =	0.43
	Treatment Vo	lume Provided	(ac.ft.) =	0.18

## Existing Development: Basin 15E Stations 595+00 - 618+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	А	6.80	49	333.20
Pavement	A	7.10	98	695.80
Pond	A	1.80	100	180.00
	71	1,00	100	100,00
<u>Offsite</u>				
Meadow	А	2.00	32	64.00
Meauow	А		52	
		17.70		1273.00
		CN=		71.9
		CRITERIA	AREA	TREATMENT
WATER QUALITY		(IN)	(AC)	(AC.FT.)
Dry Retention				
50% of 1" Over Total Project Area		1	17.70	0.74
50% of 2.5" Over Project Impervious Areas (Exc	lude Ponds)	2.5	7.10	0.74
		210		0 /
	Treatment Vol	ume Required	(ac.ft.) =	0.74
	Treatment Vol	lume Provided	(ac.ft.) =	0.80

### *Existing Development: Basin 1 Stations 1622+18.86 - 602+00*

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u> Open Space-Fair Condition Pavement Pond	A A A	10.88 8.44 1.72 21.04	39 98 39	424.32 827.12 67.08 1318.52
		CN=		62.7
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
50% of 1" Over Total Project Area 50% of 2.5" Over Project Impervious Areas (Exc	clude Ponds)	1 2.5	21.04 8.44	0.88 0.88
	Treatment Vol	lume Required	(ac.ft.) =	0.88
	Treatment Vo	lume Provided	(ac.ft.) =	1.06

## Existing Development: Basin 2 Stations 602+00 - 641+83.82

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	8.53	39	332.67
Pavement	A	12.01	98	1176.98
Pond	A	2.61	100	261.00
		23.15		1770.65
		CN=		76.5
WATER QUALITY		CRITERIA	AREA	TREATMENT
WATER GOALIN		(IN)	(AC)	(AC.FT.)
Wet Detention	Wet Detenti	onWet Detentio		
1" Over Total Project Area		1	23.15	1.93
2.5" Over Project Impervious Areas (Exclude F	onds)	2.5	12.01	2.50
	Treatment V	olume Required	(ac.ft.) =	2.50
	Treatment V	olume Provided	(ac.ft.) =	2.50

## Existing Development: Basin FGB

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Woods – Grass Combination Fair	A	7.03	43	302.29
Pavement	A	0.00	98	0.00
Pond	A	2.00	43	86.00
<u>Offsite</u>				
Woods – Grass Combination Fair	А	9.43	43	405.49
		18.46		793.78
		CN=		43.0

### Existing Development: SR 530 Basin A Stations 12+83 - 27+60

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>SR 530/US 192</u>				
Open Space-Good Condition	D	10.12	79	799.19
Pavement	A	9.79	98	959.19
Pond	D	1.37	100	136.65
	D	0.93	79	73.40
		22.20		1968.42
		CN=		88.7
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention				
1" Over Total Project Area		1	22.20	1.85
2.5" Over Project Impervious Areas (Excl	ude Ponds)	2.5	9.79	2.04
	Treatment	Volume Requirea	(ac.ft.) =	1.85
	Treatment	Volume Providea	(ac.ft.) =	2.16

## <u>NOTES:</u>

1. Permit states 1.85-acres required, however this does not appear to be the greater of the two calculations.

Existing Development: SR 530 Basin C

Stations 31+70 - 55+00

<u>*Project*</u>: Widen Western Beltway PD&E <u>*Project No.*</u>: 446164–1–22–01 Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>SR 530/US 192</u>				
Pavement	D	9.29	98	910.51
Pond	D	1.85	98	180.99
Grassed Area – Fair	A	8.26	49	404.77
	D	1.11	84	93.40
Pavement	D	3.11	98	304.39
Off-site Impervious	D	1.09	98	106.55
Grassed Area – Fair	D	3.61	84	303.04
Pavement	D	5.53	98	541.95
Off-site Impervious	D	1.04	98	101.46
Grassed Area – Fair	A	3.04	49	148.93
		37.92	-	3096.00
		CN=		81.7
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention		1	37.92	3.16
1" Over Total Project Area 2.5" Over Project Impervious Areas (E.	xclude Ponds)	2.5	20.05	4.18
	Treatment Vo	olume Required	(ac.ft.) =	4.18
	Troatmont V	olume Provided	(acft) =	4.18
	i i eatilient vi	orume i rovrueu	(ac.rc.) -	4.10

## <u>NOTES:</u>

1. CN differs from permit because of a calculation error for the 3.61-ac of Grassed Area.

# APPENDIX C – POST-DEVELOPMENT CALCULATIONS

Pond Siting Report Widening Western Beltway PD&E Study from Interstate 4 to Seidel Road Florida's Turnpike Enterprise Financial Project ID 446164-1-22-01

## Treatment Summary Page: Pre Conditions vs. Post Conditions

Project: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 <u>Company</u>: RS&H

11/4/2022

	Pre Conditions	Post Conditions	
Basin	Treatment Volume Provided (ac.ft.)	Treatment Volume Required (ac.ft.)	Delta (ac-ft)
F-4	3.36	3.26	-0.10
В-2	1.78	1.68	-0.10
B-3 & B-5	3.72	3.66	-0.06
B-4	2.47	2.41	-0.06
В-6	2.03	1.91	-0.12
2A-2	11.62	13.71	2.09
2A-3	5.43	4.86	-0.57
2B-1	4.81	4.65	-0.16
2B-2	4.25	2.64	-1.61
10	1.60	0.89	-0.71
11A	12.54	0.75	-11.79
11B	0.69	0.93	0.24
11C	0.54	0.50	-0.04
11D	0.81	0.66	-0.15
Total 11	14.58	2.85	-11.73
12	1.80	1.47	-0.33
13	6.10	5.98	-0.12
14A	1.03	0.88	-0.16
14B	0.44	0.33	-0.11
14C	0.80	0.83	0.03
15A	1.57	0.77	-0.80
15B	1.68	0.83	-0.85
15C	0.32	0.15	-0.17
15D 15E	0.18 0.80	0.43 0.74	0.25 -0.06
Total 15	4.55	2.92	-0.00
1 1	1.06	0.88	-0.18
2	2.50	2.50	0.00
Basin B (FGB)	-	1.54	1.54
FL 530 (Basin A)	2.16	2.41	0.25
FL 530 (Basin C)	4.18	4.40	0.22

## Attenuation Summary Page: Pre Conditions vs. Post Conditions

Project: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 <u>Company</u>: RS&H

11/4/2022

	Pre Conditions	Post Conditions	
Basin	Runoff Volume (ac.ft.)	Runoff Volume (ac.ft.)	Delta (ac-ft)
F-4	24.37	25.23	0.86
В-2	12.23	12.23	0.00
B-3 & B-5	26.39	29.23	2.84
B-4	16.90	16.94	0.04
В-6	13.72	14.51	0.79
2A-2	103.51	110.11	6.60
2A-3	34.36	34.20	-0.16
2B-1	39.76	37.31	-2.45
2B-2	23.75	21.96	-1.79
10	28.04	18.93	-9.11
11A	13.04	13.89	0.85
11B	12.40	13.62	1.22
11C	9.27	8.73	-0.54
11D	11.24	11.12	-0.12
Total 11	45.95	47.36	1.41
12	12.62	10.79	-1.83
13	45.39	47.10	1.71
14A	-	-	-
14B	-	-	-
14C	11.60	11.74 15.85	0.14 -5.23
15A 15B	21.08 21.52	15.85	-5.23 -4.82
15B 15C	2.81	3.01	0.20
15C 15D	5.98	5.87	-0.11
15E	14.22	11.79	-2.43
Total 15	65.61	53.22	-12.39
1	11.30	11.30	0.00
2	16.19	16.19	0.00
Basin B (FGB)	5.35	8.86	3.51
FL 530 (Basin A)	22.16	22.53	0.37
FL 530 (Basin C)	34.87	35.48	0.61

## Post Development: Basin F-4 Stations 54+00 to 80+40

<u>Project</u>: Widen Western Beltway PD&E <u>Project No</u>.: 446164-1-22-01 Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Basin F-4</u> Impervious Area Pervious Pervious Water	A A D	15.63 16.12 0.00 4.57 36.32	98 48 80 100	1531.74 773.76 0.00 457.00 2762.50
		CN=		76.1
WATER QUALITY		CRITERIA	AREA	TREATMENT
Wet Detention 1" Over Total Project Area 2.5" Over Project Impervious Areas (Exclude	Ponds)	1 2.5	36.32 15.63	3.03 3.26
	Treatment Vo	lume Required	(ac.ft.) =	3.26
	Treatment Volu	ume Permitted	(ac.ft.) =	3.36
	Additional Treati	ment Required	(ac.ft.) =	-0.10
WATER QUANTITY (50-yr/72-hr)	PRE-DEV	ELOPMENT	POST D	EVELOPMENT
Precipitation, in Potential Maximum Retention (S) Runoff Depth (Q), in Runoff Volume, acre-ft Volume Differential, acre-ft	3. 8.	.40 51 05 .37 <b>0.8</b> 6		11.40 3.15 8.33 25.23

<u>NOTES:</u>

## Post Development: Basin B-2

Stations 80+40 to 101+00

<u>*Project:*</u> Widen Western Beltway PD&E <u>*Project No.*</u>: 446164–1–22–01 Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
<u>Onsite</u> Open Space-Good Condition	A	3.51	48	168.48
Pavement	D A	0.00 8.08	80 98	0.00 791.84
New/Future 8-Lane Pavement (Req.	D A	0.00 0.00	98 98	0.00 0.00
treatment) Pond	D A	0.00 3.45	98 100	0.00 345.00
	D	0.00	100	0.00 1305.32
		CN=		86.8
WATER QUALITY		CRITERIA	AREA	TREATMENT
		(IN)	(AC)	(AC.FT.)
Wet Detention 1" Over Total Project Area 2.5" Over Project Impervious Areas (Exc	lude Ponds)	1 2.5	15.04 8.08	1.25 1.68
	Treatment Vo	olume Required	(ac.ft.) =	1.68
	Treatment Vol	ume Permitted	(ac.ft.) =	1.78
Д	dditional Treat	ment Required	(ac.ft.) =	-0.10
WATER QUANTITY (50-yr/72-hr)	PRE-DEV	ELOPMENT	POST D	EVELOPMENT
Precipitation, in		.40		11.40
Potential Maximum Retention (S) Runoff Depth (Q), in		52 76		1.52 9.76
Runoff Volume, acre-ft Volume Differential, acre-ft	12	0.00		12.23

## <u>NOTES:</u>

1. Existing permit assumed paved median. New impervious area does not exceed permitted impervious area.

Post Development: Basin B-3-A, B-3-B, B-3-C, B-3-D, B-5 Stations 101+00 to 141+50

<u>Project</u>: Widen Western Beltway PD&E Project No.: 446164-1-22-01

Date: 7/12/2022

Basin Info:

	LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
Impervious Area Pervious Pervious Water	Basin B-3-A	A A D	7.87 3.05 0.00 1.28 12.20	98 48 80 100	771.26 146.40 0.00 128.00 1045.66
Impervious Area Pervious Pervious Water	<u>Basin B-3-B</u>	A A D	1.93 1.95 0.00 0.29 4.17	98 48 80 100	189.14 93.60 0.00 29.00 311.74
Impervious Area Pervious Pervious Water	<u>Basin B-3-C</u>	A A D	1.91 6.08 0.00 0.00 7.99	98 48 80 100	187.18 291.84 0.00 0.00 479.02
Impervious Area Pervious Pervious Water	<u>Basin B-3-D</u>	A A D	3.21 3.99 0.00 0.00 7.20	98 48 80 100	314.58 191.52 0.00 0.00 506.10
Impervious Area Pervious Pervious Water	<u>Basin B-5</u>	A A D	2.10 6.71 0.00 3.60 12.41	98 48 80 100	205.80 322.08 0.00 360.00 887.88
м	VATER QUALITY		CN= CRITERIA	AREA	73.5 TREATMENT
Wet Detention 1" Over Total Pro		onds)	1 2.5	43.97 17.02	3.66 3.55
		Treatment Vo	ume Required	(ac.ft.) =	3.66
		Treatment Volu	ume Permitted	(ac.ft.) =	3.72
	A	dditional Treatı	ment Required	(ac.ft.) =	-0.06

Post Development: Basin B-3-A, B-3-B, B-3-C, B-3-D, B-5 Stations 101+00 to 141+50

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

WATER QUANTITY (50-yr/72-hr)	PRE-DEVELOPMENT	POST DEVELOPMENT	
	11 40	11.40	
Precipitation, in	11.40	11.40	
Potential Maximum Retention (S)	3.68	3.61	
Runoff Depth (Q), in	7.93	7.98	
Runoff Volume, acre-ft	26.39	29.24	
Volume Differential, acre-ft	2.84		

## <u>NOTES:</u>

## <u>Post Development: Basin B-4</u>

Stations 141+50 to 167+00 (180+00)

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Basin B-4</u> Impervious Area Pervious Pervious Water	A A D	11.57 6.14 1.66 2.60 21.97	98 48 80 100	1133.86 294.72 132.80 260.00 1821.38
		CN=		82.9
WATER QUALITY		CRITERIA	AREA	TREATMENT
Wet Detention 1" Over Total Project Area 2.5" Over Project Impervious Areas (Exclude P	onds)	1 2.5	21.97 11.57	1.83 2.41
	Treatment Vo	lume Required	(ac.ft.) =	2.41
	Treatment Vol	ume Permitted	(ac.ft.) =	2.47
A	dditional Treat	ment Required	(ac.ft.) =	-0.06
WATER QUANTITY (50-yr/72-hr)	PRE-DEV	ELOPMENT	POST D	EVELOPMENT
Precipitation, in Potential Maximum Retention (S) Runoff Depth (Q), in Runoff Volume, acre-ft Volume Differential, acre-ft	2. 8.	.40 51 85 .90 <b>0.0</b> 4		11.40 2.06 9.25 16.94

## <u>NOTES:</u>

1. Pond can be expanded 10 to 15-ft to the east to provide additional attenuation volume with the use of an MSE wall.

Post Development: Basin B-6-A, B-6-B, B-6-C

Stations 101+00 to 125+00 <u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

	LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
Impervious Area Pervious	Basin B-6-A	A A	1.22 3.85	98 48	119.56 184.80
Pervious Water		D	0.41 3.33 8.81	80 100	32.80 333.00 670.16
Impervious Area Pervious	<u>Basin B-6-B</u>	A A	3.44 4.24	98 48	337.12 203.52
Pervious Water		D	0.00 0.00 7.68	80 100	0.00 0.00 540.64
Impervious Area Pervious Pervious Water	<u>Basin B-6-C</u>	A A D	2.04 4.37 0.00 0.00	98 48 80 100	199.92 209.76 0.00 0.00
			6.41 CN=		409.68 <b>70.8</b>
W	ATER QUALITY		CRITERIA	AREA	TREATMENT
Wet Detention 1" Over Total Proj 2.5" Over Project	ect Area Impervious Areas (Exclude	e Ponds)	1 2.5	22.90 6.70	1.91 1.40
		Treatment Vo	lume Required	(ac.ft.) =	1.91
		Treatment Vol	ume Permitted	(ac.ft.) =	2.03
		Additional Treat	ment Required	(ac.ft.) =	-0.12
WATER QU	IANTITY (50-yr/72-hr)	PRE-DEV	ELOPMENT	POST D	EVELOPMENT
Precipitation, in Potential Maximum Runoff Depth (Q), Runoff Volume, ac	in	3 7	1.40 .99 .71 3.72		11.40 4.13 7.60 14.51

## <u>NOTES:</u>

Post Developme	nt: Basin	Wyndham	Palms	Basin	1

Stations 198+00 - 213+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 104–0125–000

SCS CLASS	AREA (AC)	CN	PRODUCT
A	14.55	39	567.45
A	14.20	98	1391.60
A	0.85	98	83.30
	29.60		2042.35
	CN=		69.0
	CRITERIA (IN)	AREA	TREATMENT (AC.FT.)
	1	29.60	2.47
clude Ponds)	2.5	14.20	2.96
es (ac.ft.)	Treatment	Volume=	2.96
LENGTH (FT)	VELOCITY (FT/S)		TC (MIN)
Assume 1	5 minutes		15.0
N/A	N/A		
N/A	N/A		
	A A A S A A A S S S S S S S S S S S S S	A       14.55         A       14.20         A       0.85         29.60       29.60         CRITERIA (IN)         CN=       CRITERIA (IN)         1       1         clude Ponds)       2.5         es (ac.ft.)       Treatment         LENGTH       VELOCITY (FT)         Assume 15 minutes N/A       N/A	A         14.55         39           A         14.20         98           A         0.85         98           29.60         0.85         98           CN=         CRITERIA         AREA           (IN)         (AC)         1           1         29.60         29.60           CN=         CRITERIA         AREA           (IN)         (AC)         1           1         29.60         1           clude Ponds)         2.5         14.20           cs (ac.ft.)         Treatment Volume=           LENGTH         VELOCITY         CRT/S)           Assume 15 minutes         N/A           N/A         N/A

Date: 10/7/2021

## Post Development: Wyndham Palms Basin B-2

Stations 198+00 - 213+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 104–0125–000

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	A	3.09	39	120.51
Dreamer's Drive	A	1.10	98	107.80
Wyndham Pavement	А	1.20	98	117.60
Pond	А	0.71	98	69.58
		6.10		415.49
		CN=		68.1
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
1" Over Total Project Area		1	6.10	0.51
2.5" Over Project Impervious Areas (E)	xclude Ponds)	2.5	2.30	0.48
Treatment Volume=Greater of Two Valu	ues (ac.ft.)	Treatment	Volume=	0.51
TIME OF CONCENTRATION	LENGTH (FT)	VELOCITY (FT/S)		TC (MIN)
Sheet Flow		5 minutes		15.0
Ditch Flow	N/A	N/A		
Pipe Flow	N/A	N/A		
		Time of (		15.0

Date: 10/7/2021

Post Develop	oment: Wy	vndham	Palms	Basin	B-3

Stations 198+00 - 213+00

Date: 10/7/2021

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 104-0125-000

LAND USE	SCS CLASS		AREA (AC)	CN	PRODUCT
<u>Onsite</u>					
Open Space-Good Condition	A		3.09	39	120.51
			3.09		120.51
			CN=		39.0
WATER QUALITY		С	RITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
1" Over Total Project Area			1	3.09	0.26
2.5" Over Project Impervious Areas (Exclud	le Ponds)		2.5	0.00	0.00
Treatment Volume=Greater of Two Values (	ac.ft.)	7	reatment	Volume=	0.26
TIME OF CONCENTRATION	LENGTH (FT)	V	'ELOCITY (FT/S)		TC (MIN)
Sheet Flow	Assume	15 m	inutes		15.0
Ditch Flow	N/A		N/A		
Pipe Flow	N/A		N/A		
			Time of	Conc.=	15.0

Post Pre Development: Basin 2A-2

Stations 180+00 - 268+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	A	7.59	39	296.01
	D	14.03	80	1122.40
Pavement	A	12.59	98	1233.82
	D	6.70	98	656.60
"Future" Pavement (Permitted 6-Lanes)	A	6.93	98	679.14
	D	3.82	98	374.36
New/Future 8-Lane Pavement (Req.	A	6.89	98	675.22
treatment)	D	0.00	98	0.00
Livingston Interchange Pavement	A	0.00	98	0.00
	D	0.00	98	0.00
Woods – Good Cover	D	18.04	77	1389.08
Pond	А	4.97	98	487.06
	D	6.97	98	683.06
Wyndham Palms (Triangle Offsite)				
Woods - Grass Combination Fair	A	4.67	43	200.81
Dreamer's Drive	A	0.62	98	60.76
Sandhill	A	1.10	98	107.80
Treatment Plant (Offsite)			00	10,100
Woods – Grass Combination Fair	A	29.07	43	1250.01
<u>Offsite</u>	,,	23.07	15	1250.01
Woods Fair	A	20.04	36	721.44
Sand Hill Road	71	20.04	50	/ 21.44
Pavement	A	0.98	98	96.04
Funie Steed Road	7	0.50	50	50.04
Pavement	А	0.46	98	45.08
Oak Island Cove	~	0,40	50	45.00
Res. 1/8 acre or less (65% Imp)	A	16.95	77	1305.15
nes. 1/0 acre 01 less (05/0 1111)	D D	2.14	92	196.88
	D	164.56	ゴム	11580.72
		CN=		70.4

## <u>NOTES:</u>

1. Pre vs post require the same basin area, therefore this sheet represents the permitted condition with the additional offsite area required for the new interchange.

#### Post Development: Basin 2A-2 (Alt 1 Preferred) Stations 180+00 - 268+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

Basin Info:

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	А	19.00	39	741.00
	D	14.03	80	1122.40
Pavement	А	12.59	98	1233.82
	D	6.70	98	656.60
"Future" Pavement (Permitted 6-Lanes)	А	6.93	98	679.14
	D	3.82	98	374.36
New/Future 8-Lane Pavement (Req.	А	6.89	98	675.22
treatment)	D	0.00	98	0.00
Livingston Interchange Pavement	А	4.38	98	429.24
5	D	2.82	98	276.36
Woods – Good Cover	D	18.04	77	1389.08
Pond	А	13.37	98	1310.26
	D	0.00	98	0.00
Wyndham Palms (Triangle Offsite)				
Woods – Grass Combination Fair	А	4.67	43	200.81
Dreamer's Drive	А	0.62	98	60.76
Sandhill	А	1.10	98	107.80
Treatment Plant (Offsite)				
Woods – Grass Combination Fair Sand Hill Road	A	29.07	43	1250.01
Pavement	A	0.98	98	96.04
Funie Steed Road				
Pavement	A	0.46	98	45.08
Oak Island Cove				
Res. 1/8 acre or less (65% Imp)	A	16.95	77	1305.15
	D	2.14	92	196.88
		164.56		12150.01
		CN=		73.8

	CN=		/ 3.8
WATER QUALITY	CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention			
1" Over Total Project Area	1	164.56	13.71
2.5" Over Project Impervious Areas (Exclude Ponds)	2.5	59.70	12.44
Treatment Vo	lume Required	l (ac.ft.) =	13.71
Treatment Vol	ume Permitted	l (ac.ft.) =	11.62
Additional Treat	ment Required	l (ac.ft.) =	2.09

Post Development: Basin 2A-2 (Alt 1 Preferred) Stations 180+00 - 268+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

WATER QUANTITY (50-yr/72-hr)	PRE-DEVELOPMENT	POST DE	POST DEVELOPMENT		
Precipitation, in	11.40	1	11.40		
Potential Maximum Retention (S)	4.21	-	3.54		
Runoff Depth (Q), in	7.55		8.03		
Runoff Volume, acre-ft	103.51		110.11		
Volume Differential, acre-ft	6.	60			
POND SIZING					
Pond B	Rottom / Control Elevation =	101.50	FT		
	Top of bank elevation = 106.00 FT				
Area @ pond i	bottom / control elevation =	13.06			
	Area @ Top of bank =	14.32	AC		
Elevation		Area	Volume		
ft		acres	acre-ft		
101.50	Control Elev.	13.06	0.00		
<u>102.60</u> 106.00	Treat. El Inside TOB	13.37 14.32	<b>14.54</b> 61.61		
100.00	THSILE TOB	14.52	01.01		
102.60	Treat. El	13.37	0.00		
103.20	Attenuation El	13.54	8.07		
106.00	Inside TOB	14.32	47.07		
PCID CALCULATIONS (50 yr/72 br)	MAX. ALLOWABLE DISCHARGE RATE				
ID CALCULATIONS (50-yr/72-hr) (BASED ON 13 CFS			MI)		
Precipitation, in		1	2.91		
Area, ac		164.56			
Area, sq-mi		(	0.26		
Peak Allowable Runoff, cfs	3.34				

## <u>NOTES:</u>

1. Basin area changed due to new interchange

2. Used RCID rainfall to avoid drainage fee.

3. SHWT based on permitted elevation for existing Pond 2A-2.

#### <u>Post Development: Basin 2A-2 (Alt 2)</u> Stations 180+00 - 268+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164–1–22–01

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	A	15.89	39	619.71
	D	14.03	80	1122.40
Pavement	A	12.59	98	1233.82
	D	6.70	98	656.60
"Future" Pavement (Permitted 6-Lanes)	А	6.93	98	679.14
	D	3.82	98	374.36
New/Future 8-Lane Pavement (Req.	A	6.89	98	675.22
treatment)	D	0.00	98	0.00
Livingston Interchange Pavement	A	4.38	98	429.24
	D	2.82	98	276.36
Woods – Good Cover	D	18.04	77	1389.08
Pond	А	16.48	98	1615.04
	D	0.00	98	0.00
Wyndham Palms (Triangle Offsite)				
Woods – Grass Combination Fair	A	4.67	43	200.81
Dreamer's Drive	A	0.62	98	60.76
Sandhill	A	1.10	98	107.80
Treatment Plant (Offsite)				
Woods – Grass Combination Fair Sand Hill Road	А	29.07	43	1250.01
Pavement	A	0.98	98	96.04
Funie Steed Road	A	0.90	90	90.04
Pavement	А	0.46	98	45.08
Oak Island Cove	4	0.40	50	45.00
Res. 1/8 acre or less (65% Imp)	А	16.95	77	1305.15
NC3. 1/0 dele 01 1833 (05/0 1111)	D	2.14	92	196.88
	D	164.56	52	12333.50
		104.50		12,00,00
		CN=		74.9

WATER QUALITY	CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention	1	164 56	1 7 7 1
1" Over Total Project Area 2.5" Over Project Impervious Areas (Exclude Ponds)	1 2.5	164.56 59.70	13.71 12.44
Treatment Vo	olume Required	d (ac.ft.) =	13.71
Treatment Vol	lume Permitted	d (ac.ft.) =	11.62
Additional Treat	ment Required	d (ac.ft.) =	2.09

Post Development: Basin 2A-2 (Alt 2) Stations 180+00 - 268+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

WATER QUANTITY (50-yr/72-hr)	PRE-DEVELOPMENT	PRE-DEVELOPMENT POST DEVEL	
Precipitation, in Potential Maximum Retention (S) Runoff Depth (Q), in Runoff Volume, acre-ft Volume Differential, acre-ft	11.4011.404.213.347.558.18103.51112.218.70		3.34 8.18
POND SIZING			
	Bottom / Control Elevation = Top of bank elevation = bottom / control elevation = Area @ Top of bank =	101.50 104.00 15.54 16.48	FT AC
Elevation ft		Area acres	Volume acre-ft
101.50 <u>102.40</u> 104.00	Control Elev. Treat. El Inside TOB	15.54 15.88 16.48	0.00 <b>14.14</b> 40.03
102.40 103.00 104.00	Treat. El Attenuation El Inside TOB	15.88 16.10 16.48	0.00 <b>9.59</b> 25.89
RCID CALCULATIONS (50-yr/72-hr)	MAX. ALLOWABLE D (BASED ON 13 CF		
Precipitation, in Area, ac Area, sq-mi Peak Allowable Runoff, cfs		1	12.91 64.56 0.26 3.34

#### <u>NOTES:</u>

1. Basin area changed due to new interchange

2. Used RCID rainfall to avoid drainage fee.

3. SHWT based on permitted elevation for existing Pond 2A-2.

#### Post Development: Basin 2A-2 (Alt 3)

Stations 180+00 - 268+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	А	16.94	39	660.66
	D	14.03	80	1122.40
Pavement	A	12.59	98	1233.82
	D	6.70	98	656.60
"Future" Pavement (Permitted 6-Lanes)	А	6.93	98	679.14
	D	3.82	98	374.36
New/Future 8-Lane Pavement (Req.	А	6.89	98	675.22
treatment)	D	0.00	98	0.00
Livingston Interchange Pavement	А	4.38	98	429.24
5	D	2.82	98	276.36
Woods – Good Cover	D	18.04	77	1389.08
Pond	А	15.43	98	1512.14
	D	0.00	98	0.00
Wyndham Palms (Triangle Offsite)				
Woods – Grass Combination Fair	А	4.67	43	200.81
Dreamer's Drive	А	0.62	98	60.76
Sandhill	А	1.10	98	107.80
Treatment Plant (Offsite)				
Woods – Grass Combination Fair	А	29.07	43	1250.01
Sand Hill Road				
Pavement	А	0.98	98	96.04
Funie Steed Road		0100	50	
Pavement	А	0.46	98	45.08
Oak Island Cove		0110	50	15100
Res. 1/8 acre or less (65% Imp)	A	16.95	77	1305.15
	D	2.14	92	196.88
	D	164.56	52	12271.55
		104.50		122/1.55
		CN=		74.6
		CRITERIA	AREA	TREATMENT
WATER QUALITY		(1N)	(AC)	(AC ET )

WATER QUALITY	(IN)	(AC)	(AC.FT.)
Wet Detention			
1" Over Total Project Area	1	164.56	13.71
2.5" Over Project Impervious Areas (Exclude Ponds)	2.5	59.70	12.44
Treatment Volu	me Require	ed (ac.ft.) =	13.71
		-	
Treatment Volun	ne Permitte	ed (ac.ft.) =	11.62
Additional Treatme	ent Require	d(acft) =	2.09
	ene negun e		2.05

Post Development: Basin 2A-2 (Alt 3) Stations 180+00 - 268+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

WATER QUANTITY (50-yr/72-hr)	PRE-DEVELOPMENT	POST DE	VELOPMENT
Precipitation, in Potential Maximum Retention (S) Runoff Depth (Q), in Runoff Volume, acre-ft Volume Differential, acre-ft	11.40 4.21 7.55 103.51 <b>7.</b> 9	1	1.40 3.41 8.13 11.51
POND SIZING			
	ottom / Control Elevation = Top of bank elevation = pottom / control elevation = Area @ Top of bank =	101.50 104.00 14.60 15.43	FT AC
Elevation ft		Area acres	Volume acre-ft
101.50 <u>102.50</u> 104.00	Control Elev. Treat. El Inside TOB	14.60 14.93 15.43	0.00 <b>14.77</b> 37.54
102.50 103.05 104.05	Treat. El Attenuation El Inside TOB	14.93 15.11 15.43	0.00 <b>8.26</b> 23.53
RCID CALCULATIONS (50-yr/72-hr)	MAX. ALLOWABLE (BASED ON 13 C		
Precipitation, in Area, ac Area, sq-mi Peak Allowable Runoff, cfs	12.91 164.56 0.26 3.34		

#### <u>NOTES:</u>

1. Basin area changed due to new interchange

2. Used RCID rainfall to avoid drainage fee.

3. SHWT based on permitted elevation for existing Pond 2A-2.

Post Development: Basin 2A-3 Stations 268+00 - 320+50

Project: Widen Western Beltway PD&E Project No.: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	A	21.03	39	820.17
Pavement	A	12.91	98	1265.18
	D	1.40	98	137.20
"Future" Pavement (Permitted 6-Lanes)	A	5.91	98	579.18
	D	0.73	98	71.54
New/Future 8-Lane Pavement (Reg.	A	1.18	98	115.64
treatment)	D	0.00	98	0.00
Pond	A	4.71	98	461.58
Offsite				
Woods	A	0.00	36	0.00
SR 530/US 192				
Pavement	A	1.20	98	117.60
New Pavement	A	0.00	98	0.00
Open Space-Good Condition	A	0.91	39	35.49
		49.98	1	3603.58

		CN=		72.1
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention 1" Over Total Project Area 2.5" Over Project Impervious Areas (Ex	clude Ponds)	1 2.5	49.98 23.33	4.17 4.86
	Treatment Vol	lume Required	(ac.ft.) =	4.86
	Treatment Volu	ume Permitted	(ac.ft.) =	5.43
,	Additional Treati	ment Required	(ac.ft.) =	-0.57
WATER QUANTITY (50-yr/72-hr)	PRE-DEVI	ELOPMENT	POST DI	EVELOPMENT
Precipitation, in		.40		11.40
Potential Maximum Retention (S) Runoff Depth (Q), in	6.	66 62		3.87 7.79
Runoff Volume, acre-ft	34.	.36		32.44

-1.91

#### <u>NOTES:</u>

Volume Differential, acre-ft

1. Reduction in basin area is a result of Rolling Oak commercial property no longer discharging to FTE R/W.

Post Development: Basin 2B-1

Stations 320+50 - 1359+00

Project: Widen Western Beltway PD&E Project No.: 446164-1-22-01

Date: 7/12/2022

9.77

39.76

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	A	4.04	39	157.56
	С	5.87	74	434.38
	D	3.38	80	270.40
Pavement	A	2.94	98	288.12
	С	7.36	98	721.28
	D	3.79	98	371.42
"Future" Pavement (Permitted 6-Lanes)	А	2.73	98	267.54
	С	1.47	98	144.06
	D	2.28	98	223.44
New/Future 8-Lane Pavement (Reg.	А	0.00	98	0.00
treatment)	С	0.00	98	0.00
	D	0.00	98	0.00
Pond	А	3.50	98	343.00
	С	5.07	98	496.86
	D	2.92	98	286.16
SR 530/US 192				
Pavement	A	1.74	98	170.52
Open Space-Good Condition	A	1.75	39	68.25
		48.84		4242.99

	CN=		86.9
WATER QUALITY	CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention 1" Over Total Project Area 2.5" Over Project Impervious Areas (Exclude Pond	1 s) 2.5	48.84 22.31	4.07 4.65
Treatme	ent Volume Require	ed (ac.ft.) =	4.65
Treatmer	nt Volume Permitte	ed (ac.ft.) =	4.81
Additional	Treatment Require	ed (ac.ft.) =	-0.16
WATER QUANTITY (50-yr/72-hr) PRE	-DEVELOPMENT	POST D	EVELOPMENT
Precipitation, in Potential Maximum Retention (S)	11.40 1.51		11.40 1.51

9.77

39.76

0.00

Runoff Depth (Q), in

Runoff Volume, acre-ft

Volume Differential, acre-ft

Post Development: Basin 2B-2

Stations 1359+00 - 414+00

Project: Widen Western Beltway PD&E Project No.: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Good Condition	С	10.04	74	742.96
	D	1.31	80	104.80
Toll Facility	D	0.86	98	84.28
Pavement	С	5.83	98	571.34
	D	4.40	98	431.20
"Future" Pavement (Permitted 6-Lanes)	С	2.28	98	223.44
	D	1.09	98	106.82
New/Future 8-Lane Pavement (Reg.	С	-6.56	98	-642.88
treatment)	D	0.00	98	0.00
Pond	С	1.78	98	174.44
	D	0.79	98	77.42
Section 3 (Sta. 400+00 – 414+00)				
Pavement	С	1.28	98	125.44
	D	2.24	98	219.52
"Future" Pavement (Permitted 6-Lanes)	C	0.65	98	63.70
	D	1.15	98	112.70
New/Future 8-Lane Pavement (Reg.	C	-0.57	98	-55.86
treatment)	D	0.00	98	0.00
		26.57		2339.32

		CN=		88.0
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention 1" Over Total Project Area 2.5" Over Project Impervious Areas (Ex	clude Ponds)	1 2.5	26.57 12.65	2.21 2.64
	Treatment Vol	ume Required	(ac.ft.) =	2.64
	Treatment Volu	ıme Permitted	(ac.ft.) =	4.25
	Additional Treatn	nent Required	(ac.ft.) =	-1.61
WATER QUANTITY (50-yr/72-hr)	PRE-DEVE	LOPMENT	POST DE	VELOPMENT
Precipitation, in Potential Maximum Retention (S) Runoff Depth (Q), in Runoff Volume, acre-ft	11. 0.5 10. 23.	58 7 <i>3</i> 75	2	1.40 1.36 9.92 21.96
Volume Differential, acre-ft		-1.7	9	

1. Assumes the removal of the toll lanes. Assumed toll building and parking lot to remain.

#### Post Development: Basin 10

Stations 414+00 - 445+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

Basin Type: Closed Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	8.05	49	394.45
Pavement (Permitted)	A	8.40	98	823.20
New Pavement (Reg. Treatment)	A	0.15	98	14.70
Pond	A	4.50	100	450.00
Offsite				
Woods (grove)-Poor	A	0.00	57	0.00
-		21.10		1682.35
		CN=		79.7
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention				
50% of 1" Over Total Project Area		1	21.10	0.88
50% of 2.5" Over Project Impervious Areas (Ex	clude Ponds)	2.5	8.55	0.89
	Treatment Vol	ume Required	(ac.ft.) =	0.89
	Treatment Volu	ıme Permitted	(ac.ft.) =	1.60
Ac	lditional Treatr	ment Required	(ac.ft.) =	-0.71

#### <u>NOTES:</u>

1. Reduction in basin area is a result of Flamingo East Village Apartments being treated prior to entering FTE R/W.

2. Apartment exfiltration system discharges into FTE Pond 10.

#### Post Development: Basin 10

Stations 414+00 - 445+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

34.91

Basin Info:

Basin Type: Closed Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	8.05	49	394.45
Pavement (Permitted)	А	8.40	98	823.20
New Pavement (Reg. Treatment)	А	0.15	98	14.70
Pond	A	4.50	100	450.00
<u>Offsite</u>				
Woods (grove)-Poor	A	14.80	57	843.60
		35.90	=	2525.95
		CN=		70.4
WATER QUANTITY (100-yr/240-hr)	PRE-DEVE	ELOPMENT	POST D	EVELOPMENT
Precipitation, in	15.80		15.80	
Potential Maximum Retention (S)	4.25			4.21
Runoff Depth (Q), in	11.		11.67	

34.82

0.10

#### NOTES:

Runoff Volume, acre-ft

Volume Differential, acre-ft

1. Apartment exfiltration system discharges into FTE Pond 10.

### Post Development: Basin 11A Stations 435+00 - 455+00

<u>Project</u>: Widen Western Beltway PD&E Project No.: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	5.82	49	285.18
	С	0.20	79	15.80
Pavement (Permitted)	A	6.20	98	607.60
New Pavement (Req. Treatment)	A	0.98	98	96.04
Pond	A	4.90	100	490.00
		18.10		1494.62
		CN=		82.6
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention				
50% of 1" Over Total Project Area		1	18.10	0.75
50% of 2.5" Over Project Impervious Areas (E	xclude Ponds)	2.5	7.18	0.75
	Treatment Vol	ume Required	(ac.ft.) =	0.75
	Treatment Volu	me Permitted	(ac.ft.) =	12.54
A	dditional Treatn	nent Required	(ac.ft.) =	-11.79
WATER QUANTITY (50-yr/72-hr)	PRE-DEVE	LOPMENT	POST D	EVELOPMENT
Precipitation, in	11.	40		11.40
Potential Maximum Retention (S)	2.2			2.11
Runoff Depth (Q), in	9.0			9.21
Runoff Volume, acre-ft	13.			13.89
Volume Differential, acre-ft		0.8	5	

#### <u>NOTES:</u>

1. Increase in basin area associated with outside NB widening associated with 8-lanes.

#### Post Development: Basin 11B

Stations 455+00 - 490+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	5.76	49	282.24
	С	0.70	79	55.30
	D	0.40	84	33.60
Pavement (Permitted)	A	7.60	98	744.80
New Pavement (Req. Treatment)	A	1.36	98	133.28
Pond	A	2.20	100	220.00
		18.02		1469.22
		CN=		81.5
		CRITERIA	AREA	TREATMENT
WATER QUALITY		(IN)	(AC)	(AC.FT.)
Dry Retention 50% of 1" Over Total Project Area 50% of 2.5" Over Project Impervious Areas (E	xclude Ponds)	1 2.5	18.02 8.96	0.75 0.93
	Treatment Vol	ume Required	(ac.ft.) =	0.93
	Treatment Volu	ıme Permitted	(ac.ft.) =	0.69
A	Additional Treatr	nent Required	(ac.ft.) =	0.24
WATER QUANTITY (50-yr/72-hr)	PRE-DEVI	ELOPMENT	POST D	EVELOPMENT
Precipitation, in	11.	40		11.40
Potential Maximum Retention (S)	2	51		2.27
Runoff Depth (Q), in	8.8	86		9.07
Runoff Volume, acre-ft	12.	40		13.62
Volume Differential, acre-ft		1.2	2	

#### NOTES:

1. Increase in basin area is a result of ramp and side road improvements.

# Post Development: Basin 11C Stations 438+00 - 457+00

<u>Project</u>: Widen Western Beltway PD&E Project No.: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

A	3.58	49	175.42
С	2.90	79	229.10
А	3.90	98	382.20
A	0.01	98	0.98
			160.00
	11.99	100	947.70
	CN=		79.0
	CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
	1	11.99	0.50
ude Ponds)	2.5	3.91	0.41
reatment Vol	ume Required	(ac.ft.) =	0.50
eatment Volu	ıme Permitted	(ac.ft.) =	0.54
tional Treat	ment Required	(ac ft) =	-0.04
	nene negan ea	(uen en)	0.07
PRE-DEVI	ELOPMENT	POST D	EVELOPMENT
11	.40		11.40
			2.65
			8.74
			8.73
5	-0.5		00
	A A Preatment Volu Treatment Volu Treatment Volu Treatment Volu Treatment PRE-DEVI 11 3. 8.	A 0.01 A 1.60 11.99 CN= CRITERIA (IN) ude Ponds) 2.5 Treatment Volume Required reatment Volume Permitted	$\begin{array}{c} A \\ A \\ \hline 1.60 \\ \hline 1.60 \\ \hline 100 \\ \hline 11.99 \\ \hline \end{array}$

<u>NOTES:</u>

#### Post Development: Basin 11D

Stations 457+00 - 474+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	7.00	49	343.00
	C	0.20	79	15.80
Pavement (Permitted)	A	6.20	, s 98	607.60
New Pavement (Reg. Treatment)	A	0.00	98	0.00
Pond		2.50	100	250.00
Ponu	A		100	
		15.90		1216.40
		CN=		76.5
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention				
50% of 1" Over Total Project Area		1	15.90	0.66
50% of 2.5" Over Project Impervious Areas (E	xclude Ponds)	2.5	6.20	0.65
	Treatment Vol	ume Required	(ac.ft.) =	0.66
	Treatment Volu	me Permitted	(ac.ft.) =	0.81
A	dditional Treatm	nent Required	(ac.ft.) =	-0.15
WATER QUANTITY (50-yr/72-hr)	PRE-DEVE	LOPMENT	POST D	EVELOPMENT
Precipitation, in	11.	40		11.40
Potential Maximum Retention (S)	3.1			3.07
Runoff Depth (Q), in	8.3	-		8.40
Runoff Volume, acre-ft	11.			11.12
Volume Differential, acre-ft	11.	-0.1		11.12
volume Differential, acte-it		-0.1	2	

#### NOTES:

1. Adjusted basin for 8-lane widening and side road improvements.

#### Post Development: Basin 12

Stations 474+00 - 490+00

<u>*Project:*</u> Widen Western Beltway PD&E <u>*Project No.*</u>: 446164–1–22–01 Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u> Open Space-Fair Condition	A C	4.01 1.20	49 79	196.49 94.80
Woods (grove)-Fair	A	0.00	43	0.00
Pavement (Permitted) New Pavement (Reg. Treatment)	A A	6.70 0.34	98 98	656.60 33.32
Pond	A	1.80	100	180.00
		14.05		1161.21
		CN=		82.6
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention 1" Over Total Project Area 2.5" Over Project Impervious Areas (E	xclude Ponds)	1 2.5	14.05 7.04	1.17 1.47
	Treatment Vo	lume Required	(ac.ft.) =	1.47
	Treatment Vol	ume Permitted	(ac.ft.) =	1.80
	Additional Treat	ment Required	(ac.ft.) =	-0.33
WATER QUANTITY (50-yr/72-hr)	PRE-DEV	ELOPMENT	POST D	EVELOPMENT
Precipitation, in	11	.40		11.40
Potential Maximum Retention (S) Runoff Depth (Q), in		23 54		2.10 9.22
Runoff Volume, acre-ft		.62		10.79
Volume Differential, acre-ft		-1.8	13	

#### <u>NOTES:</u>

1. Reduction in basin size due to Walt Disney World Master site development. See permit 48-00714-S

Post Development: Basin 13 & 13A Stations 490+00 - 574+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
Basin 13A <u>Onsite</u> Open Space-Fair Condition	A B C	24.07 0.50 0.30	49 69 79	1179.43 34.50 23.70
Pavement (Permitted) New Pavement (Req. Treatment)	A A	25.80 2.63	98 98	2528.40 257.74
<u>Offsite</u> Tree Farm-Poor Condition	A	<u>9.50</u> 62.80	57	541.50 4565.27
		CN=		72.7
Basin 13 <u>Onsite</u>				
Open Space-Fair Condition Pond	A C A	1.50 1.30 6.20	49 79 100	73.50 102.70 620.00
		9.00	100	796.20
		CN=		88.5
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention 1" Over Total Project Area 2.5" Over Project Impervious Areas (Exclude	Ponds)	1 2.5	71.80 28.43	5.98 5.92
	Treatment V	olume Required	(ac.ft.) =	5.98
	Treatment Ve	olume Permitted	(ac.ft.) =	6.10
	Additional Trea	atment Required	(ac.ft.) =	-0.12
WATER QUANTITY (50-yr/72-hr)	PRE-DE	VELOPMENT	POST DI	EVELOPMENT
Precipitation, in Potential Maximum Retention (S) Runoff Depth (Q), in Runoff Volume, acre-ft Volume Differential, acre-ft		11.40 4.16 7.59 45.39 <b>1.7</b>		11.40 3.76 7.87 47.10

#### <u>NOTES:</u>

# Post Development: Basin 14A Stations 530+00 - 585+00

<u>Project</u>: Widen Western Beltway PD&E Project No.: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u> Open Space-Fair Condition Pavement (Permitted) New Pavement (Req. Treatment) Pond	A A A A	15.00 4.10 0.00 1.90 21.00 <b>CN=</b>	49 98 98 100	735.00 401.80 0.00 190.00 1326.80 <b>63.2</b>
<u>Compensatory Treatment</u> (Hartzog Road) Pavement	A	0.80	98	78.40
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention 50% of 1" Over Total Project Area 50% of 2.5" Over Project Impervious Ar	eas (Exclude Ponds)	1 2.5	21.00 4.90	0.88 0.51
	Treatment Vol	lume Requirea	(ac.ft.) =	0.88
	Treatment Volu	ume Permittea	(ac.ft.) =	1.03
	Additional Treati	ment Requirea	(ac.ft.) =	-0.16

<u>NOTES:</u>

1. No change

### Post Development: Basin 14B Stations 587+00 - 590+00

<u>Project</u>: Widen Western Beltway PD&E Project No.: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
<u>Onsite</u>				
Woods (Poor)	А	5.90	45	265.50
Pavement (Permitted)	A	1.10	98	107.80
New Pavement (Reg. Treatment)	A	0.00	98	0.00
Pond	Â	1.00	100	100.00
	,,,	8.00	100	473.30
		CN=		59.2
WATER QUALITY		CRITERIA	AREA	TREATMENT
WATER QUALITY		(IN)	(AC)	(AC.FT.)
Dry Retention 50% of 1" Over Total Project Area 50% of 2.5" Over Project Impervious Areas (E	xclude Ponds)	1 2.5	8.00 1.10	0.33 0.11
	Treatment Vo	lume Required	(ac.ft.) =	0.33
	Treatment Volu	ume Permitted	(ac.ft.) =	0.44
A	dditional Treati	ment Required	(ac.ft.) =	-0.11
WATER QUANTITY (50-yr/72-hr)	PRE-DEV	ELOPMENT	POST D	DEVELOPMENT
Precipitation, in	11	.40		11.40
Potential Maximum Retention (S)		90		6.90
Runoff Depth (Q), in	5.	93		5.93
Runoff Volume, acre-ft		95		3.95
Volume Differential, acre-ft	5,	0.00	0	

#### <u>NOTES:</u>

1. No change is anticipated in this basin.

## Post Development: Basin 14C Stations 574+00 - 595+00

<u>Project</u>: Widen Western Beltway PD&E Project No.: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	7.46	49	365.54
Pavement (Permitted)	A	7.70	98	754.60
New Pavement (Req. Treatment)	A	0.24	98	23.52
Pond	A	1.40	100	140.00
		16.80		1283.66
		CN=		76.4
WATER QUALITY		CRITERIA	AREA	TREATMENT
		(IN)	(AC)	(AC.FT.)
Dry Retention		1	10.00	0.70
50% of 1" Over Total Project Area		1	16.80	0.70
50% of 2.5" Over Project Impervious Areas (	Excluae Ponas)	2.5	7.94	0.83
	Treatment Vo	lume Required	(ac.ft.) =	0.83
	Treatment Volu	ume Permitted	(ac.ft.) =	0.80
	Additional Treat	ment Required	(ac.ft.) =	0.03
WATER QUANTITY (50-yr/72-hr)	PRE-DEV	ELOPMENT	POST D	EVELOPMENT
Precipitation, in	11	.40		11.40
Potential Maximum Retention (S)	= =	21		3.09
Runoff Depth (Q), in		29		8.38
Runoff Volume, acre-ft		.60		11.74
Volume Differential, acre-ft	11	0.1	4	

<u>NOTES:</u>

#### Post Development: Basin 15A

Stations 595+00 - 618+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

Basin Type: Closed Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
Basin 15A				
<u>Onsite</u>				
Open Space-Fair Condition	А	7.67	49	375.83
Pavement (Permitted)	А	5.20	98	509.60
New Pavement (Req. Treatment)	А	0.54	30	16.20
Pond	A	5.10	100	510.00
<u>Offsite</u>				
Grove-Good Condition	А	0.00	32	0.00
Meadow	А	0.00	30	0.00
		18.51	-	1411.63
		CN=		76.3

WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention 50% of 1" Over Total Project Area 50% of 2.5" Over Project Impervious Areas (Exc	clude Ponds)	1 2.5	18.51 5.74	0.77 0.60
	Treatment Volur	me Required	(ac.ft.) =	0.77
7	Freatment Volum	e Permitted	(ac.ft.) =	1.57
Add	ditional Treatme	nt Required	(ac.ft.) =	-0.80
WATER QUANTITY (100-yr/240-hr)	PRE-DEVEL	OPMENT	POST D	EVELOPMENT
Precipitation, in	15.8	)		15.80
Potential Maximum Retention (S) Runoff Depth (Q), in	8.53 8.78			3.11 12.59
Runoff Volume, acre-ft	27.3	7		19.43
Volume Differential, acre-ft		-7.9	4	

#### <u>NOTES:</u>

1. Basin 15F and Offsite have been removed due to the construction of Horizon High School, Permit No. 48–101923–P

2. It appears new roadway pavement was added which discharges to Pond 15A as part of the Horizon High School project, however there was no mention of impacts or calculations for Pond 15A presented in the permit.

#### Post Development: Basin 15B

Stations 595+00 - 618+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

Basin Type: Closed Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	5.70	49	279.30
Open Space-Fair Condition	С	1.30	79	102.70
Open Space-Fair Condition	D	0.40	84	33.60
Pavement (Permitted)	A	8.00	98	784.00
New Pavement (Req. Treatment)	A	0.00	98	0.00
Pond	A	3.00	100	300.00
		18.40		1499.60
		CN=		81.5
		CRITERIA	AREA	TREATMENT
WATER QUALITY		(IN)	(AC)	(AC.FT.)
Dry Retention 50% of 1" Over Total Project Area 50% of 2.5" Over Project Impervious Areas (Ex	(clude Ponds)	1 2.5	18.40 8.00	0.77 0.83
		2.5	0.00	0.05
	Treatment Vol	ume Required	(ac.ft.) =	0.83
	Treatment Volu	ıme Permitted	(ac.ft.) =	1.68
Ad	dditional Treatr	ment Required	(ac.ft.) =	-0.85
· · · · · · · · · · · · · · · · · · ·				
WATER QUANTITY (100-yr/240-hr)	PRE-DEVI	ELOPMENT	POST D	EVELOPMENT
Precipitation, in	15	.80		15.80
Potential Maximum Retention (S)	5.	63		2.27
Runoff Depth (Q), in	10	.60		13.37
Runoff Volume, acre-ft	27	.12		20.50
Volume Differential, acre-ft		-6.6	2	

#### NOTES:

1. Offsite has been removed due to the construction of Horizon High School, Permit No. 48–101923-P

2. It appears new roadway pavement was added which discharges to Pond 15B as part of the Horizon High School project, however there was no mention of impacts or calculations for Pond 15B presented in the permit.

## Post Development: Basin 15C Stations 595+00 - 618+00

<u>Project</u>: Widen Western Beltway PD&E Project No.: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Closed Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	1.16	49	56.84
Open Space-Fair Condition	С	0.70	79	55.30
Open Space-Fair Condition	D	0.40	84	33.60
Pavement (Permitted)	A	0.40	98	39.20
New Pavement (Req. Treatment)	A	0.34	98	33.32
Pond	A	0.50	100	50.00
		3.50		268.26
		CN=		76.6
WATER QUALITY		CRITERIA	AREA	TREATMENT
WATER QUALITY		(IN)	(AC)	(AC.FT.)
Dry Retention				
50% of 1" Over Total Project Area		1	3.50	0.15
50% of 2.5" Over Project Impervious Areas (E)	clude Ponds)	2.5	0.74	0.08
	Treatment Vol	ume Required	(ac.ft.) =	0.15
	Treatment Volu	ıme Permitted	(ac.ft.) =	0.32
				0.17
A	dditional Treatr	ment Requirea	(ac.rt.) =	-0.17
WATER QUANTITY (100-yr/240-hr)	PRE-DEVI	ELOPMENT	POST D	EVELOPMENT
Precipitation, in	15	.80		15.80
Potential Maximum Retention (S)	3.			3.05
Runoff Depth (Q), in		.91		12.65
Runoff Volume, acre-ft		48		3.69
Volume Differential, acre-ft	51	0.2	-	

<u>NOTES:</u>

## Post Development: Basin 15D Stations 595+00 - 618+00

<u>Project</u>: Widen Western Beltway PD&E Project No.: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Closed Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>		2.26	40	16464
Open Space-Fair Condition	A	3.36	49 70	164.64
Open Space-Fair Condition	C D	1.10 0.20	79 84	86.90 16.80
<i>Open Space-Fair Condition</i> <i>Pavement (Permitted)</i>	D A	1.70	84 98	166.60
New Pavement (Reg. Treatment)	A	0.04	98	3.92
Pond	A	0.20	100	20.00
<u>Offsite</u>				
Meadow	A	3.70	30	111.00
		10.30	1	569.86
		CN=		55.3
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Dry Retention		()	(****)	(2.2.2.2.3)
50% of 1" Over Total Project Area		1	10.30	0.43
50% of 2.5" Over Project Impervious Areas	(Exclude Ponds)	2.5	1.74	0.18
	Treatment Vol	ume Required	(ac.ft.) =	0.43
	Treatment Volu	me Permitted	(ac.ft.) =	0.18
				0.05
	Additional Treatn	nent Required	(ac.rt.) =	0.25
WATER QUANTITY (100-yr/240-hr)	PRE-DEVE	LOPMENT	POST D	EVELOPMENT
Precipitation, in	15.	80		15.80
Potential Maximum Retention (S)	8.1			8.07
Runoff Depth (Q), in	9.0			9.04
Runoff Volume, acre-ft	7.7			7.76
Volume Differential, acre-ft	, , ,	0.0	3	

<u>NOTES:</u>

#### Post Development: Basin 15E

Stations 595+00 - 618+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

Basin Type: Closed Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	6.80	49	333.20
Pavement (Permitted)	A	7.10	98	695.80
New Pavement (Reg. Treatment)	A	0.00	98	0.00
Pond	А	1.80	100	180.00
		15.70		1209.00
		CN=		77.0
WATER QUALITY		CRITERIA	AREA	TREATMENT
WATER QUALITY		(IN)	(AC)	(AC.FT.)
Dry Retention				
50% of 1" Over Total Project Area		1	15.70	0.65
50% of 2.5" Over Project Impervious Areas (Ex	(clude Ponds)	2.5	7.10	0.74
	Treatment Vol	lume Required	(ac.ft.) =	0.74
	Treatment Volu	ume Permitted	(ac.ft.) =	0.80
A	dditional Treatı	ment Required	(ac.ft.) =	-0.06
WATER QUANTITY (100-yr/240-hr)	PRE-DEV	ELOPMENT	POST D	EVELOPMENT
Precipitation, in	1.5	.80		15.80
Potential Maximum Retention (S)		90		2.99
Runoff Depth (Q), in		.92		12.71
Runoff Volume, acre-ft		.52		16.63
Volume Differential, acre-ft	1,	-0.9	6	

#### NOTES:

1. Basin Offsite removed due to WaterLeigh improvements, see Permit No. 48-02575-P

2. The permitted 7.10-acres of impervious is greater than the proposed pavement of 5.48-acres.

#### Post Development: Basin 1

*Stations 1622+18.86 - 602+00* <u>*Project:*</u> Widen Western Beltway PD&E <u>*Project No.*</u>: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u>				
Open Space-Fair Condition	A	8.88	39	346.32
Pavement (Permitted)	A	8.44	98	827.12
New Pavement (Req. Treatment)	A	0.00	98	0.00
Pond	A	1.72	39	67.08
		19.04		1240.52
		CN=		65.2
		CRITERIA	AREA	TREATMENT
WATER QUALITY		(IN)	(AC)	(AC.FT.)
50% of 1" Over Total Project Area		1	19.04	0.79
50% of 2.5" Over Project Impervious Areas (Ex	clude Ponds)	2.5	8.44	0.88
	Treatment Vo	lume Required	(ac.ft.) =	0.88
	Treatment Volu	ume Permitted	(ac.ft.) =	1.06
Ac	lditional Treati	ment Required	(ac.ft.) =	-0.18
WATER QUANTITY (50-yr/72-hr)	PRE-DEV	ELOPMENT	POST D	EVELOPMENT
Provinitation in	11	.40		11 40
Precipitation, in Potential Maximum Retention (S)	= =	.40 96		11.40 5.35
Runoff Depth (Q), in		90 45		6.81
Runoff Volume, acre-ft		45 .30		10.80
Volume Differential, acre-ft	11	-0.5		10.00

#### <u>NOTES:</u>

1. Permitted pavement is greater than or equal to proposed pavement. Therefore, no "New Pavement".

2. Adjusted basin boundary to remove offsite area which no longer discharges into FTE R/W.

#### Post Development: Basin 2

Stations 602+00 - 641+83.82

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	СN	PRODUCT
<u>Onsite</u> Open Space-Fair Condition Pavement (Permitted) New Pavement (Req. Treatment) Pond	A A A A	8.53 12.01 0.00 2.61 23.15	39 98 98 100	332.67 1176.98 0.00 261.00 1770.65
		CN=		76.5
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention 1" Over Total Project Area 2.5" Over Project Impervious Areas (Exclude P	onds)	1 2.5	23.15 12.01	1.93 2.50
	Treatment Vo	olume Required	(ac.ft.) =	2.50
	Treatment Vol	ume Permitted	(ac.ft.) =	2.50
A	dditional Treat	ment Required	(ac.ft.) =	0.00
WATER QUANTITY (50-yr/72-hr)	PRE-DEV	<i>ELOPMENT</i>	POST D	EVELOPMENT
Precipitation, in Potential Maximum Retention (S) Runoff Depth (Q), in Runoff Volume, acre-ft Volume Differential, acre-ft	3	1.40 .07 .39 5.19 <b>0.0</b> 0	0	11.40 3.07 8.39 16.19

#### <u>NOTES:</u>

1. Permitted pavement is greater than or equal to proposed pavement. Therefore, no "New Pavement".

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>Onsite</u> Woods - Grass Combination Fair	A	3.72	43	159.96
Pavement	A A	3.31	43 98	324.38
Pond	A	2.00	100	200.00
Offsite				
Woods – Grass Combination Fair	A	9.43	43	405.49
		18.46		1089.83
		CN=		59.0

WATER QUALITY	CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention			
1" Over Total Project Area	1	18.46	1.54
2.5" Over Project Impervious Areas (Exclude Ponds)	2.5	3.31	0.69
Treatment Vo	lume Required	(ac.ft.) =	1.54
Treatment Vol	ume Permitted	(ac.ft.) =	0.00
Additional Treat	ment Required	(ac.ft.) =	1.54

#### Post Development: Basin FGB - Alt 3

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01 Date: 7/12/2022

WATER QUANTITY (50-yr/72-hr)	PRE-DEVELOPMENT	POST DEVELOPMENT	
Precipitation, in	11.40	11.40	
Potential Maximum Retention (S)	13.26	6.94	
Runoff Depth (Q), in	3.48	5.91	
Runoff Volume, acre-ft	5.35	9.10	
Volume Differential, acre-ft	3.75		
POND SIZING			
Pond	Bottom / Control Elevation =	108.00 FT	
	Top of bank elevation =	112.00 FT	

	Area @ pond bottom / control elevation = Area @ Top of bank =	2.00 2.16	AC
Elevation ft		Area acres	Volume acre-ft
108.00	Control Elev.	2.00	0.00
109.00	Treat. El	2.04	2.02
112.00	Inside TOB	2.16	8.32
109.00	Treat. El	2.04	0.00
111.00	Attenuation El	2.12	4.16
112.00	Inside TOB	2.16	6.30

REEDY CREEK CALCULATIONS (50-yr/72-hr)		
Precipitation, in	12.91	

Precipitation, in	12.91	12.91
Area, ac		18.46
Area, sq-mi		0.03
Peak Allowable Runoff, cfs		0.37

#### <u>NOTES:</u>

1. Basin area changed due to new interchange

#### Post Development: SR 530 Basin A Stations 12+83 - 27+60

<u>*Project:*</u> Widen Western Beltway PD&E <u>*Project No.*</u>: 446164–1–22–01

Volume Differential, acre-ft

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT	
<u>SR 530/US 192</u> Open Space-Good Condition Pavement Pond	D A D D	8.34 11.57 1.37 0.93 22.20	79 98 100 79	658.57 1133.63 136.65 73.40 2002.24	
		CN=		90.2	
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)	
Wet Detention 1" Over Total Project Area 2.5" Over Project Impervious Areas (Exc	lude Ponds)	1 2.5	22.20 11.57	1.85 2.41	
	Treatment Vo	lume Required	(ac.ft.) =	2.41	
	Treatment Vol	ume Permitted	(ac.ft.) =	2.16	
A	Additional Treat	ment Required	(ac.ft.) =	0.25	
WATER QUANTITY (50-yr/72-hr)	PRE-DEV	ELOPMENT	POST DE	EVELOPMENT	
Precipitation, in Potential Maximum Retention (S) Runoff Depth (Q), in Runoff Volume, acre-ft	1. 11	.40 28 .98 .16	]	13.40 1.09 12.18 22.53	

0.37

#### Post Development: SR 530 Basin A Stations 12+83 - 27+60

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

POND SIZING	NC	NGVD-29		
Pond Bottom / Control Elevation = Top of bank elevation = Area @ pond bottom / control elevation = Area @ Top of bank =	103.00 105.00 1.37 1.62	FT AC		
Elevation ft	Area acres	Volume acre-ft		
103.00Control Elev.104.50Treat. El105.00Inside TOB	1.37 1.56 1.62	0.00 2.19 2.99		

#### <u>NOTES:</u>

1. Elevations left in NGVD-29 for clarity in demonstrating the existing permitted conditions

Post Development: SR 530 Basin C Stations 31+70 - 55+00

<u>Project</u>: Widen Western Beltway PD&E <u>Project No.</u>: 446164-1-22-01

Date: 7/12/2022

Basin Info:

Basin Type: Open Basin Discharges to Impaired Waterbody: No

LAND USE	SCS CLASS	AREA (AC)	CN	PRODUCT
<u>SR 530/US 192</u>				
Pavement	D	10.37	98	1016.35
Pond	D	1.85	98	180.99
Grassed Area – Fair	А	7.18	49	351.85
	D	1.11	84	93.40
Pavement	D	3.11	98	304.39
Off-site Impervious	D	1.09	98	106.55
Grassed Area – Fair	D	3.61	84	303.04
Pavement	D	5.53	98	541.95
Off-site Impervious	D	1.04	98	101.46
Grassed Area – Fair	А	3.04	49	148.93
		37.92	-	3148.92
		CN=		83.0
WATER QUALITY		CRITERIA (IN)	AREA (AC)	TREATMENT (AC.FT.)
Wet Detention		(11)	(AC)	(AC.FT.)
1" Over Total Project Area		1	37.92	3.16
2.5" Over Project Impervious Areas (Ex	clude Ponds)	2.5	21.13	4.40
	Treatment Vo	lume Required	d (ac.ft.) =	4.40
	Treatment Vol	ume Permitted	d (ac.ft.) =	4.18
	Additional Treat	ment Required	d (ac.ft.) =	0.22
WATER QUANTITY (50-yr/72-hr)	PRE-DEV	ELOPMENT	POST D	EVELOPMENT
Precipitation, in	13	2.40		13.40
Precipitation, in Potential Maximum Retention (S)		2.40 25		
Potential Maximum Retention (S)	2.	25		2.04
Precipitation, in Potential Maximum Retention (S) Runoff Depth (Q), in Runoff Volume, acre-ft	2. 11			

#### Post Development: SR 530 Basin C Stations 31+70 - 55+00

<u>*Project:*</u> Widen Western Beltway PD&E <u>*Project No.*</u>: 446164–1–22–01

Date: 7/12/2022

POND SIZING	NGV D-29		
Pond Bottom / Control Elevation = Top of bank elevation = Area @ pond bottom / control elevation = Area @ Top of bank =	100.00 105.00 1.85 2.47	FT AC	
Elevation ft	Area acres	Volume acre-ft	
100.00         Control Elev.           102.30         Treat. El           105.00         Inside TOB	1.85 2.13 2.47	0.00 4.58 10.79	

#### <u>NOTES:</u>

1. Elevations left in NGVD-29 for clarity in demonstrating the existing permitted conditions



NOAA Atlas 14, Volume 9, Version 2 Location name: Kissimmee, Florida, USA\* Latitude: 28.3481°, Longitude: -81.6148° Elevation: 106.75 ft\*\* \* source: ESRI Maps \*\* source: USGS



#### POINT PRECIPITATION FREQUENCY ESTIMATES

Sanja Perica, Deborah Martin, Sandra Pavlovic, Ishani Roy, Michael St. Laurent, Carl Trypaluk, Dale Unruh, Michael Yekta, Geoffery Bonnin

NOAA, National Weather Service, Silver Spring, Maryland

PF\_tabular | PF\_graphical | Maps\_&\_aerials

### PF tabular

Dunation	Average recurrence interval (years)										
Duration	1	2	5	10	25	50	100	200	500	1000	
5-min	<b>0.480</b> (0.392-0.581)	<b>0.546</b> (0.445-0.662)	<b>0.650</b> (0.527-0.789)	<b>0.731</b> (0.590-0.893)	<b>0.837</b> (0.649-1.05)	<b>0.913</b> (0.693-1.17)	<b>0.984</b> (0.722-1.30)	<b>1.05</b> (0.740-1.44)	<b>1.14</b> (0.767-1.61)	<b>1.19</b> (0.788-1.74	
10-min	<b>0.703</b> (0.573-0.851)	<b>0.800</b> (0.652-0.969)	<b>0.951</b> (0.772-1.16)	<b>1.07</b> (0.864-1.31)	<b>1.23</b> (0.950-1.54)	<b>1.34</b> (1.01-1.71)	<b>1.44</b> (1.06-1.90)	<b>1.54</b> (1.08-2.11)	<b>1.66</b> (1.12-2.35)	<b>1.75</b> (1.16-2.54)	
15-min	<b>0.857</b> (0.699-1.04)	<b>0.975</b> (0.795-1.18)	<b>1.16</b> (0.942-1.41)	<b>1.31</b> (1.05-1.60)	<b>1.49</b> (1.16-1.88)	<b>1.63</b> (1.24-2.09)	<b>1.76</b> (1.29-2.32)	<b>1.88</b> (1.32-2.57)	<b>2.03</b> (1.37-2.87)	<b>2.13</b> (1.41-3.10)	
30-min	<b>1.38</b> (1.13-1.67)	<b>1.57</b> (1.27-1.90)	<b>1.86</b> (1.51-2.26)	<b>2.08</b> (1.68-2.55)	<b>2.38</b> (1.84-2.99)	<b>2.59</b> (1.97-3.32)	<b>2.79</b> (2.05-3.69)	<b>2.98</b> (2.10-4.08)	<b>3.21</b> (2.17-4.55)	<b>3.37</b> (2.23-4.90)	
60-min	<b>1.82</b> (1.48-2.20)	<b>2.07</b> (1.69-2.51)	<b>2.48</b> (2.01-3.01)	<b>2.79</b> (2.26-3.42)	<b>3.21</b> (2.49-4.03)	<b>3.51</b> (2.66-4.49)	<b>3.79</b> (2.78-5.01)	<b>4.06</b> (2.85-5.55)	<b>4.39</b> (2.96-6.21)	<b>4.61</b> (3.05-6.71)	
2-hr	<b>2.25</b> (1.85-2.71)	<b>2.58</b> (2.12-3.11)	<b>3.10</b> (2.54-3.74)	<b>3.51</b> (2.85-4.26)	<b>4.04</b> (3.15-5.04)	<b>4.42</b> (3.38-5.63)	<b>4.79</b> (3.53-6.28)	<b>5.13</b> (3.63-6.97)	<b>5.56</b> (3.78-7.82)	<b>5.86</b> (3.90-8.46)	
3-hr	<b>2.45</b> (2.02-2.93)	<b>2.81</b> (2.32-3.37)	<b>3.40</b> (2.79-4.09)	<b>3.87</b> (3.16-4.68)	<b>4.50</b> (3.53-5.61)	<b>4.96</b> (3.82-6.31)	<b>5.41</b> (4.02-7.10)	<b>5.86</b> (4.17-7.95)	<b>6.42</b> (4.39-9.02)	<b>6.83</b> (4.56-9.84)	
6-hr	<b>2.81</b> (2.34-3.34)	<b>3.22</b> (2.68-3.83)	<b>3.91</b> (3.24-4.67)	<b>4.50</b> (3.71-5.40)	<b>5.34</b> (4.26-6.70)	<b>6.02</b> (4.69-7.68)	<b>6.72</b> (5.05-8.83)	<b>7.45</b> (5.36-10.1)	<b>8.45</b> (5.84-11.9)	<b>9.23</b> (6.20-13.2)	
12-hr	<b>3.26</b> (2.74-3.85)	<b>3.68</b> (3.09-4.35)	<b>4.46</b> (3.73-5.29)	<b>5.20</b> (4.32-6.20)	<b>6.34</b> (5.15-8.02)	<b>7.33</b> (5.79-9.39)	<b>8.41</b> (6.40-11.1)	<b>9.60</b> (6.99-13.1)	<b>11.3</b> (7.91-15.9)	<b>12.7</b> (8.60-18.1)	
24-hr	<b>3.75</b> (3.18-4.40)	<b>4.22</b> (3.57-4.95)	<b>5.14</b> (4.33-6.06)	<b>6.06</b> (5.08-7.18)	<b>7.57</b> (6.24-9.60)	<b>8.91</b> (7.12-11.4)	<b>10.4</b> (8.01-13.7)	<b>12.1</b> (8.90-16.5)	<b>14.6</b> (10.3-20.5)	<b>16.7</b> (11.3-23.5)	
2-day	<b>4.29</b> (3.66-5.00)	<b>4.86</b> (4.14-5.67)	<b>5.99</b> (5.09-7.01)	<b>7.12</b> (6.01-8.38)	<b>8.96</b> (7.45-11.3)	<b>10.6</b> (8.54-13.5)	<b>12.4</b> (9.65-16.3)	<b>14.5</b> (10.8-19.6)	<b>17.6</b> (12.5-24.5)	<b>20.1</b> (13.8-28.2)	
3-day	<b>4.72</b> (4.04-5.47)	<b>5.32</b> (4.56-6.18)	<b>6.53</b> (5.57-7.61)	<b>7.73</b> (6.56-9.06)	<b>9.68</b> (8.08-12.1)	<mark>11.4</mark> (9.23-14.5)	<b>13.4</b> (10.4-17.4)	<b>15.5</b> (11.6-20.9)	<b>18.7</b> (13.4-26.0)	<b>21.4</b> (14.7-29.9)	
4-day	<b>5.10</b> (4.39-5.91)	<b>5.72</b> (4.92-6.63)	<b>6.95</b> (5.95-8.08)	<b>8.17</b> (6.95-9.55)	<b>10.1</b> (8.49-12.7)	<b>11.9</b> (9.66-15.1)	<b>13.9</b> (10.8-18.1)	<b>16.1</b> (12.0-21.6)	<b>19.3</b> (13.8-26.8)	<b>22.0</b> (15.2-30.7	

https://hdsc.nws.noaa.gov/hdsc/pfds/pfds\_printpage.html?lat=28.3481&lon=-81.6148&data=depth&units=english&series=pds

#### Precipitation Frequency Data Server


7-day	<b>6.14</b> (5.32-7.07)	<b>6.76</b> (5.85-7.79)	<b>7.98</b> (6.88-9.23)	<b>9.20</b> (7.88-10.7)	<b>11.2</b> (9.40-13.8)	<b>12.9</b> (10.5-16.2)	<b>14.9</b> (11.7-19.2)	<b>17.1</b> (12.8-22.8)	<b>20.3</b> (14.6-27.9)	<b>23.0</b> (15.9-31.8)
10-day	7.06	7.71	8.97	10.2	12.2	13.9	15.8	17.9	21.0	23.6
20-day	(6.15-8.10) <b>9.71</b>	(6.70-8.85) <b>10.6</b>	(7.77-10.3) <b>12.2</b>	(8.78-11.8) <b>13.6</b>	(10.2-14.9) <b>15.6</b>	(11.4-17.3) <b>17.4</b>	(12.4-20.3) <b>19.2</b>	(13.5-23.8) <b>21.1</b>	(15.2-28.8) <b>23.8</b>	(16.4-32.6) <b>26.0</b>
	(8.52-11.1) <b>12.1</b>	(9.30-12.1) <b>13.2</b>	(10.6-13.9) <b>15.2</b>	(11.8-15.6) <b>16.8</b>	(13.2-18.8) <b>19.1</b>	(14.2-21.2) <b>20.9</b>	(15.1-24.2) <b>22.6</b>	(15.9-27.5) <b>24.5</b>	(17.2-32.2) <b>27.0</b>	(18.2-35.7) <b>28.9</b>
30-day	(10.6-13.7)	(11.7-15.0)	(13.3-17.3)	(14.7-19.2)	(16.1-22.7)	(17.1-25.2)	(17.9-28.3)	(18.5-31.6)	(19.5-36.1)	(20.3-39.4)
45-day	<b>15.2</b> (13.5-17.2)	<b>16.8</b> (14.9-19.0)	<b>19.2</b> (17.0-21.8)	<b>21.2</b> (18.6-24.2)	<b>23.8</b> (20.1-28.0)	<b>25.8</b> (21.2-30.9)	<b>27.6</b> (21.9-34.2)	<b>29.5</b> (22.3-37.7)	<b>31.7</b> (23.0-42.1)	<b>33.4</b> (23.6-45.4)
60-day	<b>18.0</b> (16.1-20.3)	<b>20.0</b> (17.7-22.5)	<b>22.9</b> (20.3-25.9)	<b>25.2</b> (22.2-28.7)	<b>28.2</b> (23.8-32.9)	<b>30.3</b> (25.0-36.1)	<b>32.3</b> (25.6-39.7)	<b>34.1</b> (25.9-43.5)	<b>36.4</b> (26.4-48.0)	<b>37.9</b> (26.8-51.4)


<sup>1</sup> Precipitation frequency (PF) estimates in this table are based on frequency analysis of partial duration series (PDS).

Numbers in parenthesis are PF estimates at lower and upper bounds of the 90% confidence interval. The probability that precipitation frequency estimates (for a given duration and average recurrence interval) will be greater than the upper bound (or less than the lower bound) is 5%. Estimates at upper bounds are not checked against probable maximum precipitation (PMP) estimates and may be higher than currently valid PMP values.

Back to Top


Please refer to NOAA Atlas 14 document for more information.






https://hdsc.nws.noaa.gov/hdsc/pfds/pfds/printpage.html?lat=28.3481&lon=-81.6148&data=depth&units=english&series=pds

Precipitation Frequency Data Server





Maps & aerials

Small scale terrain

Precipitation Frequency Data Server





Large scale map

Precipitation Frequency Data Server





Back to Top

Precipitation Frequency Data Server

US Department of Commerce National Oceanic and Atmospheric Administration National Weather Service National Water Center 1325 East West Highway Silver Spring, MD 20910 Questions?: <u>HDSC.Questions@noaa.gov</u>

**Disclaimer** 

## APPENDIX D – FLOODPLAIN ENCROACHMENT CALCULATIONS

Pond Siting Report Widening Western Beltway PD&E Study from Interstate 4 to Seidel Road Florida's Turnpike Enterprise Financial Project ID 446164-1-22-01

This may is to use in administrating the Netronal Flood Insurance Program. It does not accessely sensity as even subject to Rooting, particularly term local drainage servers in thread loc. The transmisting may reproduce y should be normalised for provide systemical to additional final flacand industriation.

To obtain more detailed information in press where Base Flood Elevations (IFEs) and/or fleeplaceps have been intermined, sens are encouraged to alread the Flood Publies and Dedauty Data and/or Gammary of Eliberter Elevations testins contained writer the Flood Instances Study (FS) report that accompares the VIVE Unions should be assume that STRES shows in the Florid property encoursed unlike elevations. These IFES are introduct for boot instances reling purposes only and details as the outer take of STRE instance of the growthe instances. Assuming flood write the present of the FIS is post about the data of a comparison with the FIRM is proposed of communication acids to begin memoryamed.

Costal Base Flood Exvertises (BFEs) shown on this map apply only introlvent of 0.5° Holfs American Vertical Datam of THBE (MHCD ES), Users of this FIFEM visual be even the costal fixed elevations are also provided in the Summary of Stillader Exvertises table in the Flood Inscence Study sport for the pendiculor. Develops when in this termary of Stilladers Elevations able should be also the construction and/or floodplate transported purposes when they are tupor than the elevations when in this FIFM.

Boundaries of the Reodeways were computed at cross sections and interpolated between room sections. The beakaugs user leared in highwaits considerations with regard to registrement of the National Picol Insurance Trougen, Picolanay within and other performed functionaly data are provided in the Pitol Insurance Easily report of the paradiction.

Centric amain not in Special Fixed Hasself Anain may be protected by flood coefficies structures. Patter to Section 2.4 "Fixed Protection Measures" of the Fixed insurance Study report for information on fixed control elevatives for this production.

The projection code is the properties of this may use Transverse the product Like Pase Parcel East FIPS (2011) The herizontal datum was NA200 HARD, 0251900 the product Doc of FIRMs for a density problem measurement and an east of differences in the product production measurement and and east used on differences in the product production to containers. These differences do not admit the assurance of HRM.

Final elevations on Bis map are referenced to the North-American Vertical Datum of 1988. These flexible elevations must be compared to structure and ground elevations information (b) to same verbical datum. For verbination regressing concernos between the faintwird Genders: Vertrait Datum of 1909 and the North American Internation of 1999, with the Notation Genders: Verbical Genders: Genders: Survey and the Notation of Million and the North American International Genders: American Concerns: The North American Survey at the Notation Genders: Survey at the Notation Genders: Survey at the Notation of Survey and Survey Survey and Survey Survey and Survey and Survey Survey and Survey Survey and Survey Survey and Survey Su

NGS Information Sension NGAA, NMG512 National Geodetic Survey (SMC-3, VARIE 1011 Gast VARIE) Starr Sprog, Marytend 30010-3090 (381) 713-2042

To obtain summit develop, description, and/or location information for banch marks about on the map, please cardad the Information Services Strenct of the National Gendelic Servey at (MIS) 113-3342 or visit its website at <u>http://www.nos.neas.com</u>

Base map internation shown on two FIRM was possibled in dipted format by the Deceals County Parking Office. Otherphotography was obtacted in late 2007 early 2008.


The map reflects more obtained and up-to-tate stream channel configurations free frees about on the process FIRM for this possiblem. The fixed-planet and localizes the unit iteratives of them the previous FIRM me have been adouted to confirm to these new stream observed configurations. As a result, the Fixed Profiles and Fixed-have the fixed interaction of the fixed process fixed and the fixed adoutance hybrid colds) may reflect assess sharves datamase that other how when is share to the map.

Cosporate timits shown on this trap are based on the best data available at the time of publication. Boostee changes due to amoreations or de-amoreations may have ownered after this may was published, may users should contact appropriate someworks distants to worky assert septone local locations.

Press whe is the separately privitel Map Index to an surviver map of the county stroking the lipport of map panels, contravely map repeativy addresses, and a Lasting of Communities table contravening National Photo Imsurance Program datas Stre sect community as well as a listing of the panels on which each community is located.

For information and guestions about this map, sealable protects associated with the TBM including heating weapons of this TBM, bear to select product and the Nickeen Fluids Including Teleform (1997) (199

The "people base base" depicted on this map represent the hydroxic modeling baseless that match the flood potition in the IVG repart. As a result of improved superprisite data. We "york have floor", some cases, may devide significantly how the channel centerion or appear subside the STHA.



sources of anos size. The commandy may repperiony stands to rungutud Ar possible cycluted on address found hazard internation

to oblass more detailed bytematus in preas where these Fleed Elevations (1974) at To oblace more detailed information in press where these Flood Elevetions (UPEs) works backgraps frame deep distinguish and an enclosurpate out (Consultation Linear Prefilies and Eleveryary Data, subject Elevening via Stationary (Consultation Linear excitation onlights) that have been been been been been been been excitation onlights around that Eleveryary is a first in pressure analysis to the filled to be should be available and the eleven of the first interpretation and elevelations and the station of the source of staries present maximum accuration by the station of the source of staries (Linear Backgraphing and the source of the source of staries) for source of staries (Linear Backgraphing and the source of staries) and the source of staries (Linear Backgraphing and the source of staries) and the source of staries (Linear Backgraphing and the source of the source of staries) for source and the value on component way the Flood elevention of the Floor distribution of the source of the source of the elevention of the source of the source of the source of the elevention of the elevention of the source of source s

Coster Base Flood Elevations (EFEs) shown on this map apply only benearly on of their Anexican Wellian Dations of 1985 (MACD B8) users at this TRMM should be avaine that classift show anexican are also provided the tis bundled. The Revailable table in the Flood insurance Revail cart for this provided on Determined the shown of the show the show the shown of the Southard on Southar on Bodytam management purposes, when they we higher that the becations and/or Revailable (ReV

Boundaries of the floodways were computed as cross sections and interpolated between cross sections. This floodways were based on hydritude considerations use regard to requirements of sto National Flood Interance Program. A codway with the section of the se ter Des jaumcheite

Centuir amus not in Special Toxic Vagnet Analo may be primerine by Bood composi situations. Refler to Section 2.4 "Fond Protection Massiver" of the Flood massiver Dividy report to information on Read century directors for two productors

The publication used to the preparation of driving wait functively transmission Pane target anti-FIFS 0001. The bogization adams was NAIS31-MARK (MSK1985 phoniotic attentions on advance patronid, projection or State Panet protocol phoniotic attentions and advances providencian crists in Panet protocol ferences on advances providencial providencial may reveat in signif postorior differences on advances produces productions for the part postorior differences on advances produces produces and providences. Target differences of on solution of FIRMS

Food skywatens on tha map sin televisited at the North-American Vertical Bazan of 1958. Tresse fload skywatens was be compared to skycture and griccal skywatens interences to me same vertical datum. For unitoration regarding convertica technoli the National Bookisto Vertica Saturn of 1929 and the Math American Vertical Bazan in 1978. The technology of the state of 1979 and the Math American National Bookisto Vertical Bazan for Units and 1979 and the Math American technoli the National Bookisto Vertical Bazan of 1979 and the Math American National Bookisto Vertical Bazan for the National Catelotic Survey vertical Bazan Scholars and the Survey Scholars and the National Catelotic Survey of the following additional

NGS Information Services NGAA, ININGST2 Pattonal Geologic Survey SSMC-3, BYVO 1315 Cathology Processing State Cathology State State State

To obtain summit develop, description, and/or location information for banch marks alsone on this, map, plaque contact the internation (Service Brauch at the Dational Gendelic Survey at (MIT) 115-3347 or with its website at <u>Http://www.vcp.notac.com</u>

Base map internetion alread on this FIRM was provided in right formal by the Occesits County Persons Office. Orthogholography may objected in use 2007 early

This may reflects more destined and up to date stream channel configurations that hisse whom on the previous HIMA to this sundation. The booldstass and Scolaray may are manaphened that will previous 100% any takes uncertain stream address contents to large new research that will be any take to the stream address of showing the stream channel computations. As a result, the field finite and showing that address that the show that the stream address takes the stream channel and the show that the stream address and the stream stream channel address that other how what is stream day the new and the stream stream address that other how what is stream day the new stream address that new stream address that new stream address that the stream channel distances that other how what is stream day the new stream address that new st

Copporte lense deserver or this may are cause on the sent table contains at the form of publication. Boostee changes due to annovations or de-annovations may have sourcest after this may was published, may users should contact appropriate torresturity officials to worky contact approach and locations.

Please only to the accurately privited Map below for an survivour map of the country showing the literat at map parents, community map repeating addresses, and a Lating of Communities later extraining National Plano Imacome Planguan data. Sho each community as well as a titting of the parels an which each community is locable.

store about this map, available pro versions of this FURM, how to only FTM including holds wearable of the FTML hole to alian products or the National Fixed Incursion Program is general, present out the FERM Mapping Information without and the FTM Electrody (14/97-205.2027) or valit the FERM Mapping including at the Information processing of the Information within at the Information processing of the Information at the Information metal Letters of Map Chargo of Reva products are to inferent or informed letters from the Information Control of the Information Street Processing within at the Information of the Information Street Processing within at the Information Control of the Information Advanced Berry Hole the weakers. Users may information the can be not be a solation of develop from the Advanced. ange

The "yeardine basis basis" depicted on this map represent the hydrautic modeling baselines that match the flood pathes in the I/D repart. As a mask of improved transpropring date, the "yorkit base low", in some cases, may devide significantly from the channel controlline or appear subside the STHA.

TAXING -

AL 07:37

COCOMUT PACE WAY

455000 77




B 85%

JOINS FRANEL DOA

455000 FT

Osceola County Unincorporated Areas 120189

470000 FT



This near is for user in agreemstering the narrowal Poort Insurance Program. It dees not reasonantly identify all areas subject to fitscaling, perticulate trave taxet deenage sources of invest size. The agreementative may repositely while be considered the possible spotland or additional flood traged retermation.

The statum resolution of information is server, actives Base Fland Bervellaues (FFE), and/or floorlwages have been determined, users are encouraged to consult the Floor Partielles and Floorlwage Data and/or Examinary of Stitthater Berechtes tables contened within the Floorl Insuitance Stoky (FS), report thet eccompanies the FRM. Dates should be assume that (FFE) shows in the FTM Respective Humbel Antiale flad devotions. These BFEs are inheritiant frequenties that flad devotions. These BFEs are inheritiant flate flat flat particular should write devotions. These BFEs are inheritiant flate flat particular should write devotions. These BFEs are inheritiant flate flat particular should write flate and the FTM the FTM spectral should be obtained in composition flate particular should be the FTM spectral should be obtained in composition with the FTMH for purchases of conduction analise flate/space interception.

Contai lass Field Electrices shown on this map upply only landscel of 50 horn American Vortical Datum of 1988 (PV-0 58), Users of this FIRM shows beaware that costate final deviations are also provided in the Buenders of Distance to the Electrices table in the Find Insurance Bioldy report for the jurisdictor. Diversions and/or flootplate management purposes when they are higher than the elevations and/or flootplate management purposes when they are higher than the elevations and/or flootplate. Find

Biochartes of the **fixedways** serve compared at orses sections and interpolated potenter drops sections. The fixedways serve based on hatmakic considerations and regard to requirements at the flatched Fixed textures fixedway within and other proteiner floodway data are provided in the Fixed insurance Biolyngoot for the guidantion.

Centen awas not in Epicod Plancingand Awas may be prototed to **Read control structures**. Refer to Sector 2.4 "Fixed Postector Neutrons" of the Fixed insurance Study report for information as fixed control structures for this jurisdiction

The projection used in the projection of this map was Table Place Rends Earl RPD Zone 0001. The borizontal dates was NAOGO. (IRSVID) attented Differences a dates, spanned applicator or (URL zones used a the production to RRNA for adjuant juradictions may result in slight positional offerences in map traduces across production boundaries. These offerences is not affect the acoustry of the FIRM.

Final elevations as this map are informated to the North American Vertical Datam of 1988. These final elevations must be compared to structure and provide development information of the same were traded allows. For information registring convention between the Tradeout Genotes Vertical Concers of 1520 and the York American Vertical Concerts of 1988, vol. to Holman Genotes Genory anotale at this them to hold with the National Genotes Survey and the fullhaving address?

Spatia Reference System Design National Geodetic Burvey, MCM Silver Spring Micro Center Tarts Sand West Highway Bilver Spring, Maryand 20110 (2011) 713-5181

To obtain surved allowing, description, and/or localism information for leasts marks shown on this map, global obtained the information Services Straight of the historial closeling Survey of (201) PG-3242 or viol in section of <u>Historic run, close groc</u>.

Rese map information shown on this FIRIT was provided in digital format by Orange County, Frands

This map software move detailed and sp-to-dete speem channel configurations lives free obsers as the previous FIRM for this standardism. The floatightens and floating the set transitional firms the previous FIRM new new bare adducts to local probability of the set of the set of the set of the set of the the set of the floating set of the set is stream of the map.

Counced and an act was permanent may every should contact appropriate counced a discuss in wally extent supported wind technon.


Please telef to the separately protect **Map index** for an overvew map of the county including the labout of imap panels, estimating map regionating including including of communicies table contraining National Pleas Incode Insurance Program State, for each occurrency as well as a linking of the parels on which each community a located.

Central we FEMA http: Service Center of 1-630-301-615 for internation on another prototice and the service of the Service product may include technology restored bettern of May Donardo - Flore Andreado Starger protote of planetament of the may Tran FDAA http://www.include.com/andreading/ Flore and -600-364-000 and its micro-andreading betternational by Flore and -600-364-000 and its micro-andreading betternation and the national service and the service and the service betternation of the service of the service and the service betternation of the service and the service and the service betternation of the service of the service and the service betternation of the service of the service of the service betternation of the service of the service of the service betternation of the service of the service of the service of the service betternation of the service of the

If you have questions about this map or questions accounting the follows filters insurance Program in general, piezze cat 1477-FEMA MAP (1-977/305-2827) to and the FRMA watche at <u>Havelowindows</u> graduatershifting.

NOVD29 to NAVD41	Venucal Datoin	Conversion	Saule Neeth

	Min march	faarimum -	AVMAGE	hia.trum
Watershod Maino	Conversion	Conversion	Conversion	Officet
Dy Ecologia color Real	-1,05	-1.15	439	049
Alvery Creek	-\$\$)	-141	-2.20	605
Crowse Davis	0.57	-0.25	-9.59	0/2
Have Dance	-250	-1.60	-026	\$\$ <b>7</b>
Lave Apopla	-0:57	-012	-014	0.09
L ang angin	441	117	-527	625
L Con Equilizatura da Rovar	-697	-197	27	\$9 <b>9</b>
Litte Webber (Low	-(1,1/1	-n 02	4919	\$12\$
Hundy Check	-6 64	-984	-624	\$4Q
-bhaqie Gravir	-6 64	ei in	4560	644
.St. voors Rvar	(1.03	+3.3ů	0.16	0.34
www.www	-9.63	-18	-034	625



1972-1977 - 1984 - 19

145 \*\*\*E

· • • • • • •

	LEGEND
500 FT 17 100 17 100	SPECIAL PLOOD INCOME AREAS (STRING) SARAELT TO INSIMULTION IN THE TRY ANDRIAL CONINCE PLOOD EVENT. The 1% annual models from (35) yes fauld, and forms in the fault fault, is the fault fa
	The serval there book. 2008 A See Trans Field (Breathers Ademiced). 2008 AF Sea Field (Breathers Ademiced). 2008 AF Seat Sead Sector 2 Sectors and Sectors
1.	EDME A3 Find depth of 1 to 3 held causity deet the or dependences, average depth adversard. For areas of discut for finding, vehicles also depresent. EDME A4 Area of special flood laced during protocol from the 3% average depth of another protocol from the 3% average during the special flood carbodic agents. The special flood carbodic agents are special for a local carbodic agents are special for a local carbodic agents. The special during the special carbodic agents are special for the special carbodic agents. The special during the special carbodic agents are special for the special carbodic agents.
N	2008 ### Areas to be protocoled from the served device fixed event to a Neders fixed orthogen motion and/or controllation fixed fixed development.
	IDER VI     Index Nod Inter with velocit heard (new active): Sale Rood (Interload active); Sale Rood (Interload)     INDOCENNY AREAS IN ZONE AL
<b>*</b>	The finalesce is the check of a assumption are adjusted floatigen units that must be tage from of incrementance in that the I's around check float one to cannot units adjusted and another host tages. CTHER HLCCO REEKS 2016 3 Area of J2% around Parce float, areas of 1% around plants float with semiger output of the start. That or write adjusted is the 1 square write, and
	ensurements and its towns have 3 to any of shares find.     OTHER ANEINE     EVEL X     Aves determined in the state of the state many dama.
in the second	2008 0     Anne is which flocing in an understroad, but possible.     COMETRAL BARREER RESOURCES SYSTEM-(CERES) AREAS     COMETRAL BARREER RESOURCES SYSTEM-(CERES) AREAS     OTHERWISE PROTECTED AREAS (OPAn)
10	CMB eres and DNs answersky loaded withs or adjacent to typest final fixed Area. (N amout during football intendity) EVA amout during football intendity Pootball boundary Date 3 footbally
2	OBS and ON foundary     OBS and ON foundary     Index y Datasy Social Flood Faces Areas of different free     Prod Destines, find depts or Rod velocitie.     Social
	Tablewood is the function formation (see of 1988) (MMC BB)     Oracle exception form     Oracle exception form     Transaction     Transaction
	Dates of cate gene any weatern introporter           11/5/11/11           Lobo event Waverge Yammarke Mecador gene bits, gave 17           S000000 FT           S000000 FT           Cate Survey Yammarke Mecador gene bits, gave 17           Cate Survey Yammarke Mecador gene bits, gave 17           S0000000 FT           Cate Survey (TSESTANLY VEX.) Transmer Mecador gene bits           Dates 10           Cate Survey (TSESTANLY VEX.) Transmer Mecador gene bits           Dates 10           Dates 11           Dates 11           Dates 12           Dates 13           Dates 14           Dates 15           Dates 15
	Filer 15 Mark Reportation 20 M May 1000 (FFECTAL Dalls On COMPTION) TOODE PARTIENT MATHEMAN EXCELEMENTER AND CONSTRUCTION OF THE SAME AND CONSTRUCTION OF THE SAME AND AND AND AND AND AND AND SEPTEMBER 20 7000 TO LIGHT CONTRACT AND AND AND AND AND AND AND SEPTEMBER 20 7000 TO LIGHT CONTRACT AND AND AND AND AND AND AND AND AND AND AND AND AND AND AND AND AND AND
	Proportiane dang dang Selection Alabar program Janan, Jahrange Seperut Alabar proton Janas Select Select Habar statuse devela to kopan menjanggar ta sud analasis ana kondunente te niceptarat protonogra dang selecti dang ta kopa Promon, ja cakest updarat lagogatana mitanakani und la makepulate produktig selecti selecti da Alap Ananabasa
	For constructing man reasons halong provide construction engines, refer to the Gammana, Man Holong table in table on the Refer Source Man reaction (in a parkition). To common a flood sourcement is available to that processing, initiated tools examine expert or sub-the reasons thand have some imagement at 1900 SSE 1932.
	LAAP SCALE 1" = 1000'
34 N	NEIP PAREL 0580F
	FIRM FLOOD INSURANCE RATE MAP ORANGE COUNTY, FLORIDA
	位と FLOADA 回こ AND INCORPORATED AREAS が近 PANEL 580 OF 750
1	IDEE MAP AUTEX FOR FURN PANE; LAVOUT) DUMANS DUMANS COMMUNIT SUBJECT MARKET COMMUNIT SUBJECT MARKET SUBJECT MARKET SUB
	Rédue to clam Thr May Mandae stone. Softwartwick: La card date plant and softwart for Constanting Remains which La card Acut to and a card and acut to a card and acut to an acut to and a card acut to a card acut to acut to acut acut to a card acut to acut to acut to acut acut to a card acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut to acut to acut acut to acut to acut to acut to acut to acut to acut to acut acut to acut to ac
1011945	MAP NUMBER 12095C0580F MAP REVISED SEPTEMBER 25, 2009
	Federal Entergency Management Agency

1

43-12

42965

This nep-5 for use in administency the factorial Food insurance Program. It datas for insufacely shelling at answs subject to financing, particularly from facel manage sources of inner size. The operationally may repositive which doe unstanded for possible updated or accidence food happed information.

politice updates of incommentation is arress where **Base Flaid Develops** (DFTs) action **foodways** have been determined, uses are ancouraged to consult the Flood Publics and Floodway Data and/or Summary of Stithater Elevations tables contened within the Flood Insymptote Stady (FS) cooper that econographs the FIGU Cases should be asses that BFTs shows on the FIGM represent fractular tables on the BFTs and instanced for flood investment into quoties fract the summary of the FIGS Insymptote Stady (FS) could be assess that and the tables of the State State of the FIGM represent fractular should be developed. These BFTs are instanced for flood investment into quoties not and the ITMM for guogoess of conduction and/or flood sized and management.

Contail Ease Fixed Elevations shown on this map apply only landscal of 0.0 horn American Vertical Datam of 1988 (MVO 86), Users of this FISM should be arear that created fixed elevations an axia provided in the Elevations Elevations table in the Fixed Insurance Biody report for the junctices. Elevations shown in the Summary of Stitester Elevations table should be used for construction and/or flootphan management purposes when they are lighter than the elevations shown in the FISE.

Bandares of the **Bookrays** new computed at crise sectors and interplated bettern ones sectors. The Bookrays were based on hybraic considentions with regard to negative and the sector of the Bookray and the and other perferent floothey data are provide in the Flood Imurance Block root. To the predictor.

Certain awas not in Special Planci Hazard Iveas may be protected to **Road Lantest** structures. Refer to Genter 2.4 "Ecod Protector Measures" of the Food Insurance Blady report for internation on food certifiel structures for this pendotton.

The projection used in the projection of this map uses that Plane Trans the Difference of the production of the map uses that Plane Trans East Differences in dubut, schemid, projection or UTM points used in the production of Differences in adapted approximation and product and defenses in a stage product of differences in map features and production to undertains. These differences is on affect the accuracy of the Plane.

Food elevations in this map are referenced to the North American Vertical Datum of 1996. These final elevations must be compared to situation and ground invasions inferenced to the same vertical datus. To information registring conversion between the Fational Dacoditic Vertical Datum of 2520 and the North American Merical Datum of 1996. Vert The National Geodetic Survey works in the inference of the Vert The National Geodetic Survey and the fationers and/them the information of inference of the National Cheodetic Survey and the fationers and/them the second control of the National Cheodetic Survey and the fationers and/them the second control of the National Cheodetic Survey and the fationers and/them the second control of the National Cheodetic Survey and the fationers and/them the second control of the National National National Cheodetic Survey and the fationers and/them the second control of the National Cheodetic Survey and the fationers and/them the second control of the National Nationa

Spatial Reference System Design National Geodetic Scrwy, ACM Silver Spring Marts Center 1315 Said West Highway Gilver Spring Margand 20040 (2010)713-0104

To obtain numeri alevation, description, and/or inclution information for leanth marks shown on this map, pieces contact the information Services Search of the Redonal Generative Buryuy of (201) 212-2312 or visit to vertice of <u>http://www.cop.ucea.apc/</u>.

Base map information shown on this FIRIT was provided in digital format by Orange County, Floxida

This map reflects more detailed and up-to-deta upteen channel configurations lives free about as the gravitics FIRM for this probability. The finalgians and focularly that user transformed has the periodic FIRM may have been addeeded to use Finishery East States a new fixed paratises, the a result the Final Politics addressible place bases a new fixed paratises, the a result the Final Politics addressible place bases and new fixed paratises and a strend the Final Politics addressible place bases and may reflect stream channel doctances that offer from what is stream on this map.


Opported limits show on this map are based on the best data available at the time of publication. Because sharings due to antereasting or disastematices may have cocurred when this map was publicated, map users should contact appropriate community difficults to write comme companies and locations.

Please where to be separately primited Map lades for an overview map of the coverty showing the signal of map panels, community map repositivy addresses, and a Lades of Communities with counting National Place's Insurance (Program date Interents community as well as a lating of the panels on which each community is located.


Conset the FEMA Hep Service Cester at LADO 304.0015 for externation an available products associated with this FEM. Available products may include provincing double Labers of Bog Change a FeMa Insurance 2004, report address doptar versions drifter may The FEMI Map Service Center may also be reached by Fixe of LADO 316-0201 and in weaked or the Lanes may labor and.

If you have questions about this map or questions instraining the National Point Insurance Program is questio, please call NATY-PERA MAP (1-627-335-3627) or val the PEAM website at <u>http://www.homa.godiscienceshifut</u>.

Watershed Name	Minimum Conversion	Centrevalen	Avetage Convension	Offsel
By Contributions River	-1.63	+110	-1.09	0.08
Repp Cost	-0.91	18.28	-0.00	0.05
Cypress Creek	-087	-696	-0.8	0.02
Avend Branch	-0.00	-1.00	-0.8	0.07
Later Aprophie	-447	-4#	-0.01	0.06
Laterial	-0.87	-1.27	-1.02	0.00
the Cost of Advances Baser	-097	- 18	-101	1009
the lower is they	-0.91	-1.10	-0.09	0.07
Ready Draik	-496	-649	-0.8	0.02
Shings Oracl	-6.08	-6.65	-0.91	0.04
D Jame Kuer	-158	+1.30	10.58	6.76
visite liter	-0.08	+1.00	-684	1.07



18



This need is for use is appreciating the narrowal Flored Insurance Frequent. It deep not exceeded, sheetly at a ware subject to finding, performing the load sheetly provide at the text of the submething way expendings while the controlled to provide control or appropriation of again intermetion.

To data on one obtaines interruption and interruption termination in the state Recot Elevations (RFFst and/or Roomways name even distantaned, users are ensuringed to consert the Flora Hordrey and Possnays (Lata and/or Statianes) of Stituates tervisions, tables contained activity tervisions interruption (Flora) report tervisions (Lates stockase and tervisions) such as a stock for the MRR interpret ensured version tervision elevations. There B/Fst are removed for tool insulator (allos) personal work tool elevations. There B/Fst are removed for tool insulator (allos) personal work tool elevations. There B/Fst are removed for tool insulator (allos) personal work tool and/or allos (and to personal on the TFS) report hereit and and and the Apertments, tool and the stock of the TFS report hereit is insulator (allos) personal store tool and the personal on the TFS report hereit is an advertised on tool and the second store for the TFS report hereit is an advertised on the FIRM for parceses of construction account for construction and provide and the second second for the terror becomes and the second second tool and the terror of the TFS report hereit is an advertised on the FIRM for parceses of construction account for construction and persons and the terror of the terror becomes and the terror of terror of the terror of te

Constant Base. From Elevations: theorem on this map apply only borewards of  $b^{\prime} d^{\prime}$  from American Varians Dalum of 1556 (2000) Sections at this FRM second boremark to the second bore analysis from the second bore and the production base in the from transmission base in the from the transmission base in the from transmission based on the from transmission based on the from the transmission based on the from the transmission based on the from the transmission based on the transmission based on the from the transmission based on the first transmission based on the transmission based on transmission based on the transmission based on

Boundarian of the **floodways** were computed at times sections and interclated between energy factors. The floodways were concearing mataxing conservators were regard to requestion of the Subtrational Food Instance Pergana. The Stockay werter and other perteent licensity data are previous in the Pood Instance Stock report in the section of the se

Contain areas not in Special Pland Hazard Areas may be protected to **Read context** structures. Role: to Sector 2.4 "Food Postector Measures" of the Flood Inspector Budy report for information in flood control ideatives for this jurisdiction

Discessors in patient spherical projection or 1704 zonas used in the production of Tablits for adjacent productions may leave in suppl positional differences in map events above prediction leaved as so . These statistics coincer areas the acturity

Figure elevations on this map are informed to the North American Vertical Datas of 1986. These final environments and its compared to structure and ground environment informance to the same vertical datas. For information registrating conversions between the flations: December Vertical Datas of 1950 and the North American Vertical Datas of 1986, vol. the National Geodetic Survey and the fully another in the National December of the National December (Survey at the fully another another in the National December Survey at the fully another in the National December of National December (Survey at the fully another in the National December of Survey at the fully another in the National December of Survey at the fully another in the National December of Survey at the fully another in the National December of Survey at the fully another in the National December of Survey at the fully another in the National December of Survey at the fully and the Survey at the fully and the Survey at the fully another in the Survey at the fully and the Survey at the fully ful

Spatial Reference System Decem National Geodetic Burvey, MCM Silver Spring Mercs Center 1015 East-West Highway Silver Spring, Maryand 2010 (2010)713-3181

To obtain survert allocation, description, and/or totalion information for **baseb marks** shown on the map, glospe contact the information Services Stanch of the National Genetics Survey of (SPI()/FG-GND in visit is network of <u>http://www.rgs.coma.gov</u>.

Base map information shown on this FORM was provided in digital formed by Orange County Enrols

hoodways that were transported from the previous intro may have been explored to carbina its black mere transported annah configurations. As a secure, the four Palake and Fracture, Cuta tostes in the Face brainface (budy recent which confishing


Corporate limits shown on this map are based on the best data available at the time Monton. Because charges due to annexations or de annexations may have not after this may was published, may come should contact appropriate water difficult to well commentioned and transformed


Please starts to the separatery pricted Map lades for an overvey-map of the county showing the legislat of map panels, community map reporting addresses, and a lasting of Communities label containing National Pland Imsumme Program sales for each structure that we late a lasting of the panels on which each summarity is


Conset the FBMA Map Service Ceder at 1.000.305.0016 for extension on available products associated with this FBM. Available products may include provincing Social Latens of Map Carage a Filed Insurance Social Volume (Ceder digital environs drifte may Tex FDBs Map Service Ceder may also be reached by Fau of 1.000.356.072 and its weeks or <u>the Service Ceder not</u>.

If you have questions about this map or questions concerning the National Point Insurance Program in general, please call **54174EBA MAP** (14/27-335-2827) or valid the PEMA variable in <u>International professionality</u>.

Watershed Name	Mainum	Maximum Conversion	Average Conversion	Offsel
By Controlitation Row	-1 (2)	-110	-1.09	0.08
Inpar Dent		-5.88	-0.00	0.00
Cases Cent	-0.87	-697	-0.0	0.02
-hand Branch	-0.00	100	-0.8	0.07
Law Apoka	-047	4#	-08	106
Laterial	-0.07	-1.07	-1.02	0.00
the Spendorshine liver	-4987	-187	-101	8.00
the steep they	-0.91	110	-0.00	1007
Reeds Dank	-496	-040	-0.8	0.02
Shinge Creak	-0.00	-0.95	-041	0.04
St Jame Ruer	-1 58	+1.30	10.04	616
Vesta Ruar	-0.48	+1.00	-0.04	447







## RS&H, Inc. FPID: 44616412201

FLOODPLAIN IMPACT VOLUME CALCULATIONS

By:	AB
Date:	10/18/2022
Checked:	ENS
Date:	11/9/2022

Location:	1
Alignment:	SR 429
Beginning Station:	125+60
End Station:	141+00
Side:	LT

Elevation (ft)	Area (ac)	Incremental Volume (ac-ft)	Cumulative Volume (ac-ft)	Comments
101.4	0.59		0.00	SHWT = 101.37 (permit)
		0.37		
102.0	0.59		0.37	
		0.59		
103.0	0.59		0.96	
		0.59		
104.0	0.59		1.55	
		0.59		
105.0	0.59		2.14	
		0.59		
106.0	0.59		2.73	100-year BFE (Zone AE)

Note: Permit data associated with ERP No. 49-187636001

## RS&H, Inc. FPID: 44616412201 FLOODPLAIN IMPACT VOLUME CALCULATIONS

By:	AB
Date:	10/18/2022
Checked:	ENS
Date:	11/9/2022

Location:	3
Alignment:	SR 429
Beginning Station:	287+80
End Station:	296+00
Side:	LT

Elevation (ft)	Area (ac)	Incremental Volume (ac-ft)	Cumulative Volume (ac-ft)	Comments
105.0	0.14		0.00	SHWT = 100.80 (Permitted Pond 2A-3)
		0.14		
106.0	0.14		0.14	
		0.14		
107.0	0.14		0.28	100-year BFE

Note: Permit data associated with ERP No. 49-187636001

#### RS&H, Inc. FPID: 44616412201 FLOODPLAIN IMPACT VOLUME CALCULATIONS

By: AB Date: 10/18/2022 Checked: ENS Date: 11/9/2022

Location:	5	
Alignment:	SR 429	

Beginning Station: 485+60 End Station: 489+20 Side: LT/RT

Elevation (ft)	Area (ac)	Incremental Volume (ac-ft)	Cumulative Volume (ac-ft)	Comments
100.0	0.06		0.00	SHWT = 100.00 (permit)
		0.06		
101.0	0.06		0.06	
		0.06		
102.0	0.06		0.11	
		0.01		
102.2	0.06		0.12	100-year BFE (permit)

Note: Permit data associated with ERP No. 49-187636001

## APPENDIX E – POND SITE EVALUATION MATRIX

Pond Siting Report Widening Western Beltway PD&E Study from Interstate 4 to Seidel Road Florida's Turnpike Enterprise Financial Project ID 446164-1-22-01

# APPENDIX F – CORRESPONDENCE, MEETING MINUTES, AND EXCERPTS FROM PREVIOUS PERMITS AND STUDIES

Pond Siting Report Widening Western Beltway PD&E Study from Interstate 4 to Seidel Road Florida's Turnpike Enterprise Financial Project ID 446164-1-22-01



## Florida Department of Transportation

RON DESANTIS GOVERNOR Florida's Turnpike Enterprise P.O. Box 613069, Ocoee, FL 34761 407-532-3999 KEVIN J. THIBAULT, P.E. SECRETARY

#### MEETING MINUTES FTE/FDEP PRE-APP COORDINATION MEETING Poinciana Parkway Extension PD&E Study from CR 532 to North of I-4 FPID No.: 446581-1-22-01 Western Beltway (SR 429) Widening PD&E Study from North of I-4 to Seidel Road FPID No.: 446164-1-22-01

Osceola and Orange Counties County, Florida Monday, April 11, 2022, 9:00 am

#### I. Attendees:

#### FTE

Henry Pinzon (PD&E) Rax Jung (Project Dev. Engineer/EMO) Philip Stein (Environmental) Annemarie Hammond (Environmental Permits Coordinator) Erin Yao (Drainage Engineer)

#### FTE/GEC

Stephanie Underwood (PM/HNTB GEC) Fred Gaines (Permitting/Atkins GEC) Adriana Kirwan (Drainage/HNTB GEC) Tiffany Crosby (Senior Scientist/Atkins GEC)

#### **FDOT Central Office**

Jonathan Turner (Project Delivery Coordinator)

#### FDEP

Teayann Duclos (Environmental Manager) Jennipher Walton (Env. Specialist) Leo Anglero (ERP/Stormwater) Allan Popak (Environmental Specialist) Lindsay Furr (Environmental Consultant) Jill Farris (Environmental Consultant)

#### **RS&H** Team

Douglas Reed (RS&H PM) Erik Scott (RS&H Drainage) Sarah Johnson (KHA/Environmental)

#### **FDOT District 5**

Casey Lyon (Env. Permits Coordinator)

#### II. Introductions

The meeting started with FDOT District 5 discussed their projects with FDEP. After attendees were introduced, Stephanie Underwood explained the purpose of the meeting was to initiate pre-application coordination with the Florida Department of Environmental Protection for the two Project Development and Environment (PD&E) studies.

#### III. PowerPoint presentation

Erik Scott explained the two projects with a PowerPoint presentation and separate exhibits (attached). Discussion is summarized below.

#### Widen Western Beltway PD&E Study:

• The PD&E study was summarized, including existing conditions and the proposed widening of SR

429 from four to eight-lanes from north of I-4 to Seidel Road. Improvements are also proposed at the existing interchanges at Sinclair Road, US 192, Western Way, and Seidel Road. A new interchange is proposed at Livingston Road. It was noted that this is early in the process in the PD&E phase, and not the Design phase, so a permit application is not imminent.

- FDEP and Reedy Creek Improvement District (RCID) permitted SR 429 in 2001. FTE is coordinating with RCID.
- The existing water quality volume was calculated based on the criteria of 1-inch over the contributing basin or 2.5-inches over the impervious area. For most of the basins the 1-inch over the contributing area was the controlling factor for the required water quality. This is due in part because the existing corridor was in located within a rural corridor and offsite areas were included in the contributing basin calculation. Since 2001, some of the offsite areas have been developed with new, offsite ponds. Therefore, when adding the additional pavement along SR 429 for the eight-lane configuration, most of the basins still have sufficient water quality volume provided in the existing ponds. For any basins lacking the required water quality volume within the existing permitted ponds, the difference will be accommodated by adjusting the existing control structures or providing additional pond area.
- Basin boundaries will be revised to reflect the development adjacent to SR 429.
- The project study area is located within two impaired WBIDs, Davenport Creek for bacteria and Whittenhorse Creek for dissolved oxygen. In addition, the project study is located within the Lake Okeechobee Subwatershed BMAP. FTE believes that additional treatment is not required given FDOT BMPs include a series of treatment trains and their facilities do not directly discharge into the impaired waterbodies. FDEP stated that additional treatment considerations may not be necessary because they are moving away from the 50% additional treatment volume but will need to be discussed further during the design phase.
- Attenuation will be provided per FDEP criteria for open and closed basins, with consideration for RCID requirements.
- FDEP agreed this stormwater approach is reasonable.
- The corridor has floodplains associated with Boggy Creek and Whittenhorse Creek. There is one existing Floodplain Compensation site located north of Indian Creek Boulevard adjacent to the southbound lanes. Though encroachments are anticipated, they will be minimal. Encroachments will be mitigated by compensation sites or by using the importer/exporter method.
- FTE confirmed with FDEP that the Environmental Resource Permit (ERP) for widening of Western Beltway (SR 429) will be handled by FDEP. This includes the 404 permit.
- Wetland lines from the previous permit will be used as much as possible in areas that are not new interchanges. Direct wetland impacts are approximately 10 acres.
- Conservation easements are located within the project study area.
- Wetlands and conservation easements impacts will be avoided and minimized as much as possible. Some minimization methods considered include bridging or MSE walls.
- Impacts to most species is minimal along the existing roadway; however, there is suitable sand skink habitat to be considered especially within the new interchange area.
- Mitigation banks are located within the available service area for this project to offset any unavoidable wetland impacts.
- Coordination with USFWS for species involvement occurred in 2021.
- There were no questions, but if any questions arise, additional coordination can occur.

#### Poinciana Parkway Extension PD&E Study:

• The PD&E study was summarized, including existing conditions; the proposed new six-lane expressway on new alignment; and interchanges at CR 532, I-4, and Sinclair Road. The new

alignment crosses Davenport Creek on bridge structure.

- There are two alternatives, but the worst-case Alternative 1 was discussed.
- FTE clarified with FDEP that they anticipated that SFWMD would be responsible for issuing the ERP and FDEP would be responsible for reviewing and issuing the 404 permit.
- The team depicted the wetlands and conservation areas within the study area.
- Wetland lines from the previous permits will be used as much as possible in existing roadway areas; new wetland lines will be set in the new alignment area. Direct wetland impacts range from 131 acres to 141 acres for the alternatives. Approximately 130 acres of direct impacts will be minimized with bridges and MSE walls.
- Conservation easements for RCID and Reunion are present within and adjacent to the project study area.
- Wetlands and conservation easements impacts will be avoided and minimized as much as possible. Some minimization methods considered include bridging or MSE walls.
- FTE has already met with USFWS in October 2020 and again in October 2021. A scrub jay survey was completed in October 2021, however; there were no observations of scrub-jays as a result of the survey. Suitable sand skink habitat is located within the project study area and sand skink tracks were observed during pedestrian transects.
- We will coordinate with FWC for state-listed species.
- Mitigation banks are located within the available service area for this project to offset any
  unavoidable wetland impacts. FDEP confirmed with FTE that mitigation banks should be utilized
  for wetland mitigation as the 1<sup>st</sup> priority and followed by other options after this measure.
  Impacts to conservation easements should be a last resort. Should the release of a Conservation
  Easement or an impact to a Conservation Easement be necessary, FDEP has asked that FTE
  coordinate with FDEP early in the design development given the process is different than that of
  mitigation banks.
- FTE indicated that the avoidance and minimization measures mentioned previously is standard and considered adequate; FDEP indicated that FTE is on the right track

#### MEETING MINUTES FTE/RCID AGENCY COORDINATION MEETING Poinciana Parkway Extension PD&E Study from CR 532 to North of I-4 FPID No.: 446581-1-22-01 Western Beltway (SR 429) Widening PD&E Study from North of I-4 to Seidel Road FPID No.: 446164-1-22-01

### Osceola and Orange Counties County, Florida Wednesday, May 19, 2021, 1:00 pm

#### I. Attendees:

Henry Pinzon	Erin Yao	Rax Jung (FTE Project	Douglas Reed
(FTE PD&E)	(FTE/Drainage)	Dev. Eng./EMO)	(RS&H PM)
Stephanie Underwood	Doug Zang	Annemarie Hammond	Erik Scott
(FTE PM)	(FTE/Environmental)	(FTE/Env. Permit Coordinator)	(RS&H Drainage)
Ramon Breton	Fred Gaines	Clif Tate	Sarah Johnson
(KHA, DPM 446581)	(FTE/Permitting)	(KHA/Engineering)	(KHA/Environmental)
Adriana Kirwan		Kate Kolbo	
(FTE/Drainage)		(RCID Planning/Engineering)	

## II. Introductions

Stephanie introduced the Florida Turnpike Enterprise (FTE) staff and explained the purpose of the meeting was to coordinate with the Reedy Creek Improvement District (RCID). RS&H team staff was introduced followed by the RCID staff. John Classe (RCID District Administrator and Sam Dewes (RCID Roadway) were not in attendance.

### III. PowerPoint presentation

Doug Reed went through a PowerPoint presentation (attached), which was sent to RCID after the meeting. Discussion is summarized below.

a. Slide 7: Kate Kolbo explained that there are no set procedures if the Wildlife Management Conservation Area (WMCA) is impacted. It was set up in 1966 as a major floodway to never be impacted. Although two crossings were anticipated, including I-4. Poinciana Parkway would also be an exemption. However, there cannot be any adverse impacts to the existing flow rates. Most flows are north to south, except for Reunion which flows south to north. Major cross drains will be required along the utility "stair step" area to maintain flows.

Sarah Johnson pointed out the two graphics were slightly different and asked which one is correct. Kate Kolbo will send the CADD file for the correct WMCA limits to Stephanie Underwood, who will distribute it to the team. Kate mentioned that they use a different datum and they will convert it to NAVD88 before sending.

Fred Gaines asked if any easements had been transferred to other owners. Kate responded that none had been transferred.

b. Slide 15: Kate indicated that the system is well defined. The cross section is fixed, canals cannot be widened, and drainage structures cannot be modified. Therefore, the flow cannot be increased. Any additional runoff must flow elsewhere. Stephanie Underwood suggested pre-post flows should be ok. Kate responded that it may not

be, depending on the definition off pre-post, but she will send the stipulations to Stephanie. The Reedy Creek system is based on 13 cfm/sq mile, and they are already exceeding that volume. Anything over that will require a fee. Kate mentioned that I-4 Beyond the Ultimate (BtU) project is attenuating to below the pre-post volume.

Fred Gaines mentioned that Turnpike had already paid a fee for SR 429 during the original construction.

Erik Scott asked about the permit process. Kate responded that a SFWMD permit application should be sent to RCID first for review and approval before being submitted to South Florida Water Management District (SFWMD). RCID will then send SFWMD a letter explaining the negotiation points and expressing support.

Kate mentioned that RCID uses a different rainfall distribution than SFWMD with a 50 yr/72 hr event. Erik asked about the unit hydrograph, and Kate will send Stephanie the RCID drainage person's contact information who can provide the information.

Erik mentioned we anticipate staying below the 290 cfs that was used previously. Kate will pull the permit and modifications can be worked through. Kate also mentioned they would require an initial 30-day review period to provide comments or questions. The Turnpike's team will provide information for RCID to feed into the model. Kate also mentioned they will review the projects even if outside the RCID boundary as long as it is within the watershed.

Erik asked if there were any other entities that were interested in taking additional water. Kate responded that there were none.

Fred asked if RCID can provide conceptual approval since this is PD&E and we are not submitting an actual permit until a later phase. Kate responded that conceptual approval can be granted.

The bottom line was reiterated:

- Stay out of the WMCA, and
- Do not discharge more flow into RCID

### IV. Action Items

- a. Doug Reed will prepare meeting minutes. (done)
- b. Kate Kolbo will send the CADD files for the correct WMCA limits and flow stipulations. (done)

#### MEETING MINUTES FTE/RCID AGENCY COORDINATION MEETING #2 Poinciana Parkway Extension PD&E Study from CR 532 to North of I-4 FPID No.: 446581-1-22-01 Western Beltway (SR 429) Widening PD&E Study from North of I-4 to Seidel Road FPID No.: 446164-1-22-01

## Osceola and Orange Counties County, Florida Thursday, March 3, 2022, 10:00 am

#### I. Attendees:

Henry Pinzon	Todd Rimmer	Rax Jung (FTE Project	Douglas Reed
(FTE PD&E)	(Walt Disney Planning)	Dev. Eng./EMO)	(RS&H PM)
Stephanie Underwood	Emam Emam	Philip Stein	Erik Scott
(FTE PM)	(FTE/Planning/Traffic)	(FTE/Environmental)	(RS&H Drainage)
Ramon Breton	Fred Gaines	Clif Tate	Matt Betancourt
(KHA, DPM 446581)	(FTE/Permitting)	(KHA/Engineering)	(RS&H Public Inv.)
Katherine Luetzow	Sarah Johnson	Kate Kolbo	Rick Langlass
(RCID)	(KHA/Env)	(RCID Planning/Eng)	(RS&H DPM/Eng.)
Sandy Morales (RCID)			

### II. Introductions

Stephanie introduced the Florida Turnpike Enterprise (FTE) staff and explained the purpose of the meeting was to continue coordination with the Reedy Creek Improvement District (RCID) on the two PD&E studies. The RS&H team and RCID was also introduced.

### III. PowerPoint presentation

Doug Reed went through a PowerPoint presentation. Discussion is summarized below.

Poinciana Parkway Extension PD&E Study and Drainage Design: Erik Scott outlined the anticipated worst—case encroachment into Whittenhorse Creek with the proposed 8-lane typical. Kate Kolbo requested the hydraulic model FTE is using to evaluate the HGL. RS&H does not anticipate any changes to the Boggy Creek culvert. Davenport Creek will be bridged

Kate Kolbo indicated that FTE is not required to use a specific hydraulic model, but all modeling (electronic executable files) would need to be submitted for RCID review.

Todd Rimmer indicated that the CADD files would be requested from Mattamy Homes for the Celebration Island Village site plan.

Erik Scott requested the RCID model for use. Kate Kolbo agreed to send it after the meeting.

Kate Kolbo suggested the permit request should be submitted to RCID before submitting to the South Florida Water Management District (SFWMD).

The fee structure of \$4.15 per acre/csm is still applicable. The \$200/acre is also still

applicable for the portion of the project located within the RCID boundary if runoff drains into RCID. The original permits will be reviewed and fees will be assessed based on the improvements.

It was noted that the easements are water management first and foremost, then wildlife conservation.

Todd Rimmer asked if the two Poinciana Parkway Extension alternatives operate similarly. The response was yes, the configuration differs, but operations are similar. Todd also suggested the relocation of utilities be included in the evaluation and footprint.

Historical storage must be preserved as this area serves a large area of Osceola and Orange counties. Flood storage is critical.

Kate Kolbo will send the latest GIS files for the most up to date information on the jurisdictional and water management conservation area limits. A separate meeting can be set up to go through the information.

#### Widen Western Beltway PD&E Study:

Todd Rimmer indicated they are looking at 2040 traffic models for Western Way due to its connection into Lake County. Emam Emam indicated he can share the Synchro files which have been coordinated with District 5 and FDOT Central Office.

Bike and pedestrian facilities can be removed from Western Way since other means (i.e. shuttles) are being incorporated by Disney for bike and pedestrian accommodations. This will ultimately be safer due to the free flow ramp movements.

RCID is evaluating widening Western Way to six lanes. Funding is included in the 10-year plan.

It was noted that Disney was not invited to the Reunion Coordination meeting scheduled for March 10, 2022.

In general, it was agreed that Poinciana Parkway Extension Alternative 2 has reduced direct and indirect impacts to RCID resources compared to Alternative 1.

#### IV. Action Items

- a. Doug Reed will prepare meeting minutes. (done)
- b. Kate Kolbo will send the RCID model.
- c. Stephanie Underwood will send the HEC-RAS and Synchro models.